Tip: Connect your appliance to a mobile device. You can conveniently change all settings via the Home Connect app.

- 1. Install the Home Connect app on your mobile device and follow the instructions.
- 2. Scan the QR code using the Home Connect app.



Ì

⋇

 $/\!\!/$

Get IT ON Google Play

ore	manual.	
	Hardness	mmol/l
	Soft	0-1.1
78 I	Soft	1.2 - 1.4

Adding special salt Ξ

programme starts.

and remove.

Adding detergent

1. Add the detergent to the

dry detergent dispenser.

water.

be selected here.

Overview of water hardness settings

Setting

value

H:00

H:01

To avoid damage to the appliance, only add special

salt to the dispenser for special salt just before the

1. Unscrew the lid of the dispenser for special salt

2. On initial start-up: Fill the dispenser right up with

You can find an overview of the Medium 1.5 - 1.8 H:02 water hardness values that can Medium 1.9-2.1 H:03 2.2 - 2.9 Medium H·04 A table of country-specific units 3.0 - 3.7 Hard H:05 can be found in the instruction Hard 3.8 - 5.4 H:06

5.5 - 8.9

Hard

H:07

Setting the water softening system

1. Press ⁽¹⁾.

- 2. To open the basic settings, press Setup 3 sec. for 3 seconds.
- ✓ The display shows H:xx.
- The display shows set.
- 3. Press or + repeatedly until the right water hardness has been set.
- 4. To save the settings, press Setup 3 sec. for 3 seconds.

The programme data has been measured in the laboratory according to European standard EN 60436. The consumption figures depend on the programme and additional function selected.

Programmes

The runtime will change if the rinse aid system is switched off or rinse aid needs to be added.

Programme	1) Duration [h:min] 2) Energy [kWh] 3) Water [l]
	1) 2:05 - 2:15
Intensive 70°	2) 1,300 - 1,400 3) 11,5 - 14,0
Auto 45-65°	1) 1:40 - 2:45 2) 0,900 - 1,500 3) 7,0 - 15,5
Eco Eco 50°	1) 4:55 2) 0,920 3) 9,5
B	1) 4:00 2) 1,050
Silence 50 ¹	3) 11,0
Glass 40°	1) 1:33 - 1:38 2) 0,800 - 0,850 3) 12,0 - 14,0
(1h)	1) 1:00 2) 1,300
Express 65° - 1h	3) 10,5
Êg	1) 0:29 ² 2) 0,800
Express 45°	3) 10,5

half standard load

Adding rinse aid st	
 Press the catch on the lid of the dispenser for rinse aid ① and lift ②. 	

2. Add rinse aid up to the max mark.

2. Close the lid of the deter-

gent dispenser. The lid clicks into position.

3. Add the special salt to the

dispenser. The water in the

dispenser is displaced and

forced out. Never add de-

tergent.

close.



CLICK

3. Close the lid of the dispenser for rinse aid. The lid clicks into position.

4. Place the lid back on the dispenser and turn to

en

Dishwasher

guide

Quick reference

How to use your appliance

1. Load the tableware.

Only clean tableware that is suitable for dishwashers. Remove large remnants of food from the tableware. Check that the spray arms can ro-

- tate freely.
- 2. Add detergent.
- 3. Switch on the appliance O.

4. Select the programme.


50 m

25 m

- 5. Start the programme Start.
- 6. Remove the tableware at the end of the programme.
- 7. To cancel the programme, press Reset 4 sec. for approx. 4 seconds. The programme is cancelled and ends after approx. 1 minute.

Cleaning filters

- 1. After each wash check the filters for residue.
- 2. Turn the coarse filter anticlockwise ① and remove the filter system ②.



3. Pull down the micro filter to remove.

)



- 5. Clean the filter elements under running water.
- $\textbf{6.} \ \text{Re-assemble the filter system}.$
- Insert the filter system into the appliance and turn the coarse filter clockwise. Make sure that the arrow markings match up.

leaning	spray	arms


4. Insert the lower spray arm.The spray arm clicks into position.

- **1.** Unscrew the upper spray arm ① and pull down to remove ②.
- 2. Pull up the lower spray arm to remove.

3. Check the outlet nozzles on the spray arms for blockages un-

der running water and remove any foreign bodies.

5. Insert the upper spray arm and screw it firmly in place.



Clean wastewater pump

- **1.** Disconnect the appliance from the power supply.
- **2.** Remove the filter system.
- **3.** Scoop out any water.
- **4.** Prise off the pump cover using a spoon and grip it by the crosspiece.



- **5.** Lift the pump cover inwards at an angle and remove.
- **6.** Remove any remnants of food and foreign bodies in the area of the impeller.
- 7. Insert the pump cover ① and press down ②.
- The pump cover clicks into position.



8. Install the filter system.

Troubleshooting

Cumply head is biglight		Cause and troubleshooting	Fault	Cause and troubleshooting
Supply hose is kinked. ► Install the supply hose without kinks.	E:92-40 will light up al- ternately.	Filters are soiled or blocked. Clean the filters.	Removable streaks are present on glasses, glass- ware with a metallic ap- pearance and cutlery. Rust spots on cutlery.	Amount of rinse aid to be dispensed is set too high.Set the rinse aid system to a lower setting.
Water tap is turned off. Turn on the water tap.	ternately.	Wastewater pump is blocked. Clean the wastewater pump. 		No rinse aid has been added. ► Add rinse aid.
 Water tap is jammed or furred up. Turn on the water tap. The flow rate must be at least 10 l/min when the water sup- 		 Cover of the wastewater pump is loose Secure the cover of the Wastewater pump so it clicks into position. 		Cutlery is not sufficiently rust-resistant. Knife blades are often more severely affected. • Use rust-resistant tableware.
 ply is open. The filters in the water connection of the supply or AquaStop hose are blocked. 1. Switch off the appliance. 2. Pull out the mains plug. 3. Turn off the water tap. 4. Unscrew the water connection. 5. Remove the filter from the supply hose 	 Remnants of food on tableware. Tableware is placed too close together or basket is overfilled. Arrange tableware with sufficient space in between. The spray jets must reach the surfaces of the tableware. Avoid points of contact. Spray arm rotation is blocked. Arrange tableware so that it does not obstruct spray arm rotation. Spray arm nozzles are blocked. Clean the Spray arms. Filters are soiled. Clean the filters. Filters are inserted incorrectly and/or not engaged. Insert the filters. Washing programme selected too weak. Select a more intensive washing programme. Adjust the sensitivity of the sensors. 		Cutlery may also rust if washed together with rusting items. Do not wash rusting items.	
			Detergent residue is present in the detergent dispenser or the tablet collecting tray.	 Spray arms were blocked by tableware so detergent was not rinsed out. Check that the spray arms are not blocked and can rotate freely.
		Arrange tableware so that it does not obstruct spray arm ro-		
		1. Insert the filters properly.		
 Re-insert the filter in the supply hose. Screw the water connection back on. Check the water connection for leaks. Restore the power supply. 		 Select a more intensive washing programme. 		
	 Turn on the water tap. Water tap is jammed or furred up. Turn on the water tap. The flow rate must be at least 10 I/min when the water supply is open. The fliters in the water connection of the supply or AquaStop hose are blocked. Switch off the appliance. Pull out the mains plug. Turn off the water tap. Unscrew the water connection. Remove the filter from the supply hose Clean the filter. Re-insert the filter in the supply hose. Screw the water connection back on. Check the water connection for leaks. 	 Turn on the water tap. Water tap is jammed or furred up. Turn on the water tap. The flow rate must be at least 10 l/min when the water supply is open. The filters in the water connection of the supply or AquaStop hose are blocked. Switch off the appliance. Pull out the mains plug. Turn off the water tap. Unscrew the water connection. Remove the filter from the supply hose Clean the filter. Re-insert the filter in the supply hose. Screw the water connection back on. Check the water connection for leaks. Restore the power supply. 	 Turn on the water tap. Water tap is jammed or furred up. Turn on the water tap. The flow rate must be at least 10 l/min when the water supply is open. The filters in the water connection of the supply or AquaStophose are blocked. 1. Switch off the appliance. 2. Pull out the mains plug. 3. Turn off the water tap. 4. Unscrew the water connection. 5. Remove the filter from the supply hose. 6. Clean the filter. 7. Reinsert the filter in the supply hose. 8. Screw the water connection back on. 9. Cheas the water connection to relaxs. 10. Restore the power supply. 	 Turn on the water tap. Clean the waster tap. Clean the wastewater pump. Clean the wastewater pump. Cover of the wastewater pump is loose Secure the cover of the Wastewater pump so it clicks into position. Secure the cover of the Wastewater pump so it clicks into position. Remnants of food on tableware. Switch off the appliance. Avoid points of contact. Secure the water connection. Secure the filter from the sup-ply hose. Clean the filter. Reinsert the filter in the supply hose. Screw the water connection for leaks. Clean the filters. Reinsert the filter in the supply hose. Screw the water connection for leaks. Clean the filters. Arrange tableware supply.