

Contents

Introduction

Ovens

- Features Unique to Bosch
- Buying Guide
- Range Information

Hobs

- Electric Hobs
- Know your Hobs
- Features Unique to Bosch
- Range Information
- Gas Hobs
- Features Unique to Bosch
- Range Information
- Domino Hobs
- Range Information

Hoods

- The Right Hood
- Recirculation VS Ducted Systems
- Features Unique to Bosch
- Range Information

Every detail of every appliance has been carefully designed, produced and tested by our engineers to fully satisfy the highest standards in quality, performance and convenience. The result is cutting-edge technology, timeless design and remarkable ease of use, reducing the workload for you in the kitchen and consistently delivering perfect results.



Why choose Bosch?

Proven quality

Bosch appliances offer premium quality, advanced technology, ease of operation and outstanding German made and engineered technology. These attributes have earned us many national and international accolades, such as the reddot Design Award, the iF product design award and other endorsements, year after year.





Top performance

What drives us every day is our desire to improve. We strive to make the best even better, by developing functional, durable and energy-efficient innovations that surpass all expectations.

Maximum convenience


Bosch is dedicated to making your life easier. Our innovative built-in appliances are easy to use, while sophisticated features deliver the best results every time, saving you time and effort.



The Intuitive Control Ring: Turn your dream dishes into reality, easily.



Everything you need at hand: our new, intuitive control ring makes cooking easier than ever. With just a small turn of the stainless steel ring, you can adjust any of your oven's settings. The TFT-touch display, with its clear and straightforward design, guides you through the various menu options. This gives you full control over your dishes at all times and everything succeeds with ease.



Become a master chef, at the touch of a button.



Bosch Assist

You could easily search through cookbooks and family recipes without ever finding the exact temperature or cooking time for that favourite dish. Thanks to Bosch Assist, you don't have to.


The advanced sensor technology found in PerfectRoast and PerfectBake™ – combined with the functionality of automatic programs as we know them today - offers an extensive menu of food categories that help create your perfect meal.



No more guesswork needed while baking

Baking perfect bread and pastries typically involves careful setting of heating modes, temperatures baking times and constant monitoring. Baking enthusiasts can consider a Bosch oven with PerfectBake sensors that measure and regulate the baking process automatically.

Simply select Assist and the type of dish such as cake and press start, your oven will do the rest. The result: bread, cake and pastries baked to perfection.





Get the perfect roast without monitoring closely

Whether it's poultry, meat or fish – with the PerfectRoast meat probe, you'll get perfect results every time. Through 3 highly sensitive measuring points, the probe determines the core temperature of your roast to the exact degree and second, guaranteeing perfect roasting results.

Simply insert the meat probe into your roast and select type of dish such as poultry and press start, your oven will do the rest. Another benefit: you can also use the meat probe in the microwave and steam oven mode.



Steams so gently, even vitamins stay for dinner.

There is no healthier or tastier way to prepare food than in a Series 8 steamer or combination steam oven.

Preserving vitamins and minerals

Dishes that are cooked in hot steam not only retain their vitamins and minerals, but also their full, natural flavour. So you can go easy on the extra seasoning, and use much less salt when cooking.

No transfer of smell

With the Series 8 steamer, you can prepare an entire set menu using up to three levels at once. Salmon with asparagus and rosemary potatoes? Cook them all together and everything will turn out perfectly. Need to prepare dessert, too? Thanks to the moisture in the oven, there's no intermingling of flavours – each dish retains its own authentic flavour.



Other steam functions



Reheating

At 90 - 95°C, food is gradually reheated to taste as if it was freshly cooked.



Added steam function

Enhance your cooking results by adding a little bit of moisture from time to time, thanks to the added steam function. Whether you're reheating dishes, proving dough, baking or roasting, you can set the oven to automatically add bursts of steam, or you can add steam manually to regulate the intensity. Added steam works with: 4D Hotair, Hot air grilling, Top and bottom heating and Keep warm feature.



Drying Function

Drying option enables to dry the internal after steam usage.



The versatility of all in 1 solution.

With the Bosch Series 8 combination oven(s), you can do various types of cooking such as baking, steaming or microwaving.

For a combination steam oven, it combines the benefits of pure steam cooking and functions of a conventional oven which give your roasts and home-made bread a crispy finish.

You can also add speed to your traditional cooking process without comprising on taste while using the combination microwave ovens.

Bosch Combination ovens provide convenience and help achieve improved food results.

Perfect heating modes to meet your every cooking need.

Perfect baking and roasting not only requires the right temperature, but also the appropriate heating function, too. From 4D Hotair to Hotair Eco, Bosch ovens offer heating functions that deliver everything from haute cuisine to everyday feasts.

	What does it do?	Recommended for
4D Hotair [^]	For baking and roasting on one or more levels. The fan distributes heat from the ring heating element in the back panel evenly around the cooking compartment. You can also bake and roast up to 4 different levels simultaneously.	Cakes and small baked items (Muffins, biscuits)
Hotair Eco	For energy-optimised cooking of selected dishes on one level without preheating. The fan distributes the energy-optimised heat from the ring heating element in the back wall evenly around the cooking compartment.	Cakes and small baked items (Muffins, biscuits)
Top and bottom heat Eco	This supports cooking on a single shelf for energy efficient cooking.	Cakes and bread
Intensive heat	Combines the top element with a more powerful bottom heating element that is perfect for crispy bases and baking in tins.	Tarts and savoury cakes
/ ////	1991	



		What does it do?	Recommended for
W	Hot air grilling*	For roasting. The grill element and fan switch on and off producing even and crisp roasting results.	Poultry, whole fish and larger pieces of meat
	Full-width grill	For grilling flat items.	Steak and sausage and making toast
~	Half-width grill	For grilling small amounts of food where grilling a smaller surface area is required.	Small portion of steak, sausage and making toast
	Slow Cooking	For gentle and slow cooking of seared, tender pieces of meat in ovenware without a lid. The heat is emitted evenly from the top and bottom at low temperatures.	Poultry and other meats (Beef, pork, lamb)
<u>\$\$\$</u>	Keeping warm*	Keeps cooked food warm.	Any cooked food

		What does it do?
Rapid Heating	Rapid heating	With rapid heating, you can shorten the heat-up time for selected heating functions, including 4D Hotair, Top and bottom heating and Intensive heat.

Possible to use added steam for this type of heating (operation only possible when the water tank is full). ^To cook on all four levels simultaneously, four wire racks are required for best results. For up to three levels, all accessories are suitable, ie. universal tray or baking tray. Features may vary depending on models. Please check individual product specifications.


At last, someone in the house who enjoys cleaning up.

Anyone who has ever cleaned an oven by hand knows how exhausting and time-consuming it can be. However, this chore is a thing of the past, thanks to our EcoClean Direct cleaning aid and pyrolytic self-cleaning function. You won't waste a minute on cleaning, leaving you more time to enjoy cooking.



Save time and energy with EcoClean Direct

While the oven bakes or roasts, the special direct coating of microfine ceramic particles on its interior walls absorbs grease and residue and breaks them down through oxidation. All you need to do is wipe the area without EcoClean Direct saving you time and energy.






Remove stubborn stains effortlessly with Pyrolytic Cleaning

When you activate the pyrolytic cleaning function, the oven heats up to 465°C and burns off any burned-on grease and food residue. All that's left is a little ash that you can easily remove with a paper towel. And because the baking trays, racks and shelf rails are all pyrolytic-proof, you can leave them in the oven during cleaning.





Ovens that suit your every need.

Types of Cooks		Suitable Oven Models			Key Oven Functions and Features
		60cm			
	The Connoisseur: Cuisiniers on a Quest for Culinary Perfection	HNG6764S1A			 PerfectBake and PerfectRoast Sensor Microwave Added Steam
	The Health Junkie: Nourishing Your Inner Wellness Warrior		CDG634BS1		• Steamer
			CSG656RS1		Steam Combination PerfectBake and PerfectRoast Sensor
	The Avant-Garde: Innovation for the Progressive Experimentalis	HBG656RS1B			PerfectBake and PerfectRoast Sensor
		HSG636ES1			PerfectBake and PerfectRoast Sensor Full Steam
	The Busy Gourmet: Food Preparation Made Quick and Fuss-Free		CMG6633BS1B	BEL554MS0K	• Microwave
	The DIY Chef: Autonomy for the Independent	HBN331E1K			
		HBN331E4SG			
		HBA5780S0B			
		HBF114BR0K			Conventional Oven
		HBG633BS1B			
		HBG635BB1J			
		HBG6753S1A			



HBG633BS1B

60cm | Stainless Steel Built-in Single Oven

Performance

- 10 heating methods:
- 4D Hotair
- Pizza setting
- Hotair Eco
- Bottom heat
- Top and bottom heat
- Defrost
- Top and bottom heat Eco
- Hot air grilling
- Full-width grill
- Half-width grill
- · Energy efficiency class: A+

Cleaning Functions

• EcoClean Direct: back panel

Features

- Cavity: 71L
- TFT color and text display with touch control buttons
- Rapid heating-up
- Temperature range: 30°C 300°C
- Softmove: oven with soft closing & opening

Safety Functions

- Childproof lock
- · Automatic switch off
- Maximum window temperature: 40°C
- · 3 layered glass door
- Integral cooling fan
- Residual heat indicator

Technical Information

- Total connected load: 2.99kW
- Voltage: 220 230V
- Power frequency: 50 / 60Hz / 13A
- Cable length: 1.2m
- Appliance dimensions (H x W x D): 595 x 595 x 548mm
- Min. cut out dimensions (H x W x D): 585 x 560 x 550mm



HBG635BB1J

60cm | Black Glass Design Built-in Single Oven

Performance

- 13 heating methods:
- 4D Hotair
- Pizza setting
- Hotair Eco
- Bottom heat
- Top and bottom heat

- Top and bottom heat Eco

- DefrostSlow cooking
- Hot air grilling
- Preheating
- Full-width grill
- Keep warm
- Half-width grill
- Energy efficiency class: A+

Cleaning Functions

• EcoClean Direct: back panel

Features

- Cavity: 71L
- TFT color and text display with touch control buttons
- 10 automatic programs
- Rapid heating-up
- Temperature range: 30°C 300°C
- Softmove: oven with soft closing & opening

Safety Functions

- Childproof lock
- Automatic switch off
- Maximum window temperature: 40°C
- 3 layered glass door
- Integral cooling fan
- · Residual heat indicator

- Total connected load: 2.85kW
- Voltage: 220 230V
- Power frequency: 50 / 60Hz / 13A
- Cable length: 1.2m
- Appliance dimensions (H x W x D): 595 x 595 x 548mm
- Min. cut out dimensions (H x W x D): 585 x 560 x 550mm



HBG6753S1A

Stainless Steel Built-in Single Oven 60cm

Performance

- 13 heating methods:
- 4D Hotair
- Pizza setting
- Hotair Eco
- Bottom heat
- Defrost
- Top and bottom heat - Top and bottom heat Eco - Slow cooking
- Hot air grilling
- Preheating
- Full-width grill
- Keep warm
- Half-width grill
- Energy efficiency class: A

Cleaning Functions

- Pyrolytic self-cleaning function
- Pyrolytic proof tray holder and baking tray

Features

- Cavity: 71L
- TFT color and text display with touch control buttons
- 10 automatic programs
- · Rapid heating-up
- Temperature range: 30°C 300°C
- Softmove: oven with soft closing & opening

Safety Functions

- · Childproof lock
- Door lock (when is off and during pyrolytic cleaning only)
- · Automatic switch off
- Maximum window temperature: 30°C
- · 4 layered glass door
- · Integral cooling fan
- · Residual heat indicator

Technical Information

- Total connected load: 3.60kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz / 16A
- Direct wiring
- Cable length: 1.2m
- Appliance dimensions (H x W x D): 595 x 595 x 548mm
- Min. cut out dimensions (H x W x D): 585 x 560 x 550mm



HBG656RS1B

Stainless Steel Built-in Single Oven 60cm

Performance

- 13 heating methods:
- 4D Hotair
- Pizza setting
- Hotair Eco
- Bottom heat
- Top and bottom heat
- Defrost - Top and bottom heat Eco - Slow cooking
- Hot air grilling
- Preheating
- Full-width grill
- Keep warm
- Half-width grill
- Energy efficiency class: A+

Cleaning Functions

• EcoClean Direct: top, side liners and back panels

- · Cavity: 71L
- Assist function (PerfectBake and PerfectRoast)
- TFT color and graphics display with direct touch function
- Rapid heating-up
- Temperature range: 30°C 300°C
- Softmove: oven with soft closing & opening

Safety Functions

- · Childproof lock
- · Automatic switch off
- Maximum window temperature: 40°C
- · 3 layered glass door
- · Integral cooling fan
- · Residual heat indicator

- Total connected load: 3.60kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz / 16A
- Direct wiring
- Cable length: 1.2m
- Appliance dimensions (H x W x D): 595 x 595 x 548mm
- Min. cut out dimensions (H x W x D): 585 x 560 x 550mm



HSG636ES1

Stainless Steel Built-in Combination Steam Oven 60cm

Performance

- 12 heating methods:
- 4D Hotair
- Pizza setting
- Hotair Eco
- Bottom heat
- Top and bottom heat
- Slow cooking
- Top and bottom heat Eco Preheating
- Hot air grilling
- Keep warm
- Full-width grill
- Half-width grill
- Additional heating methods with steam: Steam 100%, Regeneration, Fermentation, Defrost
- Additional function: 10 mins drying
- Energy efficiency class: A+

Cleaning Functions

• EcoClean Direct: back panel

Features

- · Cavity: 71L; Water tank capacity: 1L
- Assist function (PerfectBake and PerfectRoast)
- TFT color and graphics display with direct touch function
- · Rapid heating-up
- Temperature range: 30°C 250°C
- Softmove: oven with soft closing & opening

Safety Functions

- · Childproof lock
- · Automatic switch off
- Maximum window temperature: 40°C
- · 3 layered glass door
- · Integral cooling fan
- · Residual heat indicator

Technical Information

- Total connected load: 3.65kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz / 16A
- Direct wiring
- Cable length: 1.2m
- Appliance dimensions (H x W x D): 595 x 595 x 548mm
- Min. cut out dimensions (H x W x D): 585 x 560 x 550mm



HNG6764S1A

60cm | Stainless Steel Built-in Combination | Microwave Oven with Added Steam

Performance

- 14 heating methods:
- 4D Hotair - Pizza setting - Hotair Eco - Bottom heat - Top and bottom heat - Intensive heat - Top and bottom heat Eco - Slow cooking
- Hot air grilling - Preheating - Full-width grill - Keep warm - Half-width grill - Desiccation
- · Additional heating methods with steam: Regeneration, Fermentation
- · Additional heating methods with microwave: Microwave, Combi microwave variable
- · Additional function: 10 mins drying

Features

- · Cavity: 71L; Water tank capacity: 1L
- Assist function (PerfectBake and PerfectRoast)
- TFT color and graphics display with direct touch function
- · Rapid heating-up
- Temperature range: 30°C 300°C
- Softmove: oven with soft closing & opening

Cleaning Functions

- Pyrolytic self-cleaning function
- Pyrolytic proof tray holder and baking tray

Safety Functions

- Childproof lock
- Door lock (when is off and during pyrolytic cleaning only)
- · Automatic switch off
- Maximum window temperature: 30°C
- · 4 layered glass door
- · Integral cooling fan
- · Residual heat indicator

- Total connected load: 3.60kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz / 16A
- Direct wiring
- Cable length: 1.2m
- Appliance dimensions (H x W x D): 595 x 595 x 548mm
- Min. cut out dimensions (H x W x D): 585 x 560 x 550mm



CDG634BS1

45cm | Stainless Steel Built-in Steamer

Performance

- 4 heating methods:
- Steam 100%
- Regeneration
- Fermentation
- Defrost
- Additional function: 10 mins drying

Features

- · Cavity: 38L; Water tank capacity: 1.3L
- 20 automatic programs
- TFT color and text display with touch
- control buttons
- Temperature range: 30°C 100°C
- Softmove: oven with soft closing & opening

Safety Functions

- Childproof lock
- · Automatic switch off
- Maximum window temperature: 40°C
- · 3 layered glass door
- · Integral cooling fan

Technical Information

- · Total connected load: 1.9kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz / 10A
- Cable length: 1.2m
- Appliance dimensions (H x W x D): 455 x 595 x 548mm
- Min. cut out dimensions (H x W x D): 450 x 560 x 550mm



CMG633BS1B

45cm | Stainless steel Built in Oven with Microwave function

Performance

- 6 heating methods:
- 4D hot air
- Hot Air-Eco
- Hot air grilling
- Full width grill
- Half width grill
- Preheating
- Additional heating methods with microwave: Microwave, Combi microwave constant

Cleaning Functions

• Easy clean

Features

- · Cavity: 45L;
- 5 Microwave power settings (90W, 180W, 360W, 600W, 900W) with Inverter (MW)
- TFT color and graphics display with direct touch function
- Rapid heating-up
- Softmove: oven with soft closing & opening

Safety Functions

- Childproof lock
- Automatic switch off
- Maximum window temperature: 40°C
- · 3 layered glass door
- Integral cooling fan
- Residual heat indicator

- Total connected load: 3.6kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz / 16A
- Direct wiring
- Cable length: 1.5m
- Appliance dimensions (H x W x D): 455 x 595 x 548mm
- Min. cut out dimensions (H x W x D): 450-455 x 560-568 x 550mm





CSG656RS1

45cm | Stainless Steel Built-in Combination Steam Oven

Performance

- 14 heating methods:
- 4D Hotair
- Pizza setting
- Hotair Eco
- Bottom heat
- Top and bottom heat
- Intensive heat
- Top and bottom heat Eco Slow cooking
- Hot air grilling
- Preheating
- Full-width grill
- Desiccation
- Half-width grill
- Keep warm
- Additional heating methods with steam: Steam 100%, Regeneration, Fermentation, Defrost
- · Additional function: 10 mins drying
- Energy efficiency class: A+

Cleaning Functions

• EcoClean Direct: top, side liners and back panel

Features

- Cavity: 47L; Water tank capacity: 1L
- Assist function (PerfectBake and PerfectRoast)
- TFT color and graphics display with direct touch function
- Rapid heating-up
- Temperature range: 30°C 250°C
- Softmove: oven with soft closing & opening

Safety Functions

- Childproof lock
- · Automatic switch off
- Maximum window temperature: 40°C
- 3 layered glass door
- · Integral cooling fan
- · Residual heat indicator

Technical Information

- Total connected load: 3.3kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz / 16A
- · Direct wiring
- Cable length: 1.2m
- Appliance dimensions (H x W x D): 455 x 595 x 548mm
- Min. cut out dimensions (H x W x D): 450 x 560 x 550mm



BIC630NS1B

14cm | Stainless Steel Warming Drawer

Performance

- Stepless temperature control for 40°C - 80°C
- Maximum loading espresso cups: 64 pieces
- Maximum loading plates:

12 pieces

- **Features** · Cavity: 20L
- Dough proving
- Thawing foods
- · Keeping drinks and food warm
- · Pre-heating utensils

Safety Functions

- Loading up to 25kg
- Telescopic pull-out drawer
- · Cool door
- Operating indicator light

- Total connected load: 0.81kW
- Voltage: 220 240V
- Power frequency: 50 /60Hz / 10A
- Cable length: 1.5m
- Appliance dimensions (H x W x D): 140 x 595 x 548mm
- Min. cut out dimensions (H x W x D): 140 x 560 x 550mm



CTL636ES1

45cm | Stainless Steel Fully Automatic Espresso Maker / Fully Automatic Coffee Machine

Beverages

- One-touch preparation: Ristretto, Espresso, Espresso Macchiato, Coffee, Cappuccino, Latte Macchiato, Caffe Latte
- MyCoffee feature: Save 8 favourite beverages with individual names and adjustable mixing ratio of milk and espresso
- · Coffee outlet and milk frother height-adjustable: Up to 15 cm high Latte Macchiato glasses fit underneath
- IndividualCup Volume: Cup sizes adjustable individually
- OneTouch DoubleCup: Prepare two cups simultaneously for all coffee and milk specialties

Features

- · Water tank capacity: 2.4L
- · Unique SensoFlow heating System guarantees highest espresso indulgence with every cup with its ideal, constant brewing
- AromaDouble Shot prepares extra-strong coffee with less bitterness and full aroma
- CoffeeSensor Pro: The grinding unit automatically adjusts to bean variety
- One touch function for drinks with milk

Convenience

- · Intuitive control ring
- TFT display with interactive menu
- Early warning if water tank or bean container is almost empty
- · Flexible milk solution: connects the provided milk container or using any other container, e.g. a milk carton

Hygiene

- · Removable brewing unit: Easy and hygienic cleaning under running water
- AutoMilk Clean: Fully-automatic steam cleaning of the milk system after every beverage
- · Milk frother removable and dishwasher-proof
- SinglePortion Cleaning: Complete emptying of all pipes after each brewing process
- Automatic rinsing program when switching off, switching on
- Removable and dishwasher proof drip tray and coffee grounds container
- Automatic cleaning and descaling programme
- · Reminds in time of water filter change, descaling, cleaning; including display of remaining cups

Additional Features

- Concealed accessories storage
- Bean container with aroma protection lid (500g volume)
- Illuminated coffee outlet
- Grinding fineness adjustable (multi-level)
- Childproof lock

- · Connection Rating: 1.6kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz / 13A
- Cable length: 1.7m
- Appliance dimensions (H x W x D): 455 x 594 x 375mm
- Min. cut out dimensions (H x W x D): 449 x 558 x 356mm



BEL554MS0K

38cm | Stainless Steel Built-in Microwave Oven with Grill

Performance

- 3 cooking methods:
- Microwave
- Grill
- Combined operation
- 8 auto programs
- 1 memory function

Features

- · Cavity: 25L
- 900W Microwave
- 5 settings: 90W, 180W, 360W, 600W, 900W
- · Automatic switch off
- Door contact switch

Technical Information

- Total connected load: 1.45kW
- Voltage: 230 240V
- Power frequency: 50Hz / 10A
- Cable length: 1.5m
- Appliance dimensions (H x W x D): 382 x 594 x 388mm
- Min. cut out dimensions (H x W x D): 380-382 x 560-568 x 550mm



HBN331E1K

Stainless Steel Built-in Single Oven 60cm |

Performance

- 5 heating methods:
- 3D Hotair
- Bottom heat
- Hotair grilling
- Full-width variable grill
- Top and bottom heat
- Energy efficiency class: A

Features

- · Cavity: 66L
- Rapid heating-up: manual

Safety Functions

- Childproof lock
- Maximum window temperature: 50°C
- Integral cooling fan
- 3 layered glass door

Technical Information

- Total connected load: 2.9kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz / 13A
- Cable length: 2.0m
- Appliance dimensions (H x W x D): 595 x 595 x 548mm
- Min. cut out dimensions (H \times W \times D): 575 x 560 x 550mm

Accessories

- 1 x enamel baking tray
- 1 x combination grid
- 1 x universal pan



HBN331E4SG

60cm | Stainless Steel Built-in Single Oven

Performance

- 5 heating methods:
- 3D Hotair
- Hotair grilling
- Full-width variable grill
- Bottom heat
- Top and bottom heat
- Energy efficiency class: A

Features

- · Cavity: 66L
- Rapid heating-up: manual

Safety Functions

- Childproof lock
- Maximum window temperature: 50°C
- 3 layered glass door
- · Integral cooling fan

Technical Information

- Total connected load: 2.9kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz / 13A
- Cable length: 2.0m
- Appliance dimensions (H x W x D): 595 x 595 x 548mm
- Min. cut out dimensions (H x W x D): 575 x 560 x 550mm

Accessories

- 1 x combination grid
- 1 x universal pan



HBF114BR0K

60cm |

Stainless Steel Built-in Single Oven

Performance

- 7 heating methods:
- 3D Hotair
- Full Width Variable Grill
- Top and bottom Heat
- Hot Air Grilling - Pizza Setting
- Bottom Heat
- Gentle Hot Air
- Energy efficiency class: A

Cleaning Functions

• GranitEnamel – easy to clean interior

Features

- · Cavity: 66L
- Rapid Heating Up

Safety Functions

- Childproof Lock
- Maximum Window Temperature: 50 °C
- 3 Layered Glass Door
- Integral cooling fan

Technical Information

- Total Connected load: 2.95kW
- Voltage: 220-240W
- Power Frequency: 50 / 60Hz/ 13A
- Cable Length: 2.0m
- Appliance Dimensions (HxWxD): 595 x 594 x 548 mm
- Min. cut out dimensions (H x W X D): 575-597 x 560-568 x 550mm

Accessories

- 1 x combination grid
- 1 x universal pan



HBA5780S0B

60cm | Stainless Steel Built-in Single Oven

Performance

- 10 heating methods:
 - 3D Hot Air - Full Width Grill - Conventional Heat - Hot Air Grilling - Pizza Setting - Bottom Heat - Defrost - Hot Air Gentle - Low Temperature Cooking - Keep Warm
- Energy efficiency class: A

Cleaning Functions

• Pyrolytic Self Cleaning Function

Features

- Cavity: 71L
- Rapid Heating Up
- AutoPilot 30

Safety Functions

- Childproof Lock
- Maximum Window Temperature: 30 °C
- 4 Layered Glass Door
- Integral Cooling Fan

- Total Connected load: 2.99kW
- Voltage: 220-240W
- Power Frequency: 50 / 60Hz/ 13A
- Direct Wiring
- Cable Length: 1.2m
- Appliance Dimensions (H x W x D): 595 x 594 x 548 mm
- Min. cut out dimensions (H x W x D): 585 x 560 x 550 mm

Accessories

Description		
	HEZ324000	Inlaid wire shelf for universal pan Wire shelf fits into universal pan for grilling applications. Universal pan and wire shelf can be removed together. Suits all Bosch ovens except CDG634BS1.
	HEZ327000	Baking stone Ceramic baking stone and wooden paddle. Ideal when baking bread, unleavened bread, pizza and frozen food dishes. Pyrolysis compatible with pyrolytic ovens. Suits all Bosch ovens except CDG634BS1.
	HEZ631070	Baking tray Enamelled baking tray for cakes, biscuits, rolls and bread. Easy to clean. Pyrolysis compatible with pyrolytic ovens. Suits all Bosch ovens except CDG634BS1.
	HEZ633070	Professional pan, enamelled Extra deep, large enamelled pan with wire shelf insert. Best suitable for large roasts and ideal for automatic programmes when used with the fitting lid. Pyrolysis compatible with pyrolytic ovens. Suits all Bosch ovens except CDG634BS1.
	HEZ634000	Baking and roasting grid (standard) Wire rack to accomodate all dishes in forms like baking tins, ceramic and glass roasting dishes. Suits all Bosch ovens except HSG636ES1, HMG656RS1, HNG6764S1A, CDG634BS1, CSG656RS1, CNG6764S1B.
	HEZ36D663G*	Steam container, punched, size XL For steaming vegetables, fish and meat. For larger amount of food. Suits all Bosch Ovens except for HBG633BS1J, HBG635BB1J, HBG635BW1J, HBG6753S1A, HBG656RS1B, HMG656RS1, HNG6764S1A, CDG634BS1, CNG6764S1B.
	HEZ632070*	Multipurpose pan, enamelled Deep enamelled pan for juicy fruit cakes, pizza, large roasts, casseroles and bakes. Can be used to hold any residual fat during grilling. Easy to clean. Suits all Bosch Ovens except for CDG634BS1.
	HEZ864000*	Glass tray Special glass dish for roasting and bakes. Easy to clean and hygenic. Suits all Bosch Ovens except for HBG635BB1J, HBG635BW1J, HMG656RS1, HNG6764S1A, CNG6764S1B.
	HEZ638200*	2 level telescopic shelf rails Replacement for shelf support with two telescopic rails on two levels, fully extendable. Suits all Bosch Ovens except for HBG6753S1A, HBG656RS1B, HSG636ES1, HMG656RS1, HNG6764S1A, CDG634BS1, CSG656RS1, CNG6764S1B.
	HEZ638300*	3 level telescopic shelf rails Replacement for shelf support with three telescopic rails on three levels, fully extendable. Suits all Bosch Ovens except for HBG6753S1A, HBG656RS1B, HSG636ES1, HMG656RS1, HNG6764S1A, CDG634BS1, CSG656RS1, CNG6764S1B.

^{*} Accessories order will be on indent basis.



The world of Bosch electric hobs.

There is a wide range of induction and radiant hobs to choose from. As you would expect from Bosch, all are made using high-quality materials, are easy to use and add versatility, style and elegance to any kitchen.



Know your hobs.

3 main types of hobs to choose from based on heating methods.



Why induction?

Bring 2 litres of water to a boil in just 4.7 minutes. Our PowerBoost function can increase the power output to a selected cooking zone by approximately 50%. Saving you precious time.



Why is it so fast, so easy to clean and safe?

Induction Hobs are easier to clean than traditional hobs, because the ceramic glass doesn't get as hot. Any spillages can be quickly and easily wiped away.

With an Induction Hob, micro-currents are generated in the bottom of the pot. Consequently, heat is only created when the pan is connected to the hob – heating will stop as soon as it's removed, which means it's far safer than cooking with traditional hobs.



Multiple heating zones. 17 cooking levels. Endless possibilities.

Bosch FlexInduction is the result of decades of research and development. At last, practical, hi-tech appliances that escape the confines of traditional cooktops. Here is freedom in the kitchen.

What is FlexInduction?

Ideal for small pots, large pots, multiple pans, frying pans or cassarole dishes, the system allows you to control pots and pans separately, offering increased flexibility.



Combi Induction hobs

Consists of FlexInduction Zone and standard induction zones.

Our Combi Induction hobs feature one large rectangular cooking zone, ideal for any cooking needs. A flick of a switch, 2 induction zones become one large induction surface. You can also consider converting the FlexInduction zone to a Teppanyaki cooking area by adding a Teppanyaki plate.






Additional feature for Combi Induction hobs - MoveMode*

When your recipe requires you to switch from boil to simmer at just the right moment, MoveMode is there when you need it.

Switch from level 9 to level 1 by simply sliding your pot. MoveMode lets you move seamlessly from your first high-powered cooking task to the next, without a hiccup, and always in control.

*Applicable to selected models. Default setting is based on factory setting.



Set to the perfect level. Cooked to the perfect consistency.

The right temperature is crucial for successful frying. The new PerfectFry sensor automatically monitors the frying temperature and adjusts it as required to ensure perfectly-fried dishes. Say goodbye to burnt food and hello to perfection.



Perfectly frying food starts with getting the temperature right for the oil. Different types of oil have different smoke points and without exact temperature management, food can be burnt easily. PerfectFry shows you when the ideal temperature for adding the oil to the pan has been reached.



Achieving perfect results with the 5 PerfectFry temperature levels:



1

Very lowIdeal for boiling down sauces



2

Low Suitable for frying with virgin olive oil, or for frying omelettes



3

Medium-low Perfect for frying fish, meatballs or sausages



4

Medium-high Perfect for frying steak (medium or well done), ragout or vegetables



5

HighPerfect for
frying potatoes
or rare steaks

Electric hobs. Features and Benefits.

Performance



Quality ceramic top

High quality and durable ceramic top that can withstand heat up to 700°C.



17-stage power setting

Enjoy total control on every recipe with 17-stage power settings. This function allows cooking zones to be set in increments of 0.5 (eg. 0.5, 1, 1.5, 2...9).



Automatic pan recognition

The automatic pan recognition function allows our induction hobs to identify the size of the pan and only heats up the base of the pan, not the entire zone, saving time and energy.



PowerBoost


With PowerBoost, the power level of your induction hobs is increased to help you give that little extra boost when cooking. This means you can bring a pot filled with two litres of water to boil almost three times as quickly as on a conventional ceramic hob.

Safety



Childproof lock

Maximum protection for children's hands: the integrated lock function allows you to secure your cooking area and protect it against unwanted operation. This guarantees total safety – for both you and your loved ones.



2-stage residual heat display

The 2-stage residual heat display provides clear indication on the heat of the zones after it is turned off, providing enhanced safety for the family.



QuickStart

The cooktop automatically detects where a pot has been placed after being switched on, and the zone is indicated on the display. You can get started immediately and select the desired cooking level for your pot.



Overflow protection

A safety system protects the hob. If a metal object is placed on the hob or should there be any spillage, the hob may switch off and sound an alarm. An "E" naming message will appear on the display. This ensures safety for your loved ones.



ReStart

If the hob is accidentally switched off, you can restore the last selected setting by just turning on the hob.

Convenience



DirectSelect

With the DirectSelect function, all it takes is a finger select from the power level on offer, eliminating the needs to press +/- keys repeatedly.




HighSpeed ceramic glass

HighSpeed cooking zones shorten initial heat-up times, allowing for rapid searing and frying.



Wipe protection

Total control – even when you clean. With this function, you can lock the sensor buttons for 30 seconds to avoid making accidental changes to the cooking settings. This allows you to clean the surfaces without having to re-adjust settings.




Triple ring cook zone

The 32cm cooking zone for our induction hob is now the biggest in the market, allowing users to select a smaller $\,$ or larger cook zone for different pan sizes.



Count-up timer

If you want to know how long your spaghetti has been cooking and be alerted the moment it is al dente, you can simply use the new Count-up timer. It shows exactly how long you have been cooking. This is especially useful when you need to follow or test out recipes.



PPI82560MS

76cm | Ceramic Induction Hob

Performance

- 2 Induction cooking zones
- Left and right zone: 1.8kW with booster 3.1kW (Ø180mm)

Features

- Automatic pan recognition sensor
- Power management function

Convenience

• Direct Select Touch Control: 9 Power Levels

Safety

- 2 stage residual heat indicator for each zone
- Timer with switch off function for each zone
- Safety time switch-off
- · Childproof lock
- Wipe protection function

Technical Information

- Total connected load: 3.5kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1.5m without plug
- Appliance dimensions (H x W x D): 59 x 780 x 450mm
- Cut out dimension (H x W x D): 59 x 700 x 400mm
- Direct wiring



PID631BB1E

60cm | Ceramic Induction Hob

Performance

- 3 induction cooking zones
- Rear left: 3.3kW, 2.6kW, 2.2kW (with booster): 3.7kW, 4.4kW, 5.5kW ø: 210mm, 260mm, 320mm
- Rear right: 1.4kW with booster 2.2kW (ø145mm)
- Front right: 2.2kW with booster 3.7kW (ø210mm)

Features


- Automatic pan recognition sensor
- Boost function for all zones
- Quick start and Restart
- · Quality ceramic top

Convenience

• Touch Select Control: 17 power levels

- 2 stage residual heat indicator for each zone
- Timer with switch off function for each zone
- · Safety time switch-off
- Childproof lock

- Total connected load: 7.4kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1.1m without plug
- Appliance dimensions (H x W x D): 51 x 592 x 522mm
- Cut out dimensions (H x W x D): 51 x 560 x 490 - 500mm
- Direct wiring



PXE675DC1E

60cm | Ceramic Induction Hob

Performance

- 4 induction cooking zones
- Rear left / Front left: 2.2kW with booster 3.7kW (ø240mm)
- Full left area: 3.3kW with booster 3.7kW (ø380mm)
- Rear right: 1.4kW with booster 2.2kW(ø145mm)
- Front right: 2.2kW with booster 3.7kW (ø210mm)

Features

- Automatic pan recognition sensor
- Boost function for all zones
- · Perfectfry sensor
- PanBoost
- MoveMode
- Count-up timer / cooktop
- Quickstart and Restart
- · Quality ceramic top
- · Keep warm

Convenience

- Direct Select Premium: 17 power levels
- Energy consumption display

Safety

- 2 stage residual heat indicator for each zone
- Timer with switch off function for each zone
- · Safety time switch-off
- Childproof lock
- Wipe protection function

Technical Information

- · Total connected load: 7.4kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1.1m without plug
- Appliance dimensions (H x W x D): 51 x 606 x 527mm
- Cut out dimensions (H x W x D): 51 x 560 x 490 - 500mm
- Direct wiring



PKK651FP1E

60cm | Ceramic Radiant Hob

Performance

- 3 radiant cooking zones
- Left and right zone: 1.8kW with booster 3.1kW (Ø180mm)
- Left dual-circuit cooking zone: 2.7kW, 2.1kW with booster 3.4kW (Ø275mm, 210mm)
- Rear right: 1.2kW (Ø145mm)
- Front right: 1kW, 2kW with booster 2.3kW (Ø180mm, 120mm)

Features

• Quality Ceramic top

Convenience

- Direct Select Touch Control: 17 power levels
- PowerBoost function

Safety

- 2 stage residual heat indicator for each zone
- Timer with switch off function for each zone
- Safety time switch-off
- · Childproof lock
- Power on indicator light
- Wipe protection function

- Total connected load: 5.75kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1.0m without plug
- Appliance dimensions (H x W x D): 39 x 592 x 522mm
- Cut out dimension (H x W x D): 39 x 560 x 490 - 500mm
- Direct wiring

The world of Bosch gas hobs.

Our German-designed gas hobs are available in a range of different styles and burner configurations for greater cooking flexibility.



Performance



Precise flame control

Ensure precise control of inner and outer flame.



High-power wok-style burner

Selected gas cooktop models feature a powerful wok-style burner, which provides up to 6.0kW. Suitable for use with flat-based pans or with a wok using the wok ring provided.



3D flame wheel for evenly distributed heat

Our burners are designed to provide triple flame (for LPG gas) and double flame (for Towngas), to give powerful and even heat distribution.


Safety



Flame failure safety device

Safety valve systrem will cut off gas automatically when the flame goes out unexpectedly.

Convenience



Sealed top sheet

Prevention of spillage into the gas hob, ensuring safety and easy maintenance of appliance.



One-hand electric ignition

The gas ignites automatically by pushing and turning the control knobs, offering convenience as there is no separate ignition button needed for cleaning. It also reduces the hassle of changing batteries.



Flexible burners

With different burner combinations, enjoy greater cooking efficiency with the correct sized burner for the size of pan.



PBD7251SG

76cm | Stainless Steel Gas Hob (Suitable for Town Gas and LPG)

Performance

- 2 gas burners
- 2 triple circuit burner (4.5kW) for each wok burner

· Precise flame control

Convenience

• Safe and quick ignition

Safety

• Flame failure safety device

Technical Information

- Voltage: 220 240V
- Power frequency: 50Hz
- Cable length: 1.2m with plug
- Appliance dimensions (H x W x D): 80 x 760 x 460mm
- Cut out dimensions (H x W x D): 80 x 700 x 400mm



PBD7231SG / PBD7232SG*

78.5cm | Tempered Glass Gas Hob (Suitable for Town Gas / *LPG)

Performance

- 2 gas burners
- 2 triple circuit burner (4.5kW) for each wok burner

Features

· Precise flame control

Convenience

• Safe and quick ignition

Safety

• Flame failure safety device

- Voltage: 220 240V
- Power frequency: 50Hz
- Cable length: 1.2m with plug
- Appliance dimensions (H x W x D): 80 x 785 x 450mm
- Cut out dimensions (H x W x D): 80 x 700 x 400mm



PBD7351SG

76cm | Stainless Steel Gas Hob (Suitable for Town Gas and LPG)

Performance

- 3 gas burners
- Left burner: 4.5kW
- Center burner: 1.7kW
- Right burner: 4.5kW

Features

· Precise flame control

Convenience

• Safe and quick ignition

Safety

• Flame failure safety device

Technical Information

- Voltage: 220 240V
- Power frequency: 50Hz
- Cable length: 1.2m with plug
- Appliance dimensions (H x W x D): 80 x 760 x 460mm
- Cut out dimensions (H x W x D): 80 x 700 x 400mm



PBD7331SG / PBD7332SG*

78.5cm | Tempered Glass Gas Hob (Suitable for Town Gas / *LPG)

Performance

- 3 gas burners
- Left burner: 4.5kW
- Center burner: 1.7kW
- Right burner: 4.5kW

Features

• Precise flame control

Convenience

• Safe and quick ignition

Safety

• Flame failure safety device

- Voltage: 220 240V
- Power frequency: 50Hz
- Cable length: 1.2m with plug
- Appliance dimensions (H x W x D): 80 x 785 x 450mm
- Cut out dimensions (H x W x D): 80 x 700 x 400mm





PBD9351SG

90cm | Stainless Steel Gas Hob (Suitable for Town Gas and LPG)

Performance

- 3 gas burners
- Left burner: 4.5kW
- Center burner: 1.7kW
- Right burner: 4.5kW

Features

· Precise flame control

Convenience

• Safe and quick ignition

• Flame failure safety device

Technical Information

- Voltage: 220 240V
- Power frequency: 50Hz
- Cable length: 1.2m with plug
- Appliance dimensions (H x W x D): 80 x 900 x 480mm
- Cut out dimensions (H x W x D): 80 x 880 x 455mm

PBD9331SG

90cm | Tempered Glass Gas Hob (Suitable for Town Gas and LPG)

Performance

- 3 gas burners
- Left burner: 4.5kW
- Center burner: 1.7kW
- Right burner: 4.5kW

Features

• Precise flame control

Convenience

• Safe and quick ignition

• Flame failure safety device

- Voltage: 220 240V
- Power Frequency: 50Hz
- Cable length: 1.2m with plug
- Appliance dimensions (H x W x D): 80 x 920 x 480mm
- Cut out dimensions (H x W x D): 80 x 880 x 455mm



PCC6A5B90

60cm Stainless Steel Gas Hob (Suitable for LPG)

Performance

- 3 gas burners
- Rear right: Rapid burner 3kW
- Left: Wok burner 4kW
- Right front: Economy burner 1kW

Features

- FlameSelect
- Ergonomic sword control knobs

Convenience

• Cast iron continuous pan supports

Safety

• Flame failure safety device

- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1m with plug
- Appliance dimensions (H x W x D): 45 x 582 x 520mm
- Cut out dimensions (H x W x D): 45 x 560 - 562 x 480 - 492mm

Design with Flexibility









PRA3A6D70

30cm | Ceramic Domino Gas Hob (Suitable for LPG)

Performance

• 1 dual wok burner – 6.0kW

Features

- Flame select
- · Quality ceramic top

Convenience

- Flexibility: can be combined with various types of hobs
- · Cast iron and dishwasher proof pan support
- Ergonomic sword control knobs

Safety

- Flame failure safety device
- · Residual heat indicator

Technical Information

- Gas connection rating 6.0kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- · Cable length: 1m without plug
- Appliance dimensions (H x W x D): 45 x 306 x 527mm
- Cut out dimensions (H x W x D): 45 x 270 x 490 - 500mm

PRA326B91X

30cm | Ceramic Domino Gas Hob (Suitable for Town Gas)

Performance

• 1 dual wok burner - 5.5kW

Features

- · Precise flame control
- · Quality ceramic top

Convenience

- · Flexibility: can be combined with various types of hobs
- Cast iron and dishwasher proof pan support

Safety

• Flame failure safety device

Technical Information

- Gas connection rating 5.5kW
- Voltage: 220 240V
- Power frequency: 50Hz
- · Cable length: 1m with plug
- Appliance dimensions (H x W x D): 87 x 306 x 527mm
- Cut out dimensions (H x W x D): 87 x 270 x 490 - 500mm

PRB3A6D70

Ceramic Gas Hob (Suitable for LPG) 30cm

Performance

- · Double burner
- Front: 1.9kW
- Rear: 2.8kW

Features

- Flame select
- · Quality ceramic top

Convenience


- Flexibility: can be combined with various types of hobs
- · Cast iron and dishwasher proof pan support
- Ergonomic sword control knobs


Safety

- · Flame failure safety device
- · Residual heat indicator

- Gas connection rating 4.7kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1m without plug
- Appliance dimensions (H x W x D): 45 x 306 x 527mm
- Cut out dimensions (H x W x D): 45 x 270 x 490 - 500mm







PRB326B90X

30cm | Ceramic Gas Hob (Suitable for Town Gas)

Performance

- · Double burner
- Front: 1.9kW
- Rear: 2.8kW

Features

- · Precise flame control
- Quality ceramic top

Convenience

- Flexibility: can be combined with various types of hobs
- · Cast iron and dishwasher proof pan support

Safety

• Flame failure safety device

Technical Information

- · Gas connection rating 4.7kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- · Cable length: 1m without plug
- Appliance dimensions (H x W x D): 47 x 306 x 527mm
- Cut out dimensions (H x W x D): 45 x 270 x 490 - 500mm

PKF375CA1E

30cm | Ceramic Radiant Domino Hob

Performance

- 2 radiant cooking zones
- Rear center: 1.2kW (ø145mm)
- Front dual-circuit cooking zone: 2.0kW, 0.80kW (ø120mm, ø180mm)

Features

- Surface-mounted controls: 9 power levels
- · Quality ceramic top

Convenience

• Flexibility: can be combined with various types of hobs

Safety

- 2 power on indicator lights
- 2-stage residual heat indicator for each

Technical Information

- Electrical connection rating 3.2kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1m without plug
- Appliance dimensions (H x W x D): 48 x 306 x 527mm
- Cut out dimensions (H x W x D): 45 x 270 x 490 - 500mm
- · Direct wiring

PIB375FB1E

30cm | Induction Domino Hob

Performance

- 2 induction cooking zones
- Rear center: 1.4kW with booster 2.2kW
- Front center: 2.2kW with booster 3.7kW (ø210mm)

Features

- Automatic pan recognition sensor
- DirectSelect touch control: 17 power levels
- · Count-up timer
- · Quickstart and Restart
- · Quality ceramic top

Convenience

- Flexibility: can be combined with various types of hobs
- · Electronic display
- · Energy consumption display

Safety

- 2 power on indicator lights
- 2-stage residual heat indicator for each
- Childproof lock
- · Safety time switch-off

- Electrical connection rating 3.7kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- · Cable length: 1.1m without plug
- Appliance dimensions (H x W x D): 51 x 306 x 527mm
- Cut out dimensions (H x W x D): 51 x 270 x 490 - 500mm
- Direct wiring



PKY475FB1E

40cm | Teppanyaki Domino Hob

Performance

• Two separately controlled cooking zones: cook or heat using the entire or either half of the surface

- Automatic pan recognition sensor
- DirectSelect touch control: 17 power levels
- Quality ceramic top
- · Count-up timer
- Keep warm
- Restart

Convenience

- Flexibility: can be combined with various types of hobs
- Big stainless steel roast area
- Electronic display
- Energy consumption display

Safety

- Power on indicator lights
- 2 stage residual heat indicator for each zone
- Safety time switch-off

- Electrical connection rating 1.9kW
- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1m without plug
- Appliance dimensions (H x W x D): 90 x 396 x 527mm
- Cut out dimensions (H x W x D): 90 x 360 x 490 – 500mm



The Right Hood.


Match your hood with your kitchen to keep your flat smelling clean and fresh. The right hood replaces air in your kitchen ideally 10 times an hour.



What extraction rate do I need from my hood?




When choosing a hood, always match its air delivery power to the size of your kitchen. An effective extractor should be able to replace the air in your kitchen 10 times an hour.




At Bosch, ducted and recirculation systems smell the same. Of nothing.

Our hoods swiftly and reliably extract odours and grease particles from your kitchen. They create a consistently fresh feel good ambience before, during and after cooking. At the same time, they perfectly illuminate your worktop area and still look unbelievably attractive even after all that hard work.



Ducting

- Ducted hoods are powerful and effective.
- Odours, grease and steam are extracted, filtered and ducted to the outside.
- · All that is required is sufficient fresh air, for instance from an open window.



Recirculation

- · Hoods with recirculation are powerful and energy-efficient.
- · Odours and grease are extracted and filtered. The purified air is returned to the room.
- · As no ducting openings are necessary, no energy can escape (e.g. cold or heat).



Relax in a quieter kitchen.



EcoSilence Drive®

EcoSilence Drive® motor operates without carbon brushes, eliminating the disadvantages of conventional motors. Instead of energy loss, wear and noise, you get efficiency, durability, and smooth operation.

To reduce motor noise even further, we have optimised the airflow inside the hood. The result: low noise levels with high power.

Design

Worktop Lighting



LED lighting

LED lights offer a longer lifetime and use less energy than conventional halogen lighting. Additional convenience is offered with SoftLight which gently fades lighting in and out with dimmer function.



Halogen lighting

Integrated halogen lighting ensures that the cooking area is clearly illuminated. They are more efficient than standard lights and are designed to last longer.



Inner frame

The patented Bosch inner frame is specially shaped to permit an optimum flow of air and leading stability to the hood. Without any edges, cleaning the frame is also easy.


Hoods. Features and Benefits.

Performance



Powerful extraction rate

With models offering up to 1000m³/h maximum extraction and ventilating capibility, the Bosch line of efficient, high-performance hoods aids in removing steam, odours, grease and smoke quickly.



Dishwasher-safe metal grease filters

All Bosch filters have up to 5 layers of filters and for easy cleaning it can be safely loaded into any Bosch dishwasher for sparkling results.



Active carbon filter

A recirculating kit with active carbon filter eliminates unpleasant odours and is easy to install and replace.

Convenience



Variable power settings

Odours, smoke and moisture can be effectively removed with the variable power settings on Bosch hoods. An intensive extraction setting on selected hood models provides an extra boost to the performance of the hood when needed.



Electronic 'clean-filter indicator'

A light is illuminated when the filter needs a cleaning, ensuring optimal efficiency of the hood.

After running

Continuing operation of the hood for approx ten minutes after normal usage ensure vapours and odours are effectively removed.

Automatic switch back

When the intensive setting is selected, it may be set to automatically revert back to a pre-defined normal level after a short period of time.







DHI623GSG

60cm | Slimline Hood

Performance

- Max extraction rate: 380 m³/h, according to EN 61591
- Suitable for ducted or re-circulated operation
- Operating sound level: 70db

Features

· 3 speeds

Convenience

- Dishwasher safe metal grease filter
- Push buttons controls

Technical Information

- Voltage: 220 240V
- Power frequency: 50Hz
- Cable length: 2.0m
- Appliance dimensions
- Exhaust and recirculate (H x W x D): 180 x 598 x 300mm
- Cut out dimensions (H x W x D): 140 x 550 x 280mm

DHI923GSG

90cm | Slimline Hood

Performance

- Max extraction rate: 380 m³/h, according to EN 61591
- Suitable for ducted or re-circulated operation
- Operating sound level: 70db

Features

• 3 speeds

Convenience

- Dishwasher safe metal grease filter
- Push buttons controls

Technical Information

- Voltage: 220 240V
- Power frequency: 50Hz
- Cable length: 2.0m
- Appliance dimensions
 - Exhaust and recirculate (H x W x D): 180 x 898 x 300mm
- Cut out dimensions (H x W x D): 140 x 850 x 280mm

DHL755B

70cm | Silver Metallic Canopy Hood

Performance

- Max extraction rate: 630 m³/h, according to EN 61591
- Suitable for ducted or re-circulated operation
- Operating sound level: 61db

Features

- Twin motor
- 2 x 20W halogen lighting
- ullet 3 speeds plus intensive setting

Convenience

- Dishwasher safe metal grease filter
- Sliding switch control for extractor speeds and light

- Voltage: 220 240V
- Power frequency: 50Hz
- Cable length: 1.3m
- Appliance dimensions
- Exhaust and recirculate (H x W x D): 255 x 730 x 380mm
- Cut out dimensions (H x W x D): 255 x 700 x 350mm







DFS097A50B

90cm | Silver Metallic Slimline Hood

Performance

- Max extraction rate: 740m³/h, according to EN 61591
- Suitable for ducted or re-circulated operation
- Operating sound level: 55dB

Features

- EcoSilence[™] Drive
- ullet 3 speed settings plus intensive setting
- 2 x 3W LED lighting
- Automatic run on: 10 mins
- Intensive operation revert: 6 mins

Convenience

- Dishwasher safe metal grease filter
- Push button controls with electronic display

Technical Information

- Voltage: 220 240V
- ullet Power frequency: 50 / 60Hz
- Cable length: 1.75m
- Appliance dimensions
- Exhaust and recirculate (H x W x D): 426 x 898 x 290mm
- Cut out dimensions (H x W x D): 385 x 524 x 290mm

DFS098K53

90cm | Stainless Steel Slimline Hood

Performance

- Max extraction rate: 840m³/h, according to EN 61591
- Suitable for ducted or re-circulated operation
- Operating sound level: 51dB

Features

- EcoSilence™ Drive
- 3 speed plus 2 intensive settings
- 2 x 3W LED lighting
- Automatic run on: 10 mins
- Intensive operation revert: 6 mins
- Air quality sensor

Convenience

- Dishwasher safe metal grease filter
- Electronic controls with TouchControl

Technical Information

- Voltage: 220 240V
- Power frequency: 50 / 60Hz / 13A
- Cable length: 1.75m
- Appliance dimensions
- Exhaust and recirculate (H x W x D): 378 x 898 x 290mm
- Cut out Dimensions (H x W x D): 337 x 524 x 290mm

DWB097E50B

90cm | Box Design Chimney Hood

Performance

- Max extraction rate: 730m³/h, according to EN 61591
- Suitable for ducted or re-circulated operation
- Operating sound level: 55dB

Features

- Twin channel high performance fan motor
- EcoSilence[™] Drive
- 3 speed plus 2 intensive settings
- 3 x 3W LED lighting
- Soft light with dimmer function
- Automatic run on: 10 mins
- Intensive operation revert: 6 mins

Convenience

- Dishwasher safe metal grease filter
- Saturation indicator for metal & charcoal filter

- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1.3m
- Appliance dimensions
- Exhaust (H x W x D): 642 - 954 x 900 x 500mm
- Recirculate (H x W x D): 642 - 1064 x 900 x 500mm





DWB091E50

90cm | Slimline Box Design Chimney Hood

Performance

- Max extraction rate: 980m³/h, according to EN 61591
- Suitable for ducted or re-circulated operation
- Operating sound level: 62dB

Features

- Twin channel high performance fan motor
- EcoSilence™ Drive
- 3 speed plus 2 intensive settings
- 3 x 3W LED lighting
- Soft light with dimmer function
- Automatic run on: 10 mins
- Intensive operation revert: 6 mins

Convenience

- Dishwasher safe metal grease filter
- Saturation indicator for metal & charcoal filter

Technical Information

- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1.3m
- Appliance dimensions
- Exhaust (H x W x D): 628 - 954 x 900 x 500mm
- Recirculate (H x W x D): 628 - 1064 x 900 x 500mm

DEE928PSG

90cm | Slimline Pyramid Design Chimney Hood

Performance

- Max extraction rate: 1000m³/h
- Suitable for ducted or re-circulated operation
- Operating sound level: 69dB

Features

- 3 speeds
- 2 x 3W LED lighting

Convenience

- Dishwasher safe metal grease filter
- Easy to clean integrative chimney
- Push button controls

- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1.5m
- Appliance dimensions
- Exhaust (H x W x D): 707 - 1075 x 895 x 530mm
- Recirculate (H x W x D): 707 - 1195 x 895 x 530mm





DEE928BSG

90cm | Box Design Chimney Hood

Performance

- Max extraction rate: 1000m³/h
- Suitable for ducted or re-circulated operation
- Operating sound level: 69dB

Features

- 3 speeds
- 2 x 3W LED lighting

Convenience

- Dishwasher safe metal grease filter
- Easy to clean integrative chimney
- Push button controls

Technical Information

- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1.5m
- Appliance dimensions
- Exhaust (H x W x D): 678 - 1048 x 895 x 530mm
- Recirculate (H x W x D): 678 - 1168 x 895 x 530mm

DWP96BC50B

90cm | Pyramid Design Chimney Hood

Performance

- Max extraction rate: 600m³/h, according to EN 61591
- Suitable for ducted or re-circulated operation
- Operating sound level: 69dB

Features

- 2 x 1.5W LED
- Energy Efficient Capacitor Motor
- 3 Speeds via Push Buttons
- Metal Grease Filter

Convenience

• Dishwasher Safe Metal Grease Filter

- Voltage: 220 -240V
- Power Frequency: 50/60Hz
- Cable Length: 1.3m
- Appliance Dimensions
- Exhaust(H x W x D):
- 799-975 x 900 x 500 mm
- Recirculate (HxWxD):
- 799-975 x 900 x 500 mm





DIB091E51

90cm | Island Hood

Performance

- Max extraction rate: 1000m³/h, according to EN 61591
- Suitable for ducted or re-circulated operation
- Operating sound level: 60db

Features

- Twin channel high performance fan motor
- EcoSilence™ Drive
- 3 speed plus 2 intensive settings
- Softlight with dimmer function
- 4 x 3W LED lighting
- Automatic run on: 10 mins
- Intensive operation revert: 6 mins

Convenience

• Dishwasher safe metal grease filter

Technical Information

- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1.3m
- Appliance dimensions
- Exhaust (H x W x D): 744 - 924 x 900 x 600mm
- Recirculate (H x W x D): 744 - 1044 x 900 x 600mm

DIB121U50

120cm | Island Hood

Performance

- Max extraction rate: 890m³/h, according to EN 61591
- Suitable for ducted or re-circulated operation
- Operating sound level: 62db

Features

- Twin channel high performance fan motor
- EcoSilence[™] Drive
- 3 speed plus 2 intensive settings
- Softlight with dimmer function
- 4 x 3W LED lighting
- Automatic run on: 5 / 10 / 15 mins
- Intensive operation revert: 6 mins
- · Rim ventilation
- · Air quality sensor

Convenience

- Dishwasher safe metal grease filter
- Inner frame

- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1.3m
- Appliance dimensions
- Exhaust (H x W x D): 744 – 924 x 1200 x 650mm
- Recirculate (H x W x D): 744 – 1044 x 1200 x 650mm





DWF97RU60

90cm | Flat design with glass canopy Hood (wall-mounted)

Performance

- Max extraction rate: 420m³/h, according to EN 61591
- Suitable for ducted or re-circulated operation
- Operating sound level: 57db

Features

- Twin channel high performance fan motor
- EcoSilence[™] Drive
- 3 speed plus 2 intensive settings
- Softlight with dimmer function
- 4 x 3W LED lighting
- Automatic run on: 5 / 10 / 15 mins
- Intensive operation revert: 6 mins
- Rim ventilation
- · Air quality sensor

Convenience

- Dishwasher safe metal grease filter
- Inner frame

Technical Information

- Voltage: 220 240V
- Power frequency: 50 / 60Hz
- Cable length: 1.3m
- Appliance dimensions
- Exhaust (H x W x D): 744 - 924 x 1200 x 650mm
- Recirculate (H x W x D): 744 – 1044 x 1200 x 650mm

DDA097G59B

90cm | Downdraft Hood

Performance

- Max extraction rate: 710m³/h, according to EN 61591
- Suitable for ducted or re-circulated operation
- Operating sound level: 61db

Features

- Twin channel high performance fan motor
- 1 x 10W LED-module
- 4 speed plus intensive settings
- Automatic run on: 15 mins
- Intensive operation revert: 6 mins
- Rim ventilation

Convenience

• Dishwasher safe metal grease filter

- Voltage: 220 240V
- Power frequency: 50Hz
- Cable length: 1.5m
- Appliance dimensions
- Exhaust and Recirculate (H x W x D): 651 - 1052 x 912 x 351mm

Customer service support you can depend on.

Trust Bosch customer service to help you throughout the lifetime of your appliance.





Experts repairs from our qualified engineers with only original spare parts



Added peace of mind with our extended warranty plans



Bosch online store offers you the convenience to get your cleaning & care products, that will enhance the performance of your appliance



Our Customer Call Center is available from Monday to Friday 9am to 6pm and Saturday 9am to 1pm at (65) 6751 5000. Closed on Sunday and Public Holidays.



Create a MyBosch account to register your appliance warranty



All Bosch home appliances are produced with maximum care, in high quality materials. We promise it in our 2-year manufacturer's warranty on all appliances.

For service repair and spare parts replacement, please contact:

Customer Care Line:

(65) 6751 5000

Customer Service Center:

38C Jalan Pemimpin #01-01 Singapore 577180

Operating Hours:

Monday to Friday, 8.30am to 5.30pm (Excluding Public Holidays)

Whilst every care has been taken in the preparation of this publication, Bosch does not warrant the accuracy or completeness of the information in this publication and Bosch reserves the right to alter specifications without notice. To the extent permitted by law, Bosch excludes all liability, including negligence, for any loss incurred in reliance on the contents of this publication. Copyright 2019 by BSH Home Appliances Pte Ltd. Company registration number: 199608497E. Printed in Singapore.

BSH Home Appliances Pte. Ltd. (Reg. No: 199608497E)

11 Bishan Street 21 Bosch Building #04-01 Singapore 573943

Toll Free: 1800-MY-BOSCH (1800-69-26724)

Fax: (65) 6507 3818

www.bosch-home.com.sg