

**Serie | 8, Integrated rangehood, 86 cm, Stainless steel
DHL895CAU**



The integrated rangehood: offers a sleek and seamless design in the kitchen with fully integrated installation.

- **Extraction rate:** at 820 m³/h, it quickly ensures optimal kitchen air quality.
- **LED lighting:** for perfect, energy-efficient illumination of the cooktop.
- **Intensive speed setting with reset:** automatically resets the hood to regular speed setting after 6 min.
- **Especially quiet:** high performance at just 64 dB.

Technical Data

Typology :	Traditional
Approval certificates :	Australia Standards, CE, VDE
Length electrical supply cord (cm) :	150
Required niche size for installation (HxWxD) :	418mm x 836.0mm x 264mm
Minimum distance above an electric hob :	500
Minimum distance above a gas hob :	650
Net weight (kg) :	10.114
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	610
Boost position output recirculating (m ³ /h) :	370.0
Boost position air extraction (m ³ /h) :	820
Number of lights :	2
Noise level (dB) :	64
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242002831428
Connection Rating (W) :	272
Current (A) :	3
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	AU plug
Installation typology :	Built-in

Optional accessories

DHZ5605 : Standard recirculation kit



4 242002 831428

**Serie | 8, Integrated rangehood, 86 cm,
Stainless steel
DHL895CAU**

The integrated rangehood: offers a sleek and seamless design in the kitchen with fully integrated installation.

Design & Innovation

- 86 cm Fully integrated rangehood
- Appliance colour: Stainless steel

Power and Mode of Operation

- 3 power settings plus intensive setting
- Extraction rate according to EN 61591 \varnothing 15 cm:
 - max. Normal use 610 m³/h
 - Intensive 820 m³/h
- Ducted and recirculated-air operation
- Accessories required for recirculation mode: CleanAir Module
- Electronic controls with green Electronic display
- EcoSilence BLDC brushless motor
- Rim ventilation
- Noise min./max. Normal Level: 41/64 dB
 - Noise max. Intensive setting: 71 dB
- Power rating: 272 W

Comfort & Convenience

- Dishwasher safe metal grease filters
- Intensive operation automatic revert - 6min
- Automatic run on for Automatic run on time - 30 min
- 2 x 1 Watt LED lights
- Saturation display for filters

2 year warranty

Dimensions (HxWxD)

- Dimensions exhaust air (HxWxD): 418-418 x 860 x 282 mm
- Dimensions recirculating (HxWxD): 418-418 x 860 x 282 mm
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- Electrical cable length 1.5 m