

Serie | 6, wall-mounted cooker hood,
90 cm, Stainless steel
DWB091E51A



Optional accessories

DHZ5345 : Standard recirculation kit
DSZ6240 : CleanAir Recirculation Kit

The wall-mounted rangehood: a functional
design element in the kitchen.

- **Extraction rate:** at 810 m³/h, it quickly ensures optimal kitchen air quality.
- **Especially quiet:** high performance at just 66 dB.
- **LED lighting:** for perfect, energy-efficient illumination of the cooktop.
- **Intensive speed setting with reset:** automatically resets the hood to regular speed setting after 6 min.

Technical Data

Typology :	Chimney
Approval certificates :	Australia Standards, CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-908/582-1018
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	20.313
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m ³ /h) :	610
Boost position output recirculating (m ³ /h) :	480.0
Boost position air extraction (m ³ /h) :	810
Number of lights :	3
Noise level (dB) :	66
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
EAN code :	4242002780368
Connection Rating (W) :	269
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	AU plug
Installation typology :	Wall-mounted



4 242002 780368

**Serie | 6, wall-mounted cooker hood, 90 cm,
Stainless steel
DWB091E51A**

**The wall-mounted rangehood: a functional
design element in the kitchen.**

Technical Information

- Appliance width: 900 mm
- Dimensions exhaust air (HxWxD): 628-954 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
689 x 900 x 500 mm - mounting with outer chimney
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Electrical cable length 1.3 m

Design

- Box design
- Appliance colour: Stainless steel

Power and Mode of Operation

- 3 power levels + 2 intensive levels
- Extraction rate exhaust air according to EN 61591: max. 610 m³/h
- Extraction rate in recirculation mode:
Max. normal use: 400 m³/h
- Ducted and recirculated-air operation
- Accessories required for recirculation mode: CleanAir Module
- Electronic controls with red LED display
- EcoSilence BLDC brushless motor
- Rim ventilation
- Noise min./max. Normal Level: 44/66 dB
Noise max. Intensive setting: 72 dB
- Noise level in recirculation mode:
Max. normal use: 72 dB(A) re 1 pW (58 dB(A) re 20 µPa sound pressure)
- Energy Efficiency Class: A (at a range of energy efficiency classes from A++ to E)
- Average Energy Consumption: 34.4 kWh/year
- Power rating: 269 W

Comfort & Convenience

- with one-way flap: prevents outside air from entering your kitchen
- Dishwasher safe metal grease filters
- Saturation display for filters
- Intensive operation automatic revert - 6min
- Automatic run on for Automatic run on - 10 min
- Additional sound insulation mats for optimised sound absorption
- 3 x 3 Watt LED Lights
- SoftLight with dimming function

Serie | 6, wall-mounted cooker hood, 90 cm, Stainless steel DWB091E51A

