

## Series 8, Built-in oven, 60 x 60 cm, Stainless steel HBG6767S1A











HEZ327000 Pizza stone, HEZ530000 Half tray, HEZ531010 Baking tray, non-stick ceramic coated, HEZ532010 Universal pan, non-stick ceramic coated, HEZ617000 Pizza pan, enamelled, HEZ625071 Grill tray, anthracite, HEZ631070 Baking tray, enamelled, HEZ632070 Multipurpose pan, enamelled, HEZ633001 Lid for professional pan, enamelled, HEZ633070 Professional pan with grid, enamelled, HEZ634000 Baking and roasting grid, HEZ635000 Barbecue-Set, HEZ636000 Glass pan, HEZ638370 3 level telescopic rails, full ext,pyro, HEZ660050 Cover Strip, HEZ664000 Baking and roasting grid, steam, HEZ915003 Glass roasting dish, 5,4 L

# The Series 8 built-in oven with PerfectBake and PerfectRoast: you get perfect baking and roasting results – automatically.

- 4D Hotair: even heat distribution on all levels for perfect baking results without mixing flavours.
- Assist: sets the optimal type of heat, temperature and time automatically for a wide range of dishes.
- TFT touchdisplay: easy and intuitive oven control with touchscreen.
- Pyrolytic self-cleaning: effortless cleaning thanks to pyrolytic cleaning programs.
- Flap door with SoftOpen and SoftClose: the oven door opens and closes especially gently and quietly.

| Dimensions (HxWxD):       595x594x548 mm         Dimensions of the packed product (HxWxD):       670 x 660 x 690 mm         Min. required niche size for installation (HxWxD):       585-595 x 560-568         x 550 mm       357 x 480 x 415 mm         Cavity dimensions:       71 l         Usable volume of cavity:       71 l         Number of interior lights:       1         Net weight:       41.1 kg         Gross weight:       43.6 kg         EAN code:       4242002827032         Connection rating:       3600 W         Fuse protection:       16 A         Voltage:       220-240 V         Frequency:       60; 50 Hz         Length electrical supply cord:       120.0 cm | Color / Material Front:  Built-in / Free-standing:  Door opening:  Cleaning:  Control Panel Material:  Door Material: | Built-inDrop downPyrolytic+HydrolyticStainless steelGlass |  |
|---|---|---|--|
| Min. required niche size for installation (HxWxD): 585-595 x 560-568 x 550 mm         Cavity dimensions:  | Dimensions (HxWxD):   | 595x594x548 mm  |  |
| x 550 mm         Cavity dimensions:   | Dimensions of the packed product (HxWxD): 670 x 660 x 690 mm  |   |  |
| Usable volume of cavity:       .71 l         Number of interior lights:       .1         Net weight:       .41.1 kg         Gross weight:       .43.6 kg         EAN code:       .4242002827032         Connection rating:       .3600 W         Fuse protection:       .16 A         Voltage:       .220-240 V         Frequency:       .60; 50 Hz   | •   | WxD): 585-595 x 560-568                                   |  |
| Usable volume of cavity:       .71 l         Number of interior lights:       .1         Net weight:       .41.1 kg         Gross weight:       .43.6 kg         EAN code:       .4242002827032         Connection rating:       .3600 W         Fuse protection:       .16 A         Voltage:       .220-240 V         Frequency:       .60; 50 Hz   | Cavity dimensions:  | 357 x 480 x 415 mm  |  |
| Net weight:       41.1 kg         Gross weight:       43.6 kg         EAN code:       4242002827032         Connection rating:       3600 W         Fuse protection:       16 A         Voltage:       220-240 V         Frequency:       60; 50 Hz   |   |   |  |
| Gross weight:       43.6 kg         EAN code:       4242002827032         Connection rating:       3600 W         Fuse protection:       16 A         Voltage:       220-240 V         Frequency:       60; 50 Hz   | Number of interior lights:  | 1   |  |
| EAN code:       .4242002827032         Connection rating:       .3600 W         Fuse protection:       .16 A         Voltage:       .220-240 V         Frequency:       .60; 50 Hz  | Net weight:   | 41.1 kg   |  |
| Connection rating:       3600 W         Fuse protection:       16 A         Voltage:       220-240 V         Frequency:       60; 50 Hz   | Gross weight:   | 43.6 kg   |  |
| Fuse protection:  | EAN code:   | 4242002827032   |  |
| Voltage:  | Connection rating:  | 3600 W  |  |
| Frequency:  | Fuse protection:  | 16 A  |  |
|   | Voltage:  | 220-240 V   |  |
|   | Frequency:  | 60; 50 Hz   |  |
|   |   |   |  |





## Series 8, Built-in oven, 60 x 60 cm, Stainless steel HBG6767S1A

# The Series 8 built-in oven with PerfectBake and PerfectRoast: you get perfect baking and roasting results – automatically.

## **Heating Functions**

- Oven with 13 heating methods:
- 4D HotAir
- Defrost
- Full width grill
- 4D HotAir Eco
- Half width grill
- Top/bottom heating
- Top/bottom heating Eco
- Pizza setting
- Slow cooking
- Bottom heating
- Hot air grilling
- Preheat ovenware
- Keep warm
- Rapid heating-up: automatic
- Temperature range 30 °C 300 °C

### Sensor Technology & Automatic Programs

- Bosch Assist a menu of dishes for automatic cooking
- PerfectBake baking sensor
- $PerfectRoast\ multipoint\ meat\ probe$

## Design

- TFT Touch Graphic Display
- Bosch Control Ring
- Halogen lighting
- Cavity volume: 71 net usable litres
- Anthracite enamel cavity with 5 shelf positions

## Cleaning

- Pyrolytic self-cleaning function
- Pyrolitic proof trayholder and baking tray
- Full glass inner door

### Convenience

- Automatic temperature proposal
- Actual temperature display
- Residual heat indicator
- Meat probe function
- Sabbath setting
- Cavity with shelf support rails, 2 level telescopic shelf rails, fully extendable, safety stop function, pyrolitic proof
- Electronic clock/timer with end time programming
- Info button

# Safety and Environment

- Quadruple glazed CoolTouch door

- Electronic door lock
- Child lock function
- Automatic safety switch off function
- Residual heat indicator
- Start button
- Door contact switch
- Cooling fan

#### 2 year warranty

#### **Accessories**


- 1 x grill tray, suit. pyrol. clean., 2 x combination grid, 1 x universal pan

## **Technical Info**

- Appliance dimensions (HxWxD): 595 mm x 594 mm x 548 mm
- Installation dimensions (HxWxD): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Total connected load electric: 3.6 KW
- Length of mains cable: 120 cm



# Series 8, Built-in oven, 60 x 60 cm, Stainless steel HBG6767S1A



measurements in mm

min. 550 min. 35

585<sup>+10</sup>

min. 35

60

595

595

594

594

Space for appliance connection 320 x 115

measurements in mm

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

| Hob type                      | min. worktop thickness |       |
|-------------------------------|------------------------|-------|
|                               | fitted                 | flush |
| Induction hob                 | 37 mm                  | 38 mm |
| Full surface<br>Induction hob | 47 mm                  | 48 mm |
| Gas hob                       | 30 mm                  | 38 mm |
| Electric hob                  | 27 mm                  | 30 mm |

