

Series 8, Built-in oven with added steam function, 60 x 60 cm, Black HRG6769B2A











HEZ327000 Pizza stone, HEZ530000 Half tray, HEZ531010 Baking tray, non-stick ceramic coated, HEZ532010 Universal pan, non-stick ceramic coated, HEZ617000 Pizza pan, enamelled, HEZ625071 Grill tray, anthracite, HEZ631070 Baking tray, enamelled, HEZ632070 Multipurpose pan, enamelled, HEZ633001 Lid for professional pan, enamelled, HEZ633070 Professional pan with grid, enamelled, HEZ634000 Baking and roasting grid, HEZ635000 Barbecue-Set, HEZ636000 Glass pan, HEZ660050 Cover Strip, HEZ664000 Baking and roasting grid, steam, HEZ915003 Glass roasting dish, 5,4 L

The Series 8 built-in oven with PerfectBake, PerfectRoast and added steam: automatically prepares your dishes so they're perfect and moist.

- Pyrolytic self-cleaning: Automatically cleans the oven, just wipe out the ash
- 3-stage telescoping rails, fully extendable: for safe, easy insertion and removal of baking trays.
- Added Steam: achieve cooking results that are crispy on the outside and juicy on the inside.
- TFT touchdisplay: easy and intuitive oven control with touchscreen.
- 4D Hotair: even heat distribution on all levels for perfect baking results without mixing flavours.

Color / Material Front:	Built-in
Door opening:	
Cleaning:	
Control Panel Material:	
Door Material:	Glass
Dimensions (HxWxD):	595x594x548 mm
Dimensions of the packed product (HxWx	ED): 650 x 650 x 680 mm
Required niche size for installation (HxW)	xD):585-595 x 560-568 x
550 mm	
Cavity dimensions:	357 x 480 x 415 mm
Usable volume of cavity:	
Number of interior lights:	3
Net weight:	46.9 kg
Gross weight:	
EAN code:	
Connection rating:	3600 W
Fuse protection:	
Voltage:	220-240 V
Frequency:	
Length electrical supply cord:	





Series 8, Built-in oven with added steam function, 60 x 60 cm, Black HRG6769B2A

The Series 8 built-in oven with PerfectBake, PerfectRoast and added steam: automatically prepares your dishes so they're perfect and moist.

Heating Functions

- Oven with 15heating methods:
- 4D HotAir, Defrost, Drying, Full width grill, 4D HotAir Eco, Intensive heat, Half width grill, Top/bottom heating, Top/bottom heating Eco, Pizza setting, Slow cooking, Bottom heating, Hot air grilling, Preheat ovenware, Keep warm
- Additional heating methods with steam: Reheating, Dough Proving
- Automatic rapid heat function
- Bosch Assist a menu of dishes for automatic cooking
- PerfectBake baking sensor, PerfectRoast multipoint meat probe
- Temperature range 30 °C 300 °C

Design

- TFT Touch Graphic Display
- LED light, Multi-level LED lighting
- Cavity volume: 71 net usable litres
- Cavity inner surface: enamel

Cleaning

- Pyrolytic self-cleaning function
- Additional functions: Descaling programme
- drying function
- Cleaning Assistance cleaning option for light soiling

Racks and Rails

- Automatic temperature proposal, Residual heat indicator, Actual temperature display, Meat probe function
- Number of shelf levels: 5

Convenience

- Drop down door
- 3-level telescopic rails, pyrolitic proof, fully extendable, safety stop function
- Electronic clock/timer with end time programming
- Water tank empty indicator
- Location of the steam generator is outside of the cavity

Safety Features

- Quadruple glazed CoolTouch door
- Maximum door temperature 30° C
- Low door temperature during pyrolytic cleaning
- Electronic door lock, Child lock, Automatic safety switch off function, Residual heat indicator, Start button, Door contact switch
- Integrated cooling fan

Accessories

- 1 x grill tray, suit. pyrol. clean., 2 x combination grid, 1 x universal pan

Dimensions

- Appliance dimensions (HxWxD): 595 mm x 594 mm x 548 mm


- Installation dimensions (HxWxD): 585 mm - 595 mm x 560 mm - 568 mm x 550 mm


Technical Information

- Length of mains cable: 120 cm
- Nominal voltage: 220 240 V
- Total connected load electric: 3.6 KW
- Please reference the built-in dimensions provided in the installation drawing



Series 8, Built-in oven with added steam function, 60 x 60 cm, Black HRG6769B2A





measurements in mm

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm

