

**Series 8, Gas cooktop, 60 cm,
Ceramic glass, Black
PRP6A6B70A**



HEZ298105 Simmer plate
HEZ298114 Small pot support

**The ceramic glass gas cooktop with
FlameSelect: achieve perfect cooking
results thanks to nine precisely defined
power levels.**

Product name/family:gas hob w integrated controls
Built-in / Free-standing: Built-in
Energy input:Gas
Total number of positions that can be used at the same time: 4
Type of control setting devices:Sword knobs
Required niche size for installation (HxWxD): 45 x 560-562 x 490-502 mm
Width of the appliance: 606 mm
Dimensions (HxWxD): 47x606x527 mm
Dimensions of the packed product (HxWxD): 170 x 670 x 580 mm
Net weight: 12.1 kg
Gross weight: 13.3 kg
Residual heat indicator: without
Location of control panel: Front
Basic surface material:Ceramic glass
Color of surface:Black, Alu, brushed
Color of frame: Black
Length electrical supply cord: 100.0 cm
EAN code:4242005429721
Gas connection rating: 7700 W
Fuse protection:3 A
Voltage: 220-240 V
Frequency: 50-60 Hz



Series 8, Gas cooktop, 60 cm, Ceramic glass, Black PRP6A6B70A

**The ceramic glass gas cooktop with
FlameSelect: achieve perfect cooking
results thanks to nine precisely defined
power levels.**

Design

- Black Ceramic glass surface
- aluminium, brushed, side profiles
- Enamelled cast-iron trivets with rubber feet

Usage convenience

- FlameSelect (9 steps): precisely adjust the flame in nine defined and consistent levels.
- Dishwasher safe pan supports: clean without effort in the dishwasher.
- Sword control knobs: easily access knobs in front with strong grip for effortless turning.
- One-hand electronic ignition via controls: just push and turn the knob to ignite the flame.

Burners and power

- 4 Gas burners
- Left front: Standard burner up to 7.9 Mj (depending on gas type)
- Left rear: Economy burner up to 4.5 Mj (depending on gas type)
- Right rear: High-speed burner up to 11.6 Mj (depending on gas type)
- Right front: Standard burner up to 8.1 Mj (depending on gas type)

Safety

- Flame failure device fitted to each individual burner: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Preset of natural gas (10mbar)
- Nozzle set for Liquid gas nozzles (28-30/37mbar) included.
- Dimensions of the product (HxWxD mm): 47 x 606 x 527
- Required niche size for installation (HxWxD mm) : 45 x 560 x (490 - 502)
- Min. worktop thickness: 30 mm
- Power cord 1 m cable with plug.