

Serie | 8, Built-under dishwasher, 60 cm, Stainless steel SMU88TS01A



















Optional accessories

SGZ1010: inlet and outlet hose extention

SMZ5100 : Vario-cutlery basket SMZ5300: GlassSecure Tray

The ActiveWater 60 with Super 60°C programme, 15 place settings and TFT display: brilliant cleaning and drying results.

- Super 60°C programme: brilliant cleaning and drying results.
- 4.0 star energy & 5.0 star water rating: High energy efficiency and low water consumption
- SuperSilence: Operates at low noise level of 42 dB.
- HygienePlus: Extra hot final rinse kills 99.9% of bacteria.
- VarioFlex Pro basket system & VarioDrawer Pro: visibly more flexibility & loading capacity.

Technical Data

Water consumption (I): 12.0 Built-in / Free-standing: Built-in Height of removable worktop (mm):

Required niche size for installation (HxWxD):

815-875 x 600 x 550 Depth with open door 90 degree (mm): 1150 Adjustable feet: Yes - front only Maximum adjustability feet (mm): 60 Net weight (kg): 41.412 44.0 Gross weight (kg): Connection Rating (W): 2400 Current (A): 10 Voltage (V): 220-240

50; 60 Frequency (Hz): Length electrical supply cord (cm): 175 AU plug Plug type: Length inlet hose (cm): 165 Length outlet hose (cm): 190 4242002844152 EAN code: Number of place settings :

0.64 Energy consumption (kWh): Reference programme: Eco Total cycle time of reference programme (min): 170

Built-under Installation typology:



15



Serie | 8, Built-under dishwasher, 60 cm, Stainless steel SMU88TS01A

The ActiveWater 60 with Super 60°C programme, 15 place settings and TFT display: brilliant cleaning and drying results.

Capacity

- 15 international place settings

Consumption rates

- 4 Star energy rating, 5 Star WELS water rating
- 12 litres water consumption per wash and 235kWh energy consumption, based on Eco 45°C program

Design

- Built-under Dishwasher 60 cm wide
- Stainless steel finish
- Stainless steel interior tub
- Effortless door closing
- SoftTouch buttons
- Hidden control buttons integrated into the top of the door

Wash Programs and Options

- 8 programs:

Auto 35-45°C

Auto 45-65°C

Auto 65-75°C

Super 60°C

Eco 45°C

Glass 40°C

Quick wash 45°C

Pre-Rinse

- 5 special options:

HalfLoad Plus: For half loads, reduces energy, water & time ExtraDry: Provides an even better drying result VarioSpeed™: Up to 50% faster wash time IntensiveZone™: Powerful cleaning in the bottom basket HygienePlus™: Removes bacteria from utensils & crockery

Performance

- ActiveWater™: Automatic load adjustment recognises the load condition in three steps and ensures that only the amount of electricity and water required for that load is used
- DosageAssist™: Maximises the effectiveness of detergent tablets. The tablet is dropped into a specially engineered

tray and is completely dissolved. For superior cleaning performance and a quieter wash.

 EcoSilence Drive® quiet and energy-efficient brushless motor (BLDC)

BLDC Main Pump: Variable water & spray pressure to achieve optimum cleaning results

BLDC Drain Pump: Fast and extra quiet draining of water, no gargling sounds

- AquaSensor™ technology: Regulates the water usage depending on the type and degree of soiling LoadSensor technology: Provides for optimal water usage even for half loads or partial loads, saving water and electricity
- AutoBrilliance™: Automatic detergent and rinse aid sensor
- Heat Exchanger: Hygienic drying with energy & water efficiency
- 3 stage self-cleaning filter system
- Alternating spray-arm washing
- 5 Spray levels

Flexibility

- VarioDrawer™ Pro: Third loading level for cutlery & utensils
- VarioFlex™ Pro basket system with red coloured touchpoints
- 6 foldable plate racks in top basket
- 8 foldable plate racks in bottom basket
- 2 foldable cup shelves in top basket
- 2 foldable cup shelves in bottom basket
- RackmaticPlus™: 3-stage top basket can be adjusted to three height levels to maximise convenience
- Glass rack in lower basket for tall stemmed glasses
- Large item spray head: For washing extra large items such as baking trays and rangehood filters
 Vapor barrier protection plate

Convenience

- SuperSilence: Operates at low noise level of 42dB
- TFT Display in full colour on front panel
- TFT Display in full colour on inner door
- Audible program end
- Real time clock actual time display
- Time delay start: Delay programme start time by 1-24 hours to suit your schedule
- Electronic rinse aid indicator

Safety


- AquaStop™ Plus: Water supply device with lifetime anti-flood protection
- Child door lock
- 10 year rust-through warranty for the inner tub
- 2 year warranty

Dimensions


- 815-875 mm x 598 mm x 573 mm




Serie | 8, Built-under dishwasher, 60 cm, Stainless steel SMU88TS01A



measurements in mm



() Werte mit Verlängerungssatz



* Can be set using height-adjustable screw feet Base height (when appliance height is 815) - 95 mm Base height (when appliance height is 875) - 155 mm

measurements in mm