

**500 Series, Wall Hood, 36", Stainless steel
HCB56651UC**



Optional accessories

HCBEXT5UC : Chimney Extension Kit for HCB Box Hood

HCIFILTUC : Filter Replacement for all Chimney Wall

HCREC5UC : Recirculation Kit for all Chimney Wall

Wall Mounted Chimney Hoods Add Style and Sophistication to the Kitchen and Gives You Greater Freedom in Your Kitchen Planning

- Quiet At 2.1 Sones On Low Speed
- Four Power Levels
- Converts to Recirculation Mode with Accessory Kit (Separate Purchase Required)
- Absorb odors with Charcoal Replacement Filters (Available for sale)

Technical Data

Operating Mode :	Convertible: Ducted / Recirculating
Number of speed settings :	4-stage
Optional accessories :	HCBEXT5UC, HCIFILTUC, HCREC5UC
Number of lights :	2
Type of lamps used :	Halogen
Grease filter material :	Washable stainless steel
Grease filter type :	Multilayer cassette
UPC code :	825225909057
Material :	Stainless steel
Watts (W) :	530
Volts (V) :	110
Frequency (Hz) :	60
Approval certificates :	CUL, UL
Power cord length (cm) :	0
Plug type :	no plug
Overall appliance dimensions (HxWxD) (in) :	27 1/16" - 42 1/8 " / 27 1/16" - 45 13/16" x 36"
Overall appliance dimensions (HxWxD) (mm) :	687 - 1164 x 914.0 x 500.0
Product packaging dimensions (HxWxD) (in) :	26.25 x 39.99 x 17.99
Product packaging dimensions (HxWxD) (mm) :	666 x 1016 x 457
Height of the chimney (in) :	25 1/2" - 40 9/16"/25 3/8" - 44 1/4"
Height of the chimney (mm) :	647-1031/647-1124
Required distance above cooktop/ranges :	24"/27"
Net weight (lbs) :	55.000
Net weight (kg) :	25.137
Gross weight (lbs) :	62.000
Gross weight (kg) :	28.2
Motor location :	Integrated motor in hood chimney
Diameter of air duct (in) top :	8
No-return airflow flap :	Yes

500 Series, Wall Hood, 36", Stainless steel HCB56651UC

Wall Mounted Chimney Hoods Add Style and Sophistication to the Kitchen and Gives You Greater Freedom in Your Kitchen Planning

Design

- Duct Extension Accessory Kit Available for 9' to 11.5' Ceilings

Performance

- 2 Halogen Lights - 12 Volt, 20 Watt Max., G-4 Base
- 8" round duct at discharge.

Efficiency

- Blower will automatically turn on at high speed if excessive heat is sensed in the control area.
- Absorb odors with charcoal replacement filters.

Convenience

- Convenient timer built into control from 1-60 minutes.
- Signal on LCD display will illuminate as a reminder to check filters for cleaning.
- Audible tone when select controls are pressed.

500 Series, Wall Hood, 36", Stainless steel HCB56651UC

