

**Benchmark®, Wall Hood, 36",
Stainless steel
HCG56651UC**



Optional accessories

HCGEXT5UC : Chimney Extension Kit for HCG Glass Hood

HCIFILTUC : Filter Replacement for all Chimney Wall

HCREC5UC : Recirculation Kit for all Chimney Wall

Wall Mounted Chimney Hoods Add Style and Sophistication to the Kitchen and Gives You Greater Freedom in Your Kitchen Planning

- Four Power Levels
- Converts to Recirculation Mode with Accessory Kit (Separate Purchase Required)
- Absorb odors with Charcoal Replacement Filters (Available for sale)

Technical Data

Operating Mode :	Convertible: Ducted / Recirculating
Number of speed settings :	4-stage
Optional accessories :	HCGEXT5UC, HCIFILTUC, HCREC5UC
Number of lights :	2
Type of lamps used :	Halogen
Grease filter material :	Washable stainless steel
Grease filter type :	Multilayer cassette
UPC code :	825225909064
Material :	Glass
Watts (W) :	530
Volts (V) :	120
Frequency (Hz) :	60
Approval certificates :	CSA, UL
Power cord length (cm) :	0
Plug type :	no plug
Overall appliance dimensions (HxWxD) (in) :	27 7/16" - 42 3/8" / 27 7/16" - 46 5/16" x 35 7/8"
Overall appliance dimensions (HxWxD) (mm) :	697 - 1177 x 911.0 x 500.0
Product packaging dimensions (HxWxD) (in) :	26.25 x 39.99 x 17.75
Product packaging dimensions (HxWxD) (mm) :	666 x 1016 x 450
Height of the chimney (in) :	25 7/8" - 40 13/16"/25 7/8" - 44 3/4"
Height of the chimney (mm) :	657-1037/657-1137
Required distance above cooktop/ranges :	24"/27"
Net weight (lbs) :	56.000
Net weight (kg) :	25.547
Gross weight (lbs) :	63.000
Gross weight (kg) :	28.6
Motor location :	Integrated motor in hood chimney
Maximum CFM :	600
Diameter of air duct (in) top :	8
No-return airflow flap :	Yes

Benchmark®, Wall Hood, 36", Stainless steel HCG56651UC

Wall Mounted Chimney Hoods Add Style and Sophistication to the Kitchen and Gives You Greater Freedom in Your Kitchen Planning

- Touch Controls with LCD Display
- 600 CFM Centrifugal Integrated Blower Included
- Four Speed Touch Controls with LCD Display
- Dishwasher Safe Filters with Stainless Steel Covers
- Converts to Recirculation Mode with Accessory Kit (Separate Purchase Required)

Design

- Duct Extension Accessory Kit Available for 9' to 11.5' Ceilings

Performance

- 2 Halogen Lights - 12 Volt, 20 Watt Max., G-4 Base
- 8" round duct at discharge.

Efficiency

- Blower will automatically turn on at high speed if excessive heat is sensed in the control area.
- Absorb odors with charcoal replacement filters.

Convenience

- Convenient timer built into control from 1-60 minutes.
- Signal on LCD display will illuminate as a reminder to check filters for cleaning.
- Audible tone when select controls are pressed.

Benchmark®, Wall Hood, 36", Stainless steel HCG56651UC

