

**Series 4, wall-mounted cooker hood,
60 cm, , Stainless steel
DWG66CD50Z**



**The wall-mounted chimney hood: mount it
on the wall, giving you complete freedom
in your kitchen planning.**

- **Silence:** maximal extractor performance with little noise
- **Dishwasher safe aluminum mesh filters**
- **Converts to Recirculation Mode with Accessory Kit (Separate Purchase Required)**

Color chimney: Stainless steel
 Typology: Wall-mounted
 Length electrical supply cord: 100.0 cm
 Height of the chimney: 730-890/730-1000 mm
 Net weight: 15.2 kg
 Type of control: Electronic
 Number of speed settings: 3-stages + intensive setting
 Max. air extraction: 620 m³/h
 Boost position output recirculating: 440.0 m³/h
 Max. air recirculation: 415 m³/h
 Boost position air extraction: 700 m³/h
 Number of lights: 2
 Noise level: 63 dB(A) re 1 pW
 Diameter of air outlet: 150 mm
 Grease filter material: Washable aluminium
 Odour filter: No
 Operating Mode: Exhaust / Recirculation (Accessory available separately)
 Type of lamps used: LED
 Total power of the lamps: 2 W
 Grease filter type: Kassette
 Clean filter reminders: No
 Connection rating: 252 W
 Voltage: 220-240 V
 Frequency: 50-60 Hz
 Plug type: No plug (electrical connection by electrician)
 Installation typology: Wall-mounted
 Material body: Stainless steel, Glass
 Plug type: No plug (electrical connection by electrician)
 Dimensions of the product, with chimney (if exists) (in): x x
 Dimensions of the packed product: 24.01 x 28.74 x 21.25
 Net weight: 34.000 lbs
 Gross weight: 47.000 lbs
 Motor location: Integrated motor in hood chimney
 No-return airflow flap: No
 Length electrical supply cord: 100.0 cm
 Dimensions of the product, with chimney (if exists): 778-1048 x 598.0 x 520.0 mm
 Dimensions of the packed product (HxWxD): 610 x 730 x 540 mm
 Net weight: 15.2 kg
 Gross weight: 21.5 kg



4 242002 985398

**Series 4, wall-mounted cooker hood,
60 cm, , Stainless steel
DWG66CD50Z**

**The wall-mounted chimney hood: mount it
on the wall, giving you complete freedom
in your kitchen planning.**

- Brushed steel with glass canopy

Technical information

- 2 X 1W LED Illumination
- Suitable for ducted or re-circulated extraction
- 3 speeds plus intensive setting
- Metal grease filter, dishwasher safe
- Extraction rate exhaust air according to EN 61591:
 - max. normal use: 620 m³/h, intensive 700 m³/h
- Noise level according to EN 60704-2-13 exhaust air:
 - Max. normal use: 68dB(A) re 1 pW
 - Intensive: 71 dB(A) re 1 pW
- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Power rating: 252 W
- Dimensions exhaust air (HxWxD): 778-938 x 598 x 520 mm
- Dimensions recirculating (HxWxD): 778-1048 x 598 x 520 mm

**Series 4, wall-mounted cooker hood,
60 cm, , Stainless steel
DWG66CD50Z**

