

Series 2, wall-mounted cooker hood, 60 cm, Stainless steel DWP64CC50Z



DWA0KP6A Standard odor filter
DWZ6HP1U2 Standard recirculation kit

The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- **Silence:** maximal extractor performance with little noise
- **3-Speed Power Level Options To Suit Your Cooking Style And Recipes**
- **Dishwasher safe aluminum mesh filters**
- **Ducted or Non-ducted Options**

Color chimney: Stainless steel
Typology: Wall-mounted
Length electrical supply cord: 120.0 cm
Height of the chimney: 410-765/410-765 mm
Height of product, without chimney: 250 mm
Net weight: 7.6 kg
Type of control: mechanical
Number of speed settings: 3
Max. air extraction: 380 m³/h
Max. air recirculation: 235 m³/h
Number of lights: 2
Noise level: 64 dB(A) re 1 pW
Diameter of air outlet: 150 mm
Grease filter material: Washable aluminium
Odour filter: No
Operating Mode: Exhaust / Recirculation (Accessory available separately)
Optional accessories: DWA0KP6A, DWZ6HP1U2
Type of lamps used: LED
Total power of the lamps: 10 W
Grease filter type: Kassette
Clean filter reminders: No
Connection rating: 135 W
Voltage: 220-240 V
Frequency: 50 Hz
Plug type: No plug (electrical connection by electrician)
Installation typology: Wall-mounted
Material body: Stainless steel
Plug type: No plug (electrical connection by electrician)
Dimensions of the product, with chimney (if exists) (in): x x
Dimensions of the packed product: 15.74 x 27.95 x 23.22
Net weight: 17.000 lbs
Gross weight: 27.000 lbs
Motor location: Integrated motor in hood body
No-return airflow flap: No
Length electrical supply cord: 120.0 cm
Dimensions of the product, with chimney (if exists): 790-1015 x 598.0 x 470.0 mm
Dimensions of the packed product (HxWxD): 400 x 710 x 590 mm
Net weight: 7.6 kg
Gross weight: 12.3 kg



4 242002 985336

Series 2, wall-mounted cooker hood, 60 cm, Stainless steel DWP64CC50Z

**The wall-mounted chimney hood: mount it
on the wall, giving you complete freedom
in your kitchen planning.**

Measures:

- 60 cm Chimney hood, Brushed steel
- Wall mounted hood
- Suitable for ducted or re-circulated extraction
- 3 speeds
- 2 x LED 5W
- push buttons
- Extraction rate exhaust air according to EN 61591 max. 380 m³/h
- Metal grease filter, dishwasher safe
- Noise level according to EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW dB(A) re 1 pW
- Dimensions exhaust air (HxWxD): 790 - 1015 x 598 x 470 mm
- Dimensions recirculating (HxWxD): 790 - 1015 x 598 x 470 mm
- Power rating: 135 W
- 150 mm diameter pipe
- Light Intensity: 1000 lux
- Colour Temperature: 4000 K
- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 72.8 kWh/year
- Blower Efficiency Class: E*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: C
- Noise min./max. Normal Level: 53/64 dB

* In accordance with the EU-Regulation No 65/2014

**Series 2, wall-mounted cooker hood,
60 cm, Stainless steel
DWP64CC50Z**

