

**Series 2, Integrated cooker hood, 60 cm, Silver
DEM63AC00B**



Optional accessories

DWZ0IM0A0 : Standard odor filter (replacement)



Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.

- **Silent:** maximum extractor performance with minimal noise.
- **LED illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.
- An impressive extraction rate of m³/h ensures this hood will have your kitchen odour free in no time.
- 3-speed power Level options to suit your cooking style and recipes.
- Ducted or Non-ducted Options

Technical Data

Typology : Built-in/Built-under
Length of electrical supply cord : 150 cm
Minimum distance above an electric hob : 500 mm
Minimum distance above a gas hob : 650 mm
Net weight : 11.5 kg
Type of control : mechanical
Number of speed settings : 3
Maximum output air extraction : 368 m³/h
Maximum output recirculating air : 272 m³/h
Number of lights (Stck) : 2
Noise level : 62 dB(A) re 1 pW
Diameter of air outlet : 150 / 120 mm
Grease filter material : Washable aluminium
EAN code : 4242005041107
Connection rating : 126 W
Fuse protection : 10 A
Voltage : 220-240 V
Frequency : 50; 60 Hz
Plug type : GB plug
Installation type : Wall-mounted



4 242005 041107

Series 2, Integrated cooker hood, 60 cm, Silver DEM63AC00B

Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.

Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 368 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 62 dB dB*

Features

- Push button control for extractor speeds and light
- 3 power levels
- Single motor
- 2 x 3W LED
- Colour Temperature: 2700 K
- 2 removable metal grease filter cassettes
- Installation: Between Cupboards

Design

- Integrated hood
- Push button control
- Mechanical

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction charcoal filter (accessory) needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 62 dB(A) re 1 pW
- Light Intensity: 188 lux
- Electrical cable length 1.5 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating (HxWxD): 402-402 x 599 x 271 mm
- Blower Efficiency Class: E*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 65.7 kWh/year*

Optional accessories

- Recirculating kit DWZ01MOA0

* In accordance with the EU-Regulation No 65/2014

**Series 2, Integrated cooker hood, 60 cm,
Silver
DEM63AC00B**

