

**Serie | 2, Integrated cooker hood, 60 cm, silver
DEM66AC00B**



B

Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.

- **LED Illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.
- An impressive extraction rate of m³/h ensures this hood will have your kitchen odour free in no time.
- 3-speed power Level options to suit your cooking style and recipes.
- Ducted or Non-ducted Options

Technical Data

Typology : Built-in/Built-under
Approval certificates : CE
Length of electrical supply cord : 150 cm
Minimum distance above an electric hob : 500 mm
Minimum distance above a gas hob : 650 mm
Net weight : 11.9 kg
Type of control : mechanical
Number of speed settings : 3
Maximum output air extraction : 625 m³/h
Maximum output recirculating air : 416 m³/h
Number of lights (Stck) : 2
Noise level : 70 dB(A) re 1 pW
Diameter of air outlet : 150 / 120 mm
Grease filter material : Washable aluminium
EAN code : 4242005041121
Connection rating : 256 W
Fuse protection : 10 A
Voltage : 220-240 V
Frequency : 50; 60 Hz
Plug type : GB plug
Installation type : Wall-mounted



Optional accessories

DWZ0IM0A0 : Standard odor filter (replacement)



4 242005 041121

Serie | 2, Integrated cooker hood, 60 cm, silver DEM66AC00B

Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 625 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 70 dB dB*

Features

- Push button control for extractor speeds and light
- 3 power levels
- 2 x 3W LED
- Single motor
- 2 removable metal grease filter cassettes

Design

- Integrated hood
- Installation: Between Cupboards
- Push button control
- Mechanical

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction charcoal filter (accessory) needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 188 lux
- Colour Temperature: 2700 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 68.4 kWh/year*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating (HxWxD): 402-402 x 599 x 271 mm

Optional accessories

- Recirculating kit DWZ01MOA0

* In accordance with the EU-Regulation No 65/2014

**Serie | 2, Integrated cooker hood, 60 cm,
silver
DEM66AC00B**

