

**Serie | 6, Island cooker hood, 90 cm,
clear glass
DIA098E50B**

A+



Stylish island chimney hoods perfectly complement island hob installations.

- An impressive extraction rate of 790 m³/h ensures this hood will have your kitchen odour free in no time.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.

Technical Data

Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	699-879/699-999
Height of product, without chimney (mm) :	52
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	31.508
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m ³ /h) :	430
Boost position output recirculating (m ³ /h) :	360.0
Boost position air extraction (m ³ /h) :	790
Number of lights (Stck) :	4
Noise level (dB(A) re 1 pW) :	58
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242002775937
Connection rating (W) :	172
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	60; 50
Plug type :	GB plug
Installation type :	Island

Optional accessories

- DHZ1230 : Adapter for roof inclination left/right
- DHZ1240 : Adapter for roof inclination front/back
- DHZ1245 : Chimney extension 1100 mm
- DHZ1255 : Chimney extension 1600 mm
- DHZ5326 : Standard odor filter (replacement)
- DHZ5365 : Standard recirculation kit
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6220 : CleanAir Recirculation Kit
- DZZ0XX0P0 : Long Life odor filter (replacement)



4 242002 775937

Serie | 6, Island cooker hood, 90 cm, clear glass DIA098E50B

Stylish island chimney hoods perfectly complement island hob installations.

Key Information

- Electronic control
- Electronic power level display
- Grease and charcoal filter saturation indicators

Design

- 90 cm wide
- Designed for ceiling mounted installation
- Height adjustable chimney sections
- Brushed steel glass canopy

Features

- Soft touch button control for extractor speeds and light
- 4 x LED lights
- Automatic intensive revert
- Softlight dimmer function
- Dimmer function
- 2 removable metal grease filter cassettes

Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 430 m³/h
Intensive 790 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW (44 dB (A) re 20 μ Pa sound pressure)
- Maximum extraction rate 790 m³/h (intensive)
- Extractor hose 120mm

Accessories

- Recirculating kit DHZ5365

Serie | 6, Island cooker hood, 90 cm, clear glass
DIA098E50B

