

**Serie | 8, Island cooker hood, 90 cm,
Stainless steel
DIB091U51B**

A⁺



Optional accessories

DHZ1231 : Adapter for roof inclination left/right
 DHZ1241 : Adapter for roof inclination front/back
 DHZ1246 : Chimney extension 1100 mm
 DHZ1256 : Chimney extension 1600 mm
 DHZ5346 : Standard odor filter (replacement)
 DHZ5385 : Standard recirculation kit
 DSZ5201 : CleanAir active carbon filter spare part
 DSZ6230 : CleanAir Recirculation Kit
 DZZ0XX0P0 : Long Life odor filter (replacement)

Stylish island chimney hoods perfectly complement island hob installations.

- An impressive extraction rate of 1000 m³/h ensures this hood will have your kitchen odour free in no time.
- **Especially quiet:** high performance at just 46 dB.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, G-Mark, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	698-878/698-998
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	28.317
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m ³ /h) :	620
Boost position output recirculating (m ³ /h) :	480
Maximum output recirculating air (m ³ /h) :	400
Boost position air extraction (m ³ /h) :	1000
Number of lights (Stck) :	4
Noise level (dB(A) re 1 pW) :	60
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable aluminium
EAN code :	4242002779584
Connection rating (W) :	272
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation type :	Island



Serie | 8, Island cooker hood, 90 cm, Stainless steel DIB091U51B

**Stylish island chimney hoods perfectly
complement island hob installations.**

Key Information

- Electronic control
- Electronic power level display
- Grease and charcoal filter saturation indicators
- EcoSensor

Design

- 90 cm wide
- Designed for ceiling mounted installation
- Height adjustable chimney sections

Features

- Soft touch button control for extractor speeds and light
- 3 power levels and 2 intensive settings
- Automatic intensive revert
- LED lights
- Softlight dimmer function
- Dimmer function
- Additional noise reduction insulation
- 3 removable metal grease filter cassettes

Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 620 m³/h
Intensive 1000 m³/h
- Maximum extraction rate 1000 m³/h (intensive)
- Noise level according to EN 60704-3 and EN 60704-2-13 at
maximum normal setting: extraction rate: 60 dB (A) re 1pW
(46 dB (A) re 20 μ Pa sound pressure)
- Light Intensity: 888 lux
- Colour Temperature: 3500 K
- Energy Efficiency Class: A+ (at a range of energy efficiency
classes from A+++ to D)
- Average Energy Consumption: 36.9 kWh/year*
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Noise max. Normal Level: 60 dB*

* In accordance with the EU-Regulation No 65/2014

**Serie | 8, Island cooker hood, 90 cm,
Stainless steel
DIB091U51B**

