

Island cooker hood, 90 cm, Stainless steel
DIB09E850B



Stylish island chimney hoods perfectly complement island hob installations.

- An impressive extraction rate of 820 m³/h ensures this hood will have your kitchen odour free in no time.
- **Especially quiet:** high performance at just 43 dB.
- Halogen lighting provides energy efficient and bright lighting of the hob area.
- Intensive speed setting with revert gives a quick intensive 10 min burst to clear strong odours and then reverts back to the normal setting.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	698-878/698-998
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	30.662
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	540
Boost position output recirculating (m ³ /h) :	450
Maximum output recirculating air (m ³ /h) :	370
Boost position air extraction (m ³ /h) :	820
Number of lights (Stck) :	4
Noise level (dB(A) re 1 pW) :	58
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable aluminium
EAN code :	4242002625966
Connection rating (W) :	340
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation type :	Island

Optional accessories

- DHZ1231 : Adapter for roof inclination left/right
- DHZ1241 : Adapter for roof inclination front/back
- DHZ1246 : Chimney extension 1100 mm
- DHZ1256 : Chimney extension 1600 mm
- DHZ5346 : Standard odor filter (replacement)
- DHZ5385 : Standard recirculation kit
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6230 : CleanAir Recirculation Kit



Island cooker hood, 90 cm, Stainless steel DIB09E850B

**Stylish island chimney hoods perfectly
complement island hob installations.**

Key Information

- Electronic control
- Electronic power level display

Design

- 90 cm wide
- Designed for ceiling mounted installation
- Height adjustable chimney sections
- Brushed steel canopy and chimney section

Features

- Soft touch button control for extractor speeds and light
- 3 power levels & intensive setting
- Automatic intensive revert
- 4 x 20W low energy halogen lights
- Additional noise reduction insulation
- 3 removable metal grease filter cassettes

Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 550 m³/h
Intensive 820 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13
exhaust air:
Max. normal use: 57 dB(A) re 1 pW (43 dB(A) re 20 µPa sound
pressure)
Intensive: 66 dB(A) re 1 pW (52 dB(A) re 20 µPa sound
pressure)
- Extractor hose 120mm

Optional accessories

- Recirculating kit DHZ5385

