

**Serie | 6, Island cooker hood, 90 cm,
Stainless steel
DIB98JQ50B**

A+



Stylish island chimney hoods perfectly complement island hob installations.

- **PerfectAir sensor:** automatic control of settings for maximum extractor performance with minimal noise.
- **Grease filtration level:** filters out over 85% of the grease from kitchen air
- **EcoSilence Drive:** our highly efficient motor saves on energy, not on performance.
- **DirectSelect control:** direct selection of desired settings and light.
- **Intensive speed setting:** removes strong kitchen odours quickly and effectively.

Technical Data

| | |
|---|--------------------------|
| Typology : | Chimney |
| Approval certificates : | CE, VDE |
| Length of electrical supply cord (cm) : | 130 |
| Height of the chimney (mm) : | 698-878/698-998 |
| Height of product, without chimney (mm) : | 46 |
| Minimum distance above an electric hob : | 550 |
| Minimum distance above a gas hob : | 650 |
| Net weight (kg) : | 30.677 |
| Type of control : | Electronic |
| Number of speed settings : | 3-stage + 2 intensive |
| Maximum output air extraction (m ³ /h) : | 445 |
| Boost position output recirculating (m ³ /h) : | 391.0 |
| Maximum output recirculating air (m ³ /h) : | 313 |
| Boost position air extraction (m ³ /h) : | 867 |
| Number of lights (Stck) : | 4 |
| Noise level (dB(A) re 1 pW) : | 54 |
| Diameter of air outlet (mm) : | 120 / 150 |
| Grease filter material : | Washable stainless steel |
| EAN code : | 4242005099276 |
| Connection rating (W) : | 166 |
| Current (A) : | 10 |
| Voltage (V) : | 220-240 |
| Frequency (Hz) : | 50; 60 |
| Plug type : | GB plug |
| Installation type : | Island |

Optional accessories

- DHZ1231 : Adapter for roof inclination left/right
- DHZ1241 : Adapter for roof inclination front/back
- DHZ1246 : Chimney extension 1100 mm
- DHZ1251 : Extension for mounting kit 500 mm
- DHZ1256 : Chimney extension 1600 mm
- DHZ5346 : Standard odor filter (replacement)
- DHZ5385 : Standard recirculation kit
- DIZ2CX5C6 : Clean Air Plus recirc. kit external
- DZZ0XX0P0 : Long Life odor filter (replacement)
- DZZ1XX1B6 : Clean Air Plus odor filter (replacement)



Serie | 6, Island cooker hood, 90 cm, Stainless steel DIB98JQ50B

**Stylish island chimney hoods perfectly
complement island hob installations.**

Key performance features:

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 445 m³/h
Intensive 867 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 54 dB dB*

Special features

- PerfectAir sensor
- TouchControl with lightline
- 3-stage + 2 intensive
- 4 x 1.5W LED light
- Colour Temperature: 3500 K
- Dimmer function
- 850EE
- Automatic intensive revert (6mins)
- Automatic after running (Automatic after running (10 min))
- 3 removable metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- Additional noise reduction insulation
- easy to clean yes

Design

- Island chimney hood
- Designed for ceiling mounted installation
- TouchControl
- Electronic control
- Efficient BLDC technology

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 max. 445 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 54 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 54 dB(A) re 1 pW
Intensive: 69 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 54 dB (A) re 1pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
Extraction rate in recirculation mode:
Max. normal use: 353 m³/h
Intensive: 457 m³/h
Noise level in recirculation mode:
Max. normal use: 67 dB(A) re 1 pW
Intensive: 71 dB(A) re 1 pW
- Power rating: 166 W
- Light Intensity: 423 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 898 x 600 mm
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 31.6 kWh/year*

Optional accessories

- Recirculating kit DHZ1231

* In accordance with the EU-Regulation No 65/2014

**Serie | 6, Island cooker hood, 90 cm,
Stainless steel
DIB98JQ50B**

