

**Wall-mounted cooker hood, 90 cm,
clear glass
DWA09E650B**



Optional accessories

DHZ1225 : Chimney extension 1000 mm
 DHZ1235 : Chimney extension 1500 mm
 DHZ5325 : Recirculating kit
 DHZ5326 : Active carbon filter
 DSZ5201 : CleanAir active carbon filter spare part
 DSZ6200 : CleanAir Recirculation Kit



Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 650 m³/h ensures this hood will have your kitchen odour free in no time.
- Halogen lighting provides energy efficient and bright lighting of the hob area.
- Intensive speed setting with revert gives a quick intensive 10 min burst to clear strong odours and then reverts back to the normal setting.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-902/582-1012
Height of product, without chimney (mm) :	52
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	19.620
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	420
Boost position output recirculating (m ³ /h) :	380
Maximum output recirculating air (m ³ /h) :	280
Boost position air extraction (m ³ /h) :	650
Number of lights (Stck) :	2
Noise level (dB(A) re 1 pW) :	59
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable aluminium
EAN code :	4242002660134
Connection rating (W) :	250
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation type :	Wall-mounted



4 242002 660134

Wall-mounted cooker hood, 90 cm, clear glass DWA09E650B

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Key Information

- Electronic control
- Electronic power level display

Design

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections
- Brushed steel

Features

- Soft touch button control for extractor speeds and light
- 3 power levels & intensive setting
- Automatic intensive revert
- 2 x 20W low energy halogen lights
- 1 removable metal grease filter cassette

Performance/technical information

- Easy installation system
- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 430 m³/h
Intensive 650 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13
exhaust air:
Max. normal use: 57 dB(A) re 1 pW (43 dB(A) re 20 μ Pa sound pressure)
Intensive: 67 dB(A) re 1 pW (53 dB(A) re 20 μ Pa sound pressure)
- Intensive: 67 dB (A) re 1 pW (53 dB (A) re 20 μ Pa sound pressure)
- Extractor hose 120mm
- Dimensions recirculating with CleanAir module (HxWxD):
654 x 900 x 540 mm - mounting with outer chimney
774-1104 x 900 x 540 mm - mounting with telescopic chimney

