

**Wall-mounted cooker hood, 90 cm,
clear glass
DWA09W450B**



E

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 430 m³/h ensures this hood will have your kitchen odour free in no time.
- Halogen lighting provides energy efficient and bright lighting of the hob area.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-902/582-1012
Height of product, without chimney (mm) :	52
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	19.320
Type of control :	mechanical
Number of speed settings :	3
Maximum output air extraction (m ³ /h) :	420
Maximum output recirculating air (m ³ /h) :	260
Number of lights (Stck) :	2
Noise level (dB(A) re 1 pW) :	64
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242002624990
Connection rating (W) :	226
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation type :	Wall-mounted

Optional accessories

- DHZ1225 : Chimney extension 1000 mm
- DHZ1235 : Chimney extension 1500 mm
- DHZ5325 : Standard recirculation kit
- DHZ5326 : Standard odor filter (replacement)
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6200 : CleanAir Recirculation Kit



4 242002 624990

**Wall-mounted cooker hood, 90 cm, clear
glass
DWA09W450B**

**Wall mounted chimney hoods add style and
sophistication to the kitchen and give you
complete freedom in your kitchen planning.**

Design

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections
- Brushed steel

Features

- Rocker switch control for extractor speeds and light
- 3 power levels
- 2 x halogen lights
- 1 removable metal grease filter cassette

Performance/technical information

- Easy installation system
- Suitable for ducted or recirculating operation
- Maximum extraction rate exhaust air 430 m³/h according to EN 61591
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 62 dB(A) re 1 pW (48 dB(A) re 20 µPa sound pressure)
- Intensive: NO_FEATURE dB (A) re 1 pW (NO_FEATURE dB (A) re 20 µPa sound pressure)
- Extractor hose 120mm

