

Serie | 8, Wall-mounted cooker hood,
60 cm
DWB068J50B



Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 760 m3/h ensures this hood will have your kitchen odour free in no time.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.
- **Especially quiet:** high performance at just 46 dB.

Technical Data

| | |
|--|--------------------------|
| Typology : | Chimney |
| Approval certificates : | CE, VDE |
| Length of electrical supply cord (cm) : | 130 |
| Height of the chimney (mm) : | 582-908/582-1018 |
| Height of product, without chimney (mm) : | 46 |
| Minimum distance above an electric hob : | 550 |
| Minimum distance above a gas hob : | 650 |
| Net weight (kg) : | 15.429 |
| Type of control : | Electronic |
| Number of speed settings : | 3-stage + 2 intensive |
| Maximum output air extraction (m3/h) : | 430 |
| Boost position output recirculating (m3/h) : | 380.0 |
| Boost position air extraction (m³/h) : | 760 |
| Number of lights (Stck) : | 2 |
| Noise level (dB(A) re 1 pW) : | 60 |
| Diameter of air outlet (mm) : | 150 / 120 |
| Grease filter material : | Washable stainless steel |
| EAN code : | 4242002811925 |
| Connection rating (W) : | 166 |
| Current (A) : | 10 |
| Voltage (V) : | 220-240 |
| Frequency (Hz) : | 50; 60 |
| Plug type : | GB plug |
| Installation type : | Wall-mounted |

Optional accessories

- DHZ1225 : Chimney extension 1000 mm
- DHZ1235 : Chimney extension 1500 mm
- DHZ5325 : Standard recirculation kit
- DHZ5326 : Standard odor filter (replacement)
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6200 : CleanAir Recirculation Kit
- DZZ0XX0P0 : Long Life odor filter (replacement)



Serie | 8, Wall-mounted cooker hood, 60 cm DWB068J50B

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Key Information

- Electronic control via TouchControl

Design

- Designed for wall mounted installation
- 60 cm wide
- Brushed steel
- Inner frame

Features

- TouchControl with lightline
- 3 power levels and 2 intensive settings
- Automatic intensive revert (6mins)
- Automatic after running (10 min)
- 2 x LED lights
- Softlight dimmer function
- Dimmer function
- 2 removable metal grease filter cassettes
- Removable metal grease filters

Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 Ø 15 cm:
max. Normal use 430 m³/h
Intensive 760 m³/h
- Extraction rate exhaust air according to EN 61591:
max. normal use 430 m³/h, intensive 760 m³/h
- Power rating: 166 W
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 60 dB(A) re 1 pW (46 dB(A) re 20 µPa sound pressure)
Intensive: 72 dB(A) re 1 pW (58 dB(A) re 20 µPa sound pressure)
- Noise max. Normal Level: 60 dB*
- Average Energy Consumption: 29.3 kWh/year*
- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Dimensions exhaust air (HxWxD): 628-954 x 600 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 600 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD): 809-1139 x 600 x 500 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Light Intensity: 745 lux
- Colour Temperature: 3500 K
- Efficient BLDC-technology

Accessories

- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed

** In accordance with the EU-Regulation No 65/2014*