

Serie | 2
**Classixx
Box style hood
DWB094W50B Brushed steel**

Optional accessories

DHZ1223 : Chimney extension 1000 mm
 DHZ1233 : Chimney extension 1500 mm
 DHZ5345 : Recirculating kit
 DHZ5346 : Active carbon filter
 DSZ5201 : CleanAir active carbon filter spare part
 DSZ6240 : CleanAir Recirculation Kit
 DZZ0XX0P0 : CleanAir act.carbon filter regenerative


Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 470 m³/h ensures this hood will have your kitchen odour free in no time.
- **Especially quiet:** high performance at just 44 dB.
- Halogen lighting provides energy efficient and bright lighting of the hob area.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-894/582-1004
Height of product, without chimney (mm) :	60
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	18.868
Type of control :	mechanical
Number of speed settings :	3
Maximum output air extraction (m ³ /h) :	470
Maximum output recirculating air (m ³ /h) :	330
Number of lights (Stck) :	2
Noise level (dB(A) re 1 pW) :	58
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242002779553
Connection rating (W) :	170
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	60; 50
Plug type :	GB plug
Installation type :	Wall-mounted



4 242002 779553

Serie | 2 Hoods

Classixx

Box style hood

DWB094W50B Brushed steel

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Design

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections

Features

- Rocker switch control for extractor speeds and light
- 3 power levels
- 2 x halogen lights
- Additional noise reduction insulation
- 3 removable metal grease filter cassettes

Performance/technical information

- Suitable for ducted or recirculating operation
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW (44 dB (A) re 20 µPa sound pressure)

Serie | 2 Hoods

Classixx

Box style hood

DWB094W50B Brushed steel

