

**Serie | 6, Wall-mounted cooker hood,  
90 cm, Stainless steel  
DWB098E51B**

**A**



**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

- An impressive extraction rate of 860 m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- **Especially quiet:** high performance at just 41 dB.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.

**Technical Data**

Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-908/582-1018
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	18.763
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m <sup>3</sup> /h) :	460
Boost position output recirculating (m <sup>3</sup> /h) :	460.0
Boost position air extraction (m <sup>3</sup> /h) :	860
Number of lights (Stck) :	3
Noise level (dB(A) re 1 pW) :	55
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
EAN code :	4242002778334
Connection rating (W) :	169
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	60; 50
Plug type :	GB plug
Installation type :	Wall-mounted

**Optional accessories**

- DHZ1223 : Chimney extension 1000 mm
- DHZ1233 : Chimney extension 1500 mm
- DHZ5345 : Standard recirculation kit
- DHZ5346 : Standard odor filter (replacement)
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6240 : CleanAir Recirculation Kit
- DZZ0XX0P0 : Long Life odor filter (replacement)



## **Serie | 6, Wall-mounted cooker hood, 90 cm, Stainless steel DWB098E51B**

**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

---

### **Key Information**

- Electronic control
- Electronic power level display
- Grease and charcoal filter saturation indicators

### **Design**

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections

### **Features**

- Soft touch button control for extractor speeds and light
- 3 power levels and 2 intensive settings
- Automatic intensive revert
- LED lights
- Softlight dimmer function
- Dimmer function
- Additional noise reduction insulation
- 3 removable metal grease filter cassettes

### **Performance/technical information**

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591  $\varnothing$  15 cm:  
max. Normal use 460 m<sup>3</sup>/h  
Intensive 860 m<sup>3</sup>/h
- Maximum extraction rate 860 m<sup>3</sup>/h (intensive)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 55 dB (A) re 1pW (41 dB (A) re 20  $\mu$ Pa sound pressure)

**Serie | 6, Wall-mounted cooker hood, 90 cm,  
Stainless steel  
DWB098E51B**

