

**Serie | 8, Wall-mounted cooker hood,
90 cm, Stainless steel
DWB098J50B**

A



Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 860 m³/h ensures this hood will have your kitchen odour free in no time.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.
- **Especially quiet:** high performance at just 41 dB.

Technical Data

Typology :	Chimney
Approval certificates :	CE, G-Mark, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-908/582-1018
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	19.513
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m ³ /h) :	460
Boost position output recirculating (m ³ /h) :	440.0
Boost position air extraction (m ³ /h) :	860
Number of lights (Stck) :	3
Noise level (dB(A) re 1 pW) :	55
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
EAN code :	4242002811932
Connection rating (W) :	169
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation type :	Wall-mounted

Optional accessories

- DHZ1223 : Chimney extension 1000 mm
- DHZ1233 : Chimney extension 1500 mm
- DHZ5345 : Standard recirculation kit
- DHZ5346 : Standard odor filter (replacement)
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6240 : CleanAir Recirculation Kit
- DZZ0XX0P0 : Long Life odor filter (replacement)



Serie | 8, Wall-mounted cooker hood, 90 cm, Stainless steel DWB098J50B

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Key Information

- Electronic control via TouchControl

Design

- Designed for wall mounted installation
- 90 cm wide
- Brushed steel
- Inner frame

Features

- TouchControl with lightline
- 3 power levels and 2 intensive settings
- Automatic intensive revert (6mins)
- Automatic after running (10 min)
- Additional noise reduction insulation
- 3 x LED lights
- Softlight dimmer function
- Dimmer function
- 3 removable metal grease filter cassettes
- Removable metal grease filters

Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 460 m³/h
Intensive 860 m³/h
- Extraction rate exhaust air according to EN 61591:
max. normal use 460 m³/h, intensive 860 m³/h
- Power rating: 169 W
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 55 dB(A) re 1 pW (41 dB(A) re 20 μ Pa sound pressure)
Intensive: 68 dB(A) re 1 pW (54 dB(A) re 20 μ Pa sound pressure)
- Noise max. Normal Level: 55 dB*
- Average Energy Consumption: 37.2 kWh/year*
- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Dimensions exhaust air (HxWxD): 628-954 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
809-1139 x 900 x 500 mm
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- Light Intensity: 897 lux
- Colour Temperature: 3500 K
- Efficient BLDC-technology

Accessories

- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed

* In accordance with the EU-Regulation No 65/2014