

**Wall-mounted cooker hood, 90 cm,  
Stainless steel  
DWB09T855B**



**Optional accessories**

DHZ1223 : Chimney extension 1000 mm  
 DHZ1233 : Chimney extension 1500 mm  
 DHZ5345 : Recirculating kit  
 DHZ5346 : Active carbon filter  
 DSZ5201 : CleanAir active carbon filter spare part  
 DSZ6240 : CleanAir Recirculation Kit

**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

- An impressive extraction rate of 820 m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- **Especially quiet:** high performance at just 42 dB.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 10 min burst to clear strong odours and then reverts back to the normal setting.

**Technical Data**

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-908/582-1018
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	19.858
Type of control :	Electronic
Boost position output recirculating (m <sup>3</sup> /h) :	480
Maximum output recirculating air (m <sup>3</sup> /h) :	370
Boost position air extraction (m <sup>3</sup> /h) :	820
Number of lights (Stck) :	3
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable stainless steel
EAN code :	4242002687896
Connection rating (W) :	175
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation type :	Wall-mounted



4 242002 687896

## Wall-mounted cooker hood, 90 cm, Stainless steel DWB09T855B

**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

---

### Key Information

- Electronic control
- Electronic power level display
- Charcoal filter saturation indicator
- Grease and charcoal filter saturation indicators

### Design

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections
- Brushed steel canopy and chimney section

### Features

- Soft touch button control for extractor speeds and light
- 3 power levels & intensive setting
- Automatic intensive revert
- LED lights
- 3 x 5 Watt LED light strips
- Softlight dimmer function
- Dimmer function
- Additional noise reduction insulation
- 
- 3 removable metal grease filter cassettes

### Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 520 m<sup>3</sup>/h  
Intensive 820 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at  
maximum normal setting: extraction rate: 56 dB (A) re 1pW  
(42 dB (A) re 20 µPa sound pressure)
- Extractor hose 120mm

### Accessories

- Recirculating kit DHZ5345
- Dimensions recirculating with CleanAir module (HxWxD):  
654 x 900 x 500 mm - mounting with outer chimney  
774-1104 x 900 x 500 mm - mounting with telescopic chimney

