

**Wall-mounted cooker hood, 90 cm,  
Stainless steel  
DWB09W450B**

**E**



**Technical Data**

|   |                    |
|---|--------------------|
| Color chimney :                           | Stainless steel    |
| Typology :                                | Chimney            |
| Approval certificates :                   | CE, VDE            |
| Length of electrical supply cord (cm) :   | 130                |
| Height of the chimney (mm) :              | 582-894/582-1004   |
| Height of product, without chimney (mm) : | 60                 |
| Minimum distance above an electric hob :  | 550                |
| Minimum distance above a gas hob :        | 650                |
| Net weight (kg) :                         | 18.808             |
| Type of control :                         | mechanical         |
| Number of speed settings :                | 3                  |
| Maximum output air extraction (m3/h) :    | 430                |
| Maximum output recirculating air (m3/h) : | 310                |
| Number of lights (Stck) :                 | 2                  |
| Noise level (dB(A) re 1 pW) :             | 60                 |
| Diameter of air outlet (mm) :             | 150 / 120          |
| Grease filter material :                  | Washable aluminium |
| EAN code :                                | 4242002624860      |
| Connection rating (W) :                   | 226                |
| Voltage (V) :                             | 220-240            |
| Frequency (Hz) :                          | 50                 |
| Plug type :                               | GB plug            |
| Installation type :                       | Wall-mounted       |



**Optional accessories**

- DHZ1223 : Chimney extension 1000 mm
- DHZ1233 : Chimney extension 1500 mm
- DHZ5345 : Standard recirculation kit
- DHZ5346 : Standard odor filter (replacement)
- DHZ9550 : Brushed steel back panel
- DHZ9551 : Brushed steel back panel
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6240 : CleanAir Recirculation Kit

## Wall-mounted cooker hood, 90 cm, Stainless steel DWB09W450B

---

### Design

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections

### Features

- Rocker switch control for extractor speeds and light
- 3 power levels
- 2 x halogen lights
- 3 removable metal grease filter cassettes

### Performance/technical information

- Easy installation system
- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591  $\varnothing$  15 cm:
  - max. Normal use 440 m<sup>3</sup>/h
  - Intensive NO\_FEATURE m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
  - Max. normal use: 60 dB(A) re 1 pW (46 dB(A) re 20  $\mu$ Pa sound pressure)
  - Intensive: NO\_FEATURE dB(A) re 1 pW (NO\_FEATURE dB(A) re 20  $\mu$ Pa sound pressure)
- Extractor hose 120mm
- Additional noise reduction insulation
- Recirculating kit DHZ5345
- Dimensions recirculating with CleanAir module (HxWxD):
  - 654 x 900 x 500 mm - mounting with outer chimney
  - 774-1104 x 900 x 500 mm - mounting with telescopic chimney

## Wall-mounted cooker hood, 90 cm, Stainless steel DWB09W450B

