

**Serie | 8, Wall-mounted cooker hood,  
90 cm, Grey  
DWF97MS70B**



**B**

**Flat design hood: always keep an eye on your pots and pans with this design highlight.**

- **DirectSelect control:** direct selection of desired settings and light.
- An impressive extraction rate of 730 m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- **Home Connect:** Connected home appliances for an easier everyday life (only in countries where Home Connect service is available).
- **PerfectAir sensor:** automatic control of settings for maximum extractor performance with minimal noise.
- **Especially silent:** maximum extractor performance with minimal noise



**Technical Data**

Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of product, without chimney (mm) :	430
Minimum distance above an electric hob :	450
Minimum distance above a gas hob :	600
Net weight (kg) :	22.919
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m <sup>3</sup> /h) :	394
Boost position output recirculating (m <sup>3</sup> /h) :	530.0
Boost position air extraction (m <sup>3</sup> /h) :	730
Number of lights (Stck) :	2
Noise level (dB(A) re 1 pW) :	57
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242005035113
Connection rating (W) :	150
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation type :	Wall-mounted

**Optional accessories**

- DSZ5201 : CleanAir active carbon filter spare part
- DWZ0AF0A0 : Standard odor filter (replacement)
- DWZ0AF0R0 : Long Life recirculation kit (chimless)
- DWZ0AF0S0 : Long Life recirculation kit
- DWZ0AF0T0 : Standard recirculation kit (chimless)
- DWZ0AF0U0 : Standard recirculation kit
- DWZ0AX5K0 : Chimney extension 1000 mm
- DWZ0AX5L0 : Chimney extension 1500 mm
- DZZ0XX0P0 : Long Life odor filter (replacement)



## Serie | 8, Wall-mounted cooker hood, 90 cm, Grey DWF97MS70B

**Flat design hood: always keep an eye on your pots and pans with this design highlight.**

### Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 420 m<sup>3</sup>/h  
Intensive 730 m<sup>3</sup>/h
- Noise max. Normal Level: 57 dB\*

### Features

#### Home Connect: Remote Monitoring and Control (only in countries where Home Connect service is available)

- PerfectAir sensor
- AmbientLight
- Hob based hood control
- TouchControl with lightline
- 3 power levels and 2 intensive settings
- 2 x 3W LED light
- Colour Temperature: 3500 K
- Dimmer function
- Efficient BLDC technology
- Automatic after running (10 min)
- Automatic intensive revert (6mins)
- 2 removable metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- easy to clean Inner frame
- Designed for wall mounted installation
- Rim ventilation

### Design

- Grey glass canopy
- Flat glass design
- Chimney extractor hood
- TouchControl
- Electronic control

### Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Easy installation system
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 420 m<sup>3</sup>/h  
Intensive 730 m<sup>3</sup>/h
- Extraction rate according to EN 61591 max. 420 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 56 dB(A) re 1 pW (43 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:  
Max. normal use: 56 dB(A) re 1 pW (43 dB(A) re 20 µPa sound pressure)  
Intensive: 70 dB(A) re 1 pW (56 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 57 dB (A) re 1pW
- Noise max. Normal Level: 57 dB\*
- Power rating: 150 W
- Light Intensity: 460 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 969-1239 x 890 x 263 mm
- Dimensions recirculating (HxWxD): 1029-1299 x 890 x 263 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
1159 x 890 x 263 mm - mounting with outer chimney  
1229-1499 x 890 x 263 mm - mounting with telescopic chimney
- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Average Energy Consumption: 40 kWh/year\*

### Optional accessories

- Recirculating kit

\* In accordance with the EU-Regulation No 65/2014