

**Serie | 8, Wall-mounted cooker hood,
33 cm, Black
DWI37RU60B**



Cube design hood: this hood is a perfect design highlight for any kitchen.

- **7-segment display with control wheel:** settings and light can be selected conveniently by turning the control wheel.
- **Extraction rate in recirculation:** at 400 m³/h, it quickly ensures optimal kitchen air quality.
- **Silent:** maximum extractor performance with little noise
- **Easy-to-clean interior:** hidden cables along with rounded edges make cleaning easy.
- **Integrated CleanAir module:** reduces cooking odours by approx. 95%.

Technical Data

Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of product, without chimney (mm) :	501
Minimum distance above an electric hob :	550
Net weight (kg) :	14.152
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Boost position output recirculating (m ³ /h) :	400.0
Number of lights (Stck) :	2
Grease filter material :	Washable aluminium
EAN code :	4242002946641
Connection rating (W) :	146
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation type :	Wall-mounted

Optional accessories

DSZ5201 : CleanAir active carbon filter spare part
DZZ0XX0P0 : Long Life odor filter (replacement)



Serie | 8, Wall-mounted cooker hood, 33 cm, Black DWI37RU60B

Cube design hood: this hood is a perfect design highlight for any kitchen.

Key performance features:

- Extraction rate in recirculation mode:
Max. normal use: 329 m³/h
Intensive: 400 m³/h
- Noise max. Normal Level: NO_FEATURE dB*

Features

- TouchControl with Electronic display
- Electronic display
- 3 power levels and 2 intensive settings
- 2 x 3W LED light
- Colour Temperature: 3500 K
- Dimmer function
- Efficient BLDC technology
- Automatic run on duration 1-9 min
- Automatic intensive revert (6mins)
- 1 removable metal grease filter cassette
- Saturation indicator for metal and charcoal filter
- Designed for wall mounted installation
- Clean Air charcoal filter included

Design

- Black glass canopy
- Cube design
- Chimney extractor hood
- TouchControl, Control wheel
- Electronic control
- Installation with gas hob not recommended

Performance/technical information

- Suitable for recirculated operation
- Easy installation system
- Extraction rate in recirculation mode:
Max. normal use: 329 m³/h
Intensive: 400 m³/h
- Noise levels in recirculation mode:
Max. normal use: 67 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
Intensive: 72 dB(A) re 1 pW (59 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: NO_FEATURE dB (A) re 1pW
- Noise max. Normal Level: NO_FEATURE dB*
- Power rating: 146 W
- Light Intensity: 680 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Dimensions recirculating (HxWxD): 501-501 x 330 x 291 mm

Optional accessories

- Recirculating kit

** In accordance with the EU-Regulation No 65/2014*