

**Wall-mounted cooker hood, 90 cm,
clear glass black printed
DWK09M760B**



Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 700 m³/h ensures this hood will have your kitchen odour free in no time.
- Halogen lighting provides energy efficient and bright lighting of the hob area.
- Intensive speed setting with revert gives a quick intensive 5 min. burst to clear strong odours and then reverts back to the normal setting.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	553-981/553-981
Height of product, without chimney (mm) :	506
Minimum distance above an electric hob :	450
Minimum distance above a gas hob :	550
Net weight (kg) :	27.362
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	610
Boost position output recirculating (m ³ /h) :	380
Maximum output recirculating air (m ³ /h) :	360
Boost position air extraction (m ³ /h) :	700
Number of lights (Stck) :	2
Noise level (dB(A) re 1 pW) :	64
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable aluminium
EAN code :	4242002702360
Connection rating (W) :	315
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation type :	Wall-mounted



Optional accessories

DHZ5595 : Recirculating kit



4 242002 702360

Wall-mounted cooker hood, 90 cm, clear glass black printed DWK09M760B

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Key Information

- Electronic control
- Electronic power level display
- Rim ventilation
- Grease and charcoal filter saturation indicators

Design

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections
- Black

Features

- TouchControl for extractor speeds and light
- 3 power levels & intensive setting
- Automatic intensive revert
- LED lights
- 2 x 20W low energy halogen lights
- Automatic 20 minutes after running
- 2 removable metal grease filter cassettes

Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 610 m³/h
Intensive 700 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at
maximum normal setting: extraction rate: 64 dB (A) re 1pW
(50 dB (A) re 20 μ Pa sound pressure)
- Extractor hose 120mm

Optional accessories

- Recirculating kit

**Wall-mounted cooker hood, 90 cm, clear glass black printed
DWK09M760B**

