

**Serie | 4, Wall-mounted cooker hood,  
90 cm, clear glass white printed  
DWK97HM20B**

**B**



**Angled hood: perfect for keeping an eye on your pots and pans.**

- **TouchSelect control:** quick touch-control selection of desired settings and light.
- An impressive extraction rate of 700 m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- **Especially silent:** maximum extractor performance with minimal noise
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **Energy efficiency A:** maximum extractor performance with minimal energy consumption

**Technical Data**

Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of product, without chimney (mm) :	323
Minimum distance above an electric hob :	450
Minimum distance above a gas hob :	600
Net weight (kg) :	23.912
Type of control :	Electronic
Maximum output air extraction (m <sup>3</sup> /h) :	416
Boost position output recirculating (m <sup>3</sup> /h) :	557.0
Boost position air extraction (m <sup>3</sup> /h) :	700
Number of lights (Stck) :	2
Noise level (dB(A) re 1 pW) :	58
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242005035090
Connection rating (W) :	263
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50-60
Plug type :	GB plug
Installation type :	Wall-mounted

**Optional accessories**

- DSZ5201 : CleanAir active carbon filter spare part
- DWZ0AK0A0 : Standard odor filter (replacement)
- DWZ0AK0R0 : Long Life recirculation kit (chimless)
- DWZ0AK0S0 : Long Life recirculation kit
- DWZ0AK0T0 : Standard recirculation kit (chimless)
- DWZ0AK0U0 : Standard recirculation kit
- DWZ0AX5K0 : Chimney extension 1000 mm
- DWZ0AX5L0 : Chimney extension 1500 mm
- DZZ0XX0P0 : Long Life odor filter (replacement)



4 242005 035090

## Serie | 4, Wall-mounted cooker hood, 90 cm, clear glass white printed DWK97HM20B

### Angled hood: perfect for keeping an eye on your pots and pans.

#### Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 416 m<sup>3</sup>/h  
Intensive 700 m<sup>3</sup>/h
- Noise max. Normal Level: 58 dB\*

#### Features

- TouchControl with Electronic display
- Electronic display
- 3 power levels & intensive setting
- 2 x 1.5W LED light
- Colour Temperature: 3500 K
- Twin channel high performance fan motor
- Automatic intensive revert (6mins)
- 2 removable metal grease filter cassettes
- easy to clean Inner frame
- Designed for wall mounted installation
- Rim ventilation

#### Design

- White glass canopy
- angled glass design
- Chimney extractor hood
- TouchControl
- Electronic control

#### Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Easy installation system
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 416 m<sup>3</sup>/h  
Intensive 700 m<sup>3</sup>/h
- Extraction rate according to EN 61591 max. 416 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 58 dB(A) re 1 pW (45 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:  
Max. normal use: 58 dB(A) re 1 pW (45 dB(A) re 20 µPa sound pressure)  
Intensive: 67 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW
- Noise max. Normal Level: 58 dB\*
- Power rating: 263 W
- Light Intensity: 90 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 929-1199 x 890 x 499 mm
- Dimensions recirculating (HxWxD): 989-1259 x 890 x 499 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
1119 x 890 x 499 mm - mounting with outer chimney  
1189-1459 x 890 x 499 mm - mounting with telescopic chimney
- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: B\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 56.6 kWh/year\*

#### Optional accessories

- Recirculating kit

\* In accordance with the EU-Regulation No 65/2014