

## Serie | 6, Free-standing fridge-freezer with freezer at bottom KGE49AW30G


**A++**


### Included accessories

- 2 x cold accumulator
- 1 x egg tray
- 1 x ice cube tray

### Technical Data

Construction type :	Free-standing
Door panel options :	Not possible
Height (mm) :	2010
Width of the product (mm) :	700
Depth of the product :	650
Net weight (kg) :	97.000
Connection rating (W) :	90
Current (A) :	10
Door hinge :	Right reversible
Voltage (V) :	220-240
Frequency (Hz) :	50
Approval certificates :	VDE
Length of electrical supply cord (cm) :	240
Storage Period in Event of Power Failure (h) :	44
Number of compressors :	1
Number of independent cooling systems :	2
Interior ventilator :	Yes
Reversible Door Hinge :	Yes
Number of Adjustable Shelves in fridge compartment (Stck) :	2
Shelves for Bottles :	Yes
EAN code :	4242002710174
Brand :	Bosch
Product name / Commercial code :	KGE49AW30G
Energy efficiency class (2010/30/EC) :	A++
Energy consumption annual (kWh/annum) - NEW (2010/30/EC) :	255.00
Refrigerator Net capacity (l) - NEW (2010/30/EC) :	301
Freezer Net capacity (l) - NEW (2010/30/EC) :	112
Frost free system :	No
Temperature rise time (h) :	44
Freezing capacity (kg/24h) - NEW (2010/30/EC) :	15
Climate class :	SN-T
Noise level (dB(A) re 1 pW) :	39
Installation type :	N/A



4 242002 710174

## Serie | 6, Free-standing fridge-freezer with freezer at bottom KGE49AW30G

### Performance and Consumption

- Energy Efficiency Class: A++ at a range of energy efficiency classes from A+++ to D
- Energy Efficiency Class: A++ kWh/yr: 0.698 kwh
- Total net capacity: 413 litres
- Net fridge capacity: 301 litres
- Net freezer capacity: 112 litres
- Noise level dB(A) re 1 pW: 39

### Design features

- White doors and white side panels
- High-door design, Cambered door design
- Vertical door handle
- Right hinged door, door reversible
- Bright interior LED fridge light
- Electronic control for fridge and freezer with LED display
- Removable magnetic door seals - easy to clean

### Food freshness system

- 1 VitaFresh ◀0°C▶ drawer - Fish and meat stay fresh for longer
- 1 VitaFresh ◀0°C▶ drawer - Fish and meat stay fresh for longer
- 1 crisper box with divider and humidity control on rails
- Two separate cooling circuits allow independent temperature control and prevents the transference of humidity between the fridge and freezer cavity

### Key features - Fridge section

- 5 removable safety glass shelves of which 2 are easy pull out
- Door shelves in fridge door: 1 large and 2 small.
- Pull-out Deli Box under shelf
- Door trays in fridge door: 1 large and 2 small
- flexShelf - easy to pull out if required, space saving if not in use
- 5 safety glass shelves in fridge compartment of which 2 are height adjustable

### Key features - Freezer section

- 3 transparent freezer drawers, including 1 BigBox
- 4 star freezer rating
- Manual defrost freezer
- Defrost water outlet - for easy and convenient defrosting
- SuperFreezing function with automatic deactivation
- Freezing capacity in 24 hours: 15 kg
- Maximum freezer storage time in power failure: 44 hours

### Functions


- Optical and acoustical
- Freezer malfunction warning signal: optical and acoustical warning system

### Dimension and installation

- Height adjustable front feet
- Climate class SN-T (suitable for ambient temperatures between 10 to 43°C)
- Dimensions: 201 cm H x 70 cm W x 65 cm D

## Serie | 6, Free-standing fridge-freezer with freezer at bottom

### KGE49AW30G



Device name	a	b	c	d	e	f	g	h
KGV39N30GE39 (inner handle)	2010	600	650	580	600	1200	650	690
KGV39N30GE39 (outer handle)	2010	600	650	580	640	1200	690	690
KGE49 (inner handle)	2010	700	650	580	700	1300	690	690
KGE49 (outer handle)	2010	700	650	580	740	1300	690	690

**Specification**

a Height  
b Width  
c Depth with door closed, without handles and without flexible spacing piece  
d Cabinet depth without flexible spacing piece  
e Width with door opened to 90°  
f Depth with door opened, without handle and without flexible spacing piece  
g Depth with door closed, with handles and without flexible spacing piece  
h Depth with door closed, without handles and with flexible spacing piece

measurements in mm