

# Series 4, Free-standing fridge-freezer with freezer at bottom, 186 x 60 cm, White KGN36VWEAG





#### Included accessories 3 x egg tray 1 x ice cube tray

NoFrost bottomfreezer : no need to defrost your freezer

- VitaFresh: keeps food fresh for longer in climate controlled drawers at near 0°C.
- **Perfect Fit:** place your fridge right next to walls and other appliances to save space.
- LED lights bring a completely new lighting concept to fridges
- Automatic Super Freezing function: optimal for freezing smaller food load faster whilst protecting your frozen items from defrosting, thanks to the detection of temperature increase and the automatic decrease of temperature
- **EasyAccess Shelf:** pull-out glass shelf gives you better access to the contents of your fridge.

## **Technical Data**

A G E

> Energy Efficiency Class: E Average annual energy consumption in kilowatt hour per year (kWh/a): 238 kWh/annum Sum of volume of frozen compartments: 89 l Sum of volume of chill compartments: 237 l Airborne acoustical noise emissions : 39 dB(A) re 1 pW Airborne acoustical noise emission class: C Construction type: Free-standing Door panel options: Not possible Height: 1860 mm Width of the appliance: 600 mm Depth of the product: 660 mm Net weight: 74.5 kg Connection rating: 100 W Fuse protection: 10 A Door hinge: Right reversible Frequency: 50-60 Hz Length of electrical supply cord: 240 cm Number of compressors: 1 Number of independent cooling systems: 2 Interior ventilator: No Reversible Door Hinge: Yes Number of Adjustable Shelves in fridge compartment (Stck): 2 Shelves for Bottles: Yes Installation type: N/A





# Series 4, Free-standing fridge-freezer with freezer at bottom, 186 x 60 cm, White KGN36VWEAG

# NoFrost bottomfreezer : no need to defrost your freezer

- KGN36VWEAG
- No Frost, Fridge freezer
- Cambered door, High-door design White

#### **Design features**

- White doors and white side panels
- Integrated vertical handle
- Right hinged door, door reversible
- Separate, electronic temperature control with LED display

#### Food freshness system

- Two separate cooling circuits allow independent temperature control and prevents the transference of humidity between the fridge and freezer cavity

#### **Key features - Fridge section**

- 1 VitaFresh drawer Fish and meat stay fresh for longer 1 VitaFresh drawer with humidity control - Fruits and vegetables retain vitamins and stay fresh for longer
- MultiAirflow system improves circulation of air around the fridge
- Bright interior LED fridge light
- 4 safety glass shelves (2 height adjustable)
- Door shelves in fridge door: 1 large and 2 small.
- Super Cooling: automatic deactivation
- Metal bottle rack

#### **Key features - Freezer section**

- No Frost, never have to defrost ever again
- 3 freezer drawers
- SuperFreeze function with automatic deactiviation
- Calendar frozen food
- Freezer malfunction warning signal: optical and acoustical warning system

#### Additional features

- Optical and accoustical
- 3 x egg tray, 1 x ice cube tray

### Dimension and installation

- Connection value 100 W
- 220 240 V
- Height adjustable front feet
- Dimensions: 186 cm H x 60 cm W x 66 cm D
- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.
- To achieve the declared energy consumption, the distanceholders have to be used. As a result, the appliance depth increases by about 3.5 cm. The appliance used without the distance holder is fully functional, but has a slightly higher energy consumption.


### Functions


#### **Performance and Consumption**

- EU19\_EEK\_D: E
- Total Volume : 326 l
- Net Fridge Volume : 237 l
- Net Freezer Volume : 89 l
- Freezing capacity 24h : 10 kg
- Annual Energy Consumption: 238 kWh/a
- Climate Class: SN-T
- EU19\_Fast freezer facility\_D
- Noise Level : 39 dB , EU19\_Noise emission class\_D: C
- Temperature rise time : EU19\_Temperature rise time\_D: 13 H



# Series 4, Free-standing fridge-freezer with freezer at bottom, 186 x 60 cm, White KGN36VWEAG





Dimension A: In models with vertical integrated handles, in order to open easily, a minimum distance of 65 mm is needed.

measurements in mm