


## Series 8, Built-in fridge, 177.2 x 55.8 cm, flat hinge KIF81PFE0















#### Included accessories

1 x bottle holder in door tray

#### **Optional accessories**

KSZB0S00 Heavy-duty hinge support

KSZGGM00 Butter box

# The Built-in refrigerator with VitaFresh pro: thanks to 0°C technology and optimal humidity levels, your food stays vitamin-rich and fresher for longer

- VitaFresh pro: keeps food fresh for longer thanks to optimal climate control and +0°C technology.
- Easy Access Shelf: a pull-out glass shelf for easier access to everything inside your fridge.
- Vario Shelf: easily store large items with this split, sliding shelf.
- LED lighting: all your items in perfect view.

A T G

• Super Cool function: cools new food faster, to protect what is already inside.

#### **Technical Data** Energy Efficiency Class<sup>1</sup>: ..... E Average annual energy consumption in kilowatt hour per year (kWh/a): ...... 150 kWh/annum Sum of volume of frozen compartments: ...... 0 l Airborne acoustical noise emission class: ......C Width of the appliance: ......558 mm Required niche size for installation (HxWxD): ...... 1775x560x550 mm Net weight: ......70.3 kg Connection rating: ...... 90 W Fuse protection: ......10 A Door hinge: ...... Right reversible Length electrical supply cord: ......230.0 cm Number of compressors: ......1 Number of independent cooling systems: ......1 Interior ventilator: ...... No Number of Adjustable Shelves in fridge compartment: ...... 6 Brand: ...... Bosch Product name / Commercial code: ......KIF81PFE0 Product category: ......Refrigerator Installation typology: ...... Integrated Included accessories: ...... 1 x bottle holder in door tray



<sup>&</sup>lt;sup>1</sup> Scale of Energy Efficiency Classes from A to G



## Series 8, Built-in fridge, 177.2 x 55.8 cm, flat hinge KIF81PFE0

# The Built-in refrigerator with VitaFresh pro: thanks to 0°C technology and optimal humidity levels, your food stays vitamin-rich and fresher for longer

#### **Functions**

- Bright interior LED fridge light in fridge section

#### **Design features**

- Electronic LED display
- FreshSense Constant temperature control by intelligent sensor technology
- Super Cooling: automatic deactivation
- Optical and acoustical door open warning

#### **Dimension and installation**

- Right hinged door, door reversible
- Connection value 90 W
- 220 240 V
- Dimensions: 177.2 cm H x 55.8 cm W x 54.5 cm D
- Niche Dimensions: 177.5 cm H x 56 cm W x 55 cm D

#### Key features - Fridge section

#### Freshness System

- 1 VitaFresh pro 0°C drawer with humidity control fruits and vegetables stay vitamin-rich and fresher for longer.
- 2 VitaFresh pro 0°C drawers -Fish and meat stay vitamin-rich and fresher for longer.
- 5 door trays, including 1x dairy compartment
- 7 safety glass shelves (6 height adjustable)

- .

- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.


#### **Dimension and installation**


#### **Performance and Consumption**

- EU19\_EEK\_D: E
- Total Volume : 289 l
- Net Fridge Volume : 289 l
- Annual Energy Consumption: 150 kWh/a
- Climate Class: SN-ST
- Noise Level : 37 dB , EU19\_Noise emission class\_D: C



### Series 8, Built-in fridge, 177.2 x 55.8 cm, flat hinge KIF81PFE0







#### Maximal permissible weight of the unit fronts


Fitted unit fronts that exceed the permissible weight may cause damage and result in functional impairment of the hinges Å Weight A: Appliance door height including hinges in mm

- B: Undamped hinge, unit front in kg
- C: Damped hinge, unit front in kg
- D: Additional possible load in kg with heavy load kit

| Α         | В  | С  | D         |
|-----------|----|----|-----------|
| 1500-1750 | 22 | 22 |           |
| 720-1400  | 19 | 19 | B+5 / C+5 |
| A1        | 15 | 19 |           |
| A2        | 15 | 19 |           |








measurements in mm

Maximal permissible weight of the unit fronts




Fitted kitchen unit doors that exceed the permissible weight may cause damage and result in functional impairment of the hinges.

| of appliance door | undamped<br>hinge, | damped<br>hinge, |
|-------------------|--------------------|------------------|
| Hinges in mm:     | Door in kg:        | Door in kg:      |
| 1500-1750         | 22                 | 22               |



### measurements in mm Recommended gap dimensions for flat hinges



| F     | R   | X   |
|-------|-----|-----|
| 16-19 | 0-3 | 2.5 |
| 20    | 0-1 | 3   |
|       | 2-3 | 2.5 |
| 21    | 0-1 | 3   |
|       | 2-3 | 2.5 |
| 22    | 0   | 4   |
|       | 1   | 3.5 |
|       | 2-3 | 3   |

The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.