

Series 6, Gas hob, 60 cm, Enamel, Black PCP6A6B90





HEZ298105 Simmer plate HEZ298115 Small pot support

- Four powerful gas burners allow you to cook multiple dishes with a full range BTU performance.
- Stainless steel design: The seamless, one-piece stainless steel design makes cleaning simple
- Biomethane-ready: your gas hob can also be powered with renewable biomethane gas.
- FlameSelect: adjust the gas flame precisely using nine defined levels.
- Continuous cast-iron pan support: for high firmness and stability of cookware.

Appliance type: gas hob w integrated controls
Built-in / Free-standing:
Heating type:Gas
Number of cooking zones:4
Type of control setting devices: sword knobs
Required niche size for installation (HxWxD): 45 x 560-562 x 480-492
mm
Width of the appliance:582 mm
Dimensions:
Dimensions of the packed product (HxWxD): 141 x 651 x 578 mm
Net weight:11.1 kg
Gross weight:
Residual heat indicator: without
Location of control panel:Front
Basic surface material: Enamel
Color of surface:Black
Length electrical supply cord:
EAN code:
Gas connection rating:
Fuse protection:
Voltage:
Frequency:





Series 6, Gas hob, 60 cm, Enamel, Black PCP6A6B90

Design

- Enamel surface, Black
- Cast iron pan supports

Usage convenience

- FlameSelect: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 gas burners:
- Left front: standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: high-speed burner up to 3 KW (depending on gas type)
- Right front: economy burner up to 1 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): $53 \times 582 \times 520$
- Required niche size for installation (HxWxD mm) : $45 \times 560 \times (480 492)$
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.5 KW



Series 6, Gas hob, 60 cm, Enamel, Black PCP6A6B90

