

# Series 6, Gas hob, 75 cm, Stainless steel PCS7A5B90





HEZ211310 Simmer cap
HEZ298105 Simmer plate
HEZ298107 Wok ring
HEZ298115 Small pot support

# The stainless-steel gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

- Dual Control Wok enables you to precisely control flame level by two
- $\bullet$  different flame rings on the same burner.
- Five powerful high-efficiency gas burners allows you to cook multiple dishes with a full range BTU performance.

Appliance type:
Heating type:
Number of cooking zones:
Type of control setting devices:sword knobs Required niche size for installation (HxWxD): 45 x 560-562 x 480-492
mm
Width of the appliance:750 mm
Dimensions:
Dimensions of the packed product (HxWxD): 145 x 793 x 597 mm
Net weight:
Gross weight:
Residual heat indicator: without
Location of control panel: Front
Basic surface material:Stainless steel
Color of surface: Stainless steel
Length electrical supply cord:100.0 cm
EAN code:
Gas connection rating:
Fuse protection:3 A
Voltage:
Frequency: 50; 60 Hz





### Series 6, Gas hob, 75 cm, Stainless steel PCS7A5B90

The stainless-steel gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

#### Design

- Stainless steel surface
- Cast iron pan supports

#### Usage convenience

- FlameSelect: precisely control and adjust the flame in nine defined
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

#### **Burners and power**

- 5 gas burners:
- Including 1 dual control wok burner: use an extra wide power range, separately controlling two flame rings.
- Left: wok burner up to 5 KW (depending on gas type)
- Center front: economy burner up to 1 KW (depending on gas type)
- Center rear: standard burner up to 1.75 KW (depending on gas type)  $\,$
- Right rear: high-speed burner up to 3 KW (depending on gas type)
- Right front: standard burner up to 1.75 KW (depending on gas type)

#### Safety


- Flame failure safety device: prevents unwanted gas flow when flame goes out.

#### Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm):  $53 \times 750 \times 520$
- Required niche size for installation (HxWxD mm) :  $45 \times 560 \times (480 492)$
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 12.5 KW



# Series 6, Gas hob, 75 cm, Stainless steel PCS7A5B90



measurements in mm