

Serie | 4, Gas hob, 60 cm, Stainless steel PGH6B5B60



The gas hob with front-mounted controls: the desired cooking zones can be conveniently operated from the front.

- Wok burner: powerful cooking at up to 3.3 kW
- Continuous cast-iron finish pan supports: for maximum stability.
- Ergonomic control knobs with raised center for precise adjustments.
- Surface colour: elegant stainless-steel design.
- Low profile stainless steel cooking surface is easily accessible and quick to clean.

Technical Data

Product name/family :	gas hob w integrated controls
Construction type :	Built-in
Energy input :	Gas
Total number of positions that can be used at the same time $: 4$	
Type of control setting devices :	sword knobs
Required niche size for installation	on (HxWxD) :
	45 x 560-562 x 480-492
Width of the appliance :	582
Dimensions :	45 x 582 x 520
Dimensions of the packed product (HxWxD) (mm) :	
	141 x 651 x 578
Net weight (kg) :	8.106
Gross weight (kg) :	9.0
Residual heat indicator :	without
Location of control panel :	Hob front
Basic surface material :	Stainless steel
Color of surface :	Stainless steel
Color of frame :	Stainless steel
Approval certificates :	CE, Eurasian, Ukraine
Length of electrical supply cord	(cm): 100
EAN code :	4242002929903
Electrical connection rating (W)	: 1
Gas connection rating (W) :	8000
Current (A) :	3
Voltage (V) :	220-240
Frequency (Hz) :	60; 50





Serie | 4, Gas hob, 60 cm, Stainless steel PGH6B5B60

The gas hob with front-mounted controls: the desired cooking zones can be conveniently operated from the front.

Design

- Stainless steel

Special features

- Design co-ordinated control dials
- Ignition via control dials
- cast iron finish pan supports with rubber feet

Power and size

- 4 gas burners:
- Dual control burner
- 3 gas + wok
- Left rear: Standard burner 1.75 KW
- Right rear: wok burner 3.3 KW
- Left front: standard burner 1.75 KW
- Right front: economy burner 1 KW

Safety Features

- Flame failure safety device
- Pre-set for natural gas. Also usable for Nat gas L/LL G25/20mbar(DE)
 NG H/E 20mbar, E+ 20/25mbar
 Natural gas H 25 mbar (HU)
 Natural gas L 25 mbar (NL)
 Liquid gas G30,31 28-30/37mbar
 Liquid gas 50 mbar
 For the use of these gas types nozzles need to be changed.
 Please check if the required nozzles are included (see Accessories).

Technical information

- Power cord length 100 cm

Accessories

- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service.



Serie | 4, Gas hob, 60 cm, Stainless steel PGH6B5B60

