

## Series 4, Gas hob, 75 cm, Stainless steel **PGQ7B5B90**



HEZ298105 Simmer plate Wok ring

HEZ298108 HEZ298115 Small pot support

# The gas hob with front-mounted controls: the desired cooking zones can be conveniently operated from the front.

• Dual ring burner has a wide range of power from a high heat dual flame down to one small simmer flame.

Appliance type: gas hob w integrated contro	ols
Built-in / Free-standing:	in
Heating type:Ga	
Number of cooking zones:	
Type of control setting devices:sword knob	
Required niche size for installation (HxWxD): 45 x 560-562 x 480-49	
mm	<i></i>
Width of the appliance:	ım
Dimensions:	
Dimensions of the packed product (HxWxD): 168 x 798 x 596 m	
Net weight:	
Gross weight: 14.5 k	_
· · · · · · · · · · · · · · · · · · ·	_
Residual heat indicator: withou	
Location of control panel: From	
Basic surface material:	
Color of surface:	
Length electrical supply cord:	m
EAN code:	30
Gas connection rating:	W
Fuse protection:3	Α
Voltage:	٧
Frequency: 50; 60 H	Hz





## Series 4, Gas hob, 75 cm, Stainless steel PGQ7B5B90

# The gas hob with front-mounted controls: the desired cooking zones can be conveniently operated from the front.

#### Design

- Stainless steel surface
- Cast iron pan supports

## Usage convenience

- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

### **Burners and power**

- 5 gas burners:
- Left front: economy burner up to 1 kW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: wok burner up to 3.3 KW (depending on gas type)
- Right rear: high-speed burner up to 3 KW (depending on gas type)
- Right front: standard burner up to 1.75 KW (depending on gas type)

#### Safety


- Flame failure safety device: prevents unwanted gas flow when flame goes out.

## Installation (gas types & measurements)

- Usable for: NG H/E 20mbar, E+ 20/25mbar
- Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm):  $53 \times 750 \times 520$
- Required niche size for installation (HxWxD mm) :  $45 \times 560 \times (480 492)$
- Min. worktop thickness: 30 mm
- Power cord: 1.5 m
- Connected load: 10.8 KW



## Series 4, Gas hob, 75 cm, Stainless steel PGQ7B5B90



\*\*\* With fitted oven underneath, possibly more; see space requirements for the oven

measurements in mm

