


Series 4, Induction hob, 60 cm, Black, PUE611BF1B





HEZ390090 Wok Set consisting of 3 Items HEZ9ES100 Espresso maker 4 cups HEZ9FE280 Iron pan Ø 18 / 28 cm HEZ9SE030 Set of 2 pots and 1 pan HEZ9SE040 4 pieces Set

HEZ9SE060 6 pieces Set

The Induction hob: Faster than gas and ceramic hobs, induction is easier to clean and more energy efficient.

- Plug & Play: plugs easily into the socket.
- TouchSelect: Selection of the desired cooking zone and easy setting of the desired power level.
- PowerBoost: up to 50% more power for faster heating on your induction hob.
- Restart: restores cooktop settings in case of an unintentional cooktop switch-off.
- Timer with switch-off function: Turns off the assigned cooking zone after the set time.

Appliance type:	n b 4
mm	
Width of the appliance:592 mm	n
Dimensions:51 x 592 x 522 mm	n
Dimensions of the packed product (HxWxD): 126 x 753 x 603 mm	n
Net weight:10.1 kg	g
Gross weight: 12.2 kg	g
Residual heat indicator:Separate	e
Location of control panel:Front	١t
Basic surface material:Ceramic glass	s
Color of surface:Black	k
Length electrical supply cord:110.0 cm	m
EAN code:4242002870526	6
Voltage:	٧
Frequency: 50; 60 Hz	Z





Series 4, Induction hob, 60 cm, Black, PUE611BF1B

The Induction hob: Faster than gas and ceramic hobs, induction is easier to clean and more energy efficient.

Design

- Frameless design
- 60 cm: space for 4 pots or pans.

Flexibility of cooking zones

- Cooking zone front left: 180 mm, 1.8 KW (max. power 3 KW)
- Cooking zone rear left: 180 mm, 1.8 KW (max. power 3 KW)
- Cooking zone rear right: 145 mm, 1.4 KW (max power 2.2 KW)
- Cooking zone front right: 210 mm, 2.2 KW (max. power 3 KW)

Usage convenience

- TouchSelect: control the power with imprinted +/- touch buttons.
- Variable 17-stage power settings for each zone: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Timer for all zones
- -: switches off the cooking zone at the end of the time set (e.g. for boiled eggs).
- Timer shows how long the cooktop is in use
- -: an alarm sounds at the end of the time set (e.g. for pasta).

Time saving & efficiency

- PowerBoost function for all zones
- -: boil water faster thanks to 50% more energy than at the highest standard level.
- QuickStart function: when switching on, the hob automatically selects the cooking zone with cookware (when placed on a zone whilst the hob is off).
- ReStart function: in case of unintentional switch-off, this feature restores all previous settings by switching on the hob again within
- Quick Stop: quickly switch off a cooking zone with one longer touch.

Safetv

- 2 stage residual heat indicator for each zone: indicates which cooking zones are still hot or warm.
- Control panel lock: prevent unintended activation of the hob.
- Main on/off switch: switch off all cooking zones at the touch of a button
- Automatic safety shut off: for safety reasons, heating stops after a preset time if not used.


Installation

- This hob is equipped with a UK 3 pin plug for an easy plug & play installation. The plug limits the maximum power output to 3.7 KW.
 For higher power output, please select a hob without plug and ensure installation is carried out by a qualified electrician.
- Dimensions of the product (HxWxD mm): 51 x 592 x 522
- Required niche size for installation (HxWxD mm) : 51 x 560 x (490 500)
- Min. worktop thickness: 16 mm

- Connected load: 3.7 KW
- Power management options for 16A, 13A or 10A connection: limit the maximum power if needed (depends on fuse protection of electric installation).
- Power cord 1.1 m UK 3 pin plug: plug and play, no electrician required for installation.



Series 4, Induction hob, 60 cm, Black, PUE611BF1B



measurements in mm 51 (B) ≥ 16 (**C**) ≥ 40 (A)


- A: Minimum distance from the hob cut-out to the wall.
 B: Recessed depth
 C: The clearance between the surface of the worktop and the top of the front of the oven must be 30 mm. See space requirements for the oven.


The worktop into which the hob is installed must withstand loads of approx. 60 kg; suitable substructures must be used if required.

D	E	F
585-600	50	≥ 35
> 600	> 50	> 50

① Ventilation gap must be present

All measurements in mm





Measurements in mm