

Serie | 8, Induction hob with integrated ventilation system, 80 cm, surface mount with frame PXX875D34E



Optional accessories

HEZ39050 Wireless temperature sensor for cooktop, HEZ390511 Teppan Yaki (small), HEZ390512 Teppan Yaki (large), HEZ390522 Griddle Plate, HEZ394301 Connecting strip, HEZ9SE030 Set of 2 pots and 1 pan, HEZ381401 Exhaust kit, HEZ381501 Recirculating kit, HEZ381700 Recirculation filter, HEZ390011 Stainless Steel roaster with glas lid, HEZ390012 Steaming Rack for Stainless Steel roaste, HEZ390090 Wok Set consisting of 3 Items, HEZ390210 System pan diameter 15 cm, HEZ390220 System pan diameter 19 cm, HEZ390230 System pan diameter 21cm

The induction hob with integrated ventilation module: combines best induction with best ventilation technology for perfect results.

- **Integrated ventilation module:** extract steam and cooking odours at the source.
- **DirectSelect Premium:** spacious and intuitive touch interface.
- **FlexInduction:** more flexibility on your hob for large pots and pans.
- **PerfectAir sensor:** Automatic control of the hood settings for maximum extractor performance with minimal noise.
- **PerfectCook:** the sensor which can be adjusted, prevents overcooking and boiling over by precise controlling the cooking temperature.

Technical Data

Appliance type:Cooking zone ceramic
 Built-in / Free-standing: Built-in
 Heating type:Electric hob
 Min. required niche size for installation (HxWxD): 198 x 780-780 x 490-500 mm
 Width of the appliance:816 mm
 Dimensions: 198 x 816 x 527 mm
 Dimensions of the packed product (HxWxD): 330 x 760 x 940 mm
 Net weight:28.6 kg
 Gross weight: 34.9 kg
 Residual heat indicator: Separate
 Location of control panel: Front
 Basic surface material: Ceramic glass
 Color of surface:Black, Alu, brushed
 Length electrical supply cord: 110.0 cm
 Sealed Burners: No
 heating with booster:All
 Power of 2nd heating element (kW):3.3 kW
 Number of speed settings:9-stage + intensive
 Max. air extraction: 551 m³/h
 Boost position output recirculating:620.0 m³/h
 Max. air recirculation: 557 m³/h
 Boost position air extraction: 689 m³/h
 Noise level:70 dB(A) re 1 pW
 Odour filter: No
 Air circulation: Convertible
 Grease filter type:Kassette
 Voltage: 220-240 V
 Frequency: 50; 60 Hz
 Delay Shut off modes:30 min



Serie | 8, Induction hob with integrated ventilation system, 80 cm, surface mount with frame PXX875D34E

The induction hob with integrated ventilation module: combines best induction with best ventilation technology for perfect results.

Design

- 816 mm
- Profile trim (front facette with side trim)

Control

- DirectSelect Premium touch control
- PerfectFry sensor with 5 temperature settings
- PerfectCook sensor ready (sensor sold separately)

Special features

- 4 induction cooking zones
- 2 Flex zones
- Variable 17-stage power settings for each zone
- PanBoost
- ReStart function
- QuickStart function
- Electronic display, red
- MoveMode: MoveMode (3 levels)
- Keep warm function
- Timer for all zones
- Timer - shows how long the cooktop is in use
- Count up timer per cooktop

Quickness

- PowerBoost function for all zones

Power and size

- Cooking zones:
 - 1 x Ø 400 x 240 mm, 3.3 KW Induction heating or 2 x Ø 240 mm, 200 mm
- Connected load: 7.4 KW
- Voltage: 220 - 240 V

Safety Features

- Individual energy consumption display
- 2 stage residual heat indicator for each zone
- Automatic pan recognition sensor
- Automatic safety shut off
- Control panel lock
- Freeze function
- Main on/off switch

Technical information

- Min. worktop thickness: 20 mm (Installation in thinner worktops is also possible with the spare part: 626792)
- Cable included
- Length wire connection: 110 cm
- Measurement: (H/B/T) 198 x 816 x 527 mm

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 53.5 kWh/year
- Blower Efficiency Class: A
- Grease Filtering Efficiency Class: B
- Noise min./max. Normal Level: 39/69 dB
- Induction cooktop with integrated downdraft extractor
- Suitable for ducted or re-circulated extraction (Accessory is respectively needed)
- For ducted extraction extraction kit (accessory HEZ381401) needed
- For recirculated extraction cleanAir recirculating kit (accessory HEZ381501) needed
- Fully-automatic extraction functionality with Automatic Air Sensor
- Fully-automatic fan speed level control or optionally manual control by user
- 9 speeds plus 1 intensive
- Automatic 30 minutes after running
- Extraction rate:
 - min. normal setting 169 m3/h
 - max. normal setting 551 m3/h
 - Boost/Intensive setting 689 m3/h
- Noise level in ducted extraction :
 - min. normal setting 42 dB(A) re 1 pW (31 dB(A) re 20 µPa sound pressure)
 - max. normal setting 70 dB(A) re 1 pW (58 dB(A) re 20 µPa sound pressure)
 - Boost/Intensive setting 75 dB(A) re 1 pW (64 dB(A) re 20 µPa sound pressure)
- Performance in re-circulated extraction:
 - min. normal setting 139 m3/h
 - max. normal setting 557 m3/h
 - Boost-/Intensive setting 620 m3/h
- Noise level in re-circulated extraction:
 - min. normal setting 42 dB(A) re 1 pW (31 dB(A) re 20 µPa sound pressure)
 - max. normal setting 73 dB(A) re 1 pW (62 dB(A) re 20 µPa sound pressure)
 - Boost-/Intensive setting 75 dB(A) re 1 pW (62 dB(A) re 20 µPa sound pressure)
- Grease filter efficiency: 90 %
- Odour reduction rate: 85 %
- Large-scale stainless-steel grease filters with 12 layers for high grease filtration efficiency
- Cast-iron air inlet grid, heat resistant, dishwasher safe
- Removable and detachable grease filter and liquid collector unit, dishwasher safe
 - integrated stainless steel grease filters, dishwasher safe
 - condensate and liquid collector unit; ca. 200ml capacity; dishwasher safe
- Liquid spillover safety tank, ca. 2000ml capacity, Twist-off lock, dishwasher safe
- Saturation indicator for cleanAir odour filter

Installation Advice

- Base cupboard width: min. 80 cm.
- Worktop depth: min. 60 cm (with shortened drawers), max. drawer's depth can be used starting with a worktop depth of 70 cm.
- Immersion depth: 19.8 cm



- Modules for ducted extraction or re-circulated extraction must be ordered separately as special accessory.

test

Serie | 8, Induction hob with integrated ventilation system, 80 cm, surface mount with frame PXX875D34E



