

Serie | 2, Free-standing dishwasher, 60 cm, Stainless steel, lacquered SMS25EI00G











Optional accessories

SGZ1010: inlet and outlet hose extention

SMZ5300 : GlassSecure Tray

- ExtraDry: extra drying option for difficult-to-dry loads.
- Glass 40°C: gentle cleaning for your delicate glassware.
- VarioDrawer: 3rd level loading for cutlery and smaller kitchen utensils.
- **Rackmatic:** even more adjustment options and thus maximum flexibility.
- Rackmatic: height-adjustable dishwasher basket for tall items.

Technical Data

Energy Efficiency Class: E

Energy Consumption for 100 cycles Eco Programme: 94 kWh

Maximum number of place settings: 13

The water consumption of the eco programme in liters per cycle:

9.5 l

A ↑ G

Programme duration: 3:30 h

Airborne acoustical noise emissions : 48 dB(A) re 1 pW

Airborne acoustical noise emission class: C

Construction type: Free-standing Height of removable worktop: 30 mm

Dimensions of the product (HxWxD): 845 x 600 x 600 mm

Depth with open door 90 degree: 1155 mm

Adjustable feet: Yes - all

Maximum adjustability feet: 20 mm

Adjustable plinth: No
Net weight: 49.0 kg
Gross weight: 50.3 kg
Connection rating: 2400 W
Fuse protection: 10 A
Voltage: 220-240 V
Frequency: 50; 60 Hz

Length of electrical supply cord: 175 cm

Plug type: GB plug Length inlet hose: 150 cm Length outlet hose: 190 cm EAN code: 4242005028436





Serie | 2, Free-standing dishwasher, 60 cm, Stainless steel, lacquered SMS25EI00G

Performance

- Energy Efficiency Class¹: E
- Energy² / Water³: 94 kWh / 9.5 litres
- Capacity: 13 place settings
- Programme duration⁴: 3:30 (h:min)
- Noise level: 48 dB(A) re 1 pW
- Noise Efficiency Class: C

Programmes/functions

- 5 programmes: Intensive 70 °C, Eco 50 °C, Glass 40 °C, Quick, Pre rinse
- 2 special options: VarioSpeed Plus, Extra Dry

Flexible design elements

- Vario baskets
- VarioDrawer loading of cutlery on 3rd level
- 3 stage Rackmatic height-adjustable top basket
- 2 foldable plate racks in bottom basket
- Upper rack cup shelf

Innovations and technology

- Heat exchanger.
- DosageAssist detergent dispenser
- EcoSilence BLDC drive
- Automatic detergent detection
- Load Sensor

Design features

- Time delay (3, 6 or 24 hours)
- Leak protection system
- LED salt refill indicator, LED rinse aid refill indicator
- Self-cleaning filter system with 3 piece corrugated filter
- Child safety Childproof door lock
- Dimensions (HxWxD): 84.5 x 60 x 60cm
- ¹ Scale of Energy Efficiency Classes from A to G
- ² Energy consumption in kWh per 100 cycles (in programme Eco 50 °C)
- ³ Water consumption in litres per cycle (in programme Eco 50 °C)
- ⁴ Duration of programme Eco 50 °C



Serie | 2, Free-standing dishwasher, 60 cm, Stainless steel, lacquered SMS25EI00G

