

Serie | 8, steamer, White CDG634BW1



The steamer: prepare foods especially gently, retaining the aroma and vitamins.

- **Steam function:** for gentle, healthy food preparation.

Technical data

| | |
|---|-------------------------|
| Color / Material Front : | White |
| Built-in / Free-standing : | Built-in |
| Required niche size for installation (HxWxD) : | 450-455 x 560-568 x 550 |
| Dimensions of the product (mm) : | 455 x 594 x 548 |
| Dimensions of the packed product (HxWxD) (mm) : | 520 x 650 x 710 |
| Control Panel Material : | Glass |
| Door Material : | Glass |
| Net weight (kg) : | 25.023 |
| Approval certificates : | CE, VDE |
| Length electrical supply cord (cm) : | 150 |
| Connection Rating (W) : | 1750 |
| Current (A) : | 10 |
| Voltage (V) : | 220-240 |
| Frequency (Hz) : | 60; 50 |
| Plug type : | Gardy plug w/ earthing |
| Approval certificates : | CE, VDE |



Included accessories

1 x steam container, punched, size L, 1 x steam container, unpunched, size L, 1 x sponge

Serie | 8, steamer, White CDG634BW1

The steamer: prepare foods especially gently, retaining the aroma and vitamins.

Programmes/ Additional Features:

- Compact steamer with 4 heating methods: Steam, Reheat, Prove, defrost
- Cavity volume: 38L

Design:

- Rotary swivel knobs control
- Cavity inner surface: Stainless steel

Key Features:

- Full glass inner door

Design:

- IC6_CBO_61
- Temperature proposal Actual temperature display Heating-up control automatic programmes
- Additional functions: descaling programme autom. boiling point detection
- Automatic programmes
- Number of automatic programmes: 20 PC
- Electronic clock
- Halogen lighting
- Water tank capacity 1.3 l
- Integrated water reservoir that does not require direct water connection
- 455 mm x 594 mm x 548 mm
- Enamel cavity
- Stainless-steel fan
- Info button
- Bar handle

Hook-in racks / rails

- Cavity with shelf support

Accessory:

- 1 x steam container, punched, size L, 1 x steam container, unpunched, size L, 1 x sponge

Safety:

- Childproof lock Automatic switch off Start button door contact switch

Technical Information:

- Length of mains cable: 150 cm
- Total connected load: 1.75kW
- 455 mm x 594 mm x 548 mm
- 455 mm x 594 mm x 548 mm
- Please reference the built-in dimensions provided in the installation drawing
- Triple glass cool touch door (40° C door temperature)