

6,0 kW 220 -240 V
RDH06111



Compact instantaneous hydraulically controlled

- Compact instantaneous hydraulically controlled
- Suggested cable cross-section(mm²): 4 mm²
- Pressurised unit
- With spray regulator to optimize the water spray
- Compact instantaneous hydraulically controlled

Color / Material panel:night blue
 Gross weight: 1.6 kg
 Net weight: 1.6 kg
 Height of the appliance: 235 mm
 Width of the appliance: 144 mm
 Depth: 100 mm
 Dimensions of the packed product (HxWxD): 120 x 170 x 275 mm
 Voltage: 220-240 V
 Heating type:Tubular heater
 Plug type:fixed connection



6,0 kW 220 -240 V RDH06111

Compact instantaneous hydraulically controlled

RDH06111

- Compact instantaneous hydraulically controlled

Equipment

- Suggested cable cross-section(mm²): 4 mm²
- Pressurised unit
- With spray regulator to optimize the water spray
- Compact instantaneous hydraulically controlled
- Operation indicator light
- Hot water rating (38 °C) 3 l/min
- Low switch-on flow rate of 2.3 l/min
- Maximum initial temperature up to 20 °C
- Fixed connection, rating: 6 kW
- Electrical connection 220 - 240 V/ 50 Hz / Fuse 32 A
- Splash-proof standard IP24D
- Dimensions (H x W x D): 23.5 x 14.4 x 10 cm
- Fixing material Wall plugs, Mounting template, Screws

Water pipe connection thread ["]: 21,3 / G1/2A

6,0 kW 220 -240 V
RDH06111

