

**Series 2, Integrated cooker hood, 60 cm, Silver
DEM63AC00B**



Optional accessories

DWZ01M0A0 Standard odor filter (replacement)

Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.

- **Quiet extraction with powerful performance**
- **LED Illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.
- **High extraction rate - for continuously clean air in the kitchen.**
- **Dishwasher safe metal grease filter**
- **3 Power Levels:** Adjust the extraction intensity according to your cooking needs.

Technical Data

Typology: Built-in/Built-under
 Length electrical supply cord: 150 cm
 Height of the appliance: 402 mm
 Minimum distance above an electric hob: 500 mm
 Minimum distance above a gas hob: 650 mm
 Net weight: 10.3 kg
 Type of control: mechanical
 Number of speed settings: 3
 Max. air extraction: 368 m³/h
 Max. air recirculation: 272 m³/h
 Maximum Air flow: 368 m³/h
 Number of lights: 2
 Noise level: 62 dB(A) re 1pW
 Diameter of air outlet: 150 / 120 mm
 Grease filter material: Washable aluminium
 EAN code: 4242005041107
 Connection rating: 126 W
 Fuse protection: 10 A
 Voltage: 220-240 V
 Frequency: 50; 60 Hz
 Plug type: GB plug
 Installation typology: Wall-mounted



Series 2, Integrated cooker hood, 60 cm, Silver DEM63AC00B

Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.

Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 368 m³/h
- Noise max. Normal Level: 62 dB*

Features

- Push button control for extractor speeds and light
- 3 power levels
- Single motor
- 2 x 3W LED
- Colour Temperature: 2700 K
- 2 metal grease filter cassettes
- Installation Installation: Between Cupboards

Design

- Integrated hood
- Push button control
- Mechanical

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction charcoal filter (accessory) needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 62 dB(A) re 1 pW
- Light Intensity: 188 lux
- Electrical cable length 1.5 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating (HxWxD): 402-402 x 599 x 271 mm
- Blower Efficiency Class: E*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 65.7 kWh/year*

Optional accessories

- Recirculating kit DWZ0IM0AO

* In accordance with the EU-Regulation No 65/2014

**Series 2, Integrated cooker hood, 60
cm, Silver
DEM63AC00B**

