

**Serie | 2, built-under cooker hood, 60 cm, Stainless steel
DHU625MGB**

- An impressive extraction rate of 270 m³/h ensures this hood will have your kitchen odour free in no time.
- Halogen lighting provides energy efficient and bright lighting of the hob area.

E



Technical Data

Typology :	Traditional
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Minimum distance above an electric hob :	500
Minimum distance above a gas hob :	650
Net weight (kg) :	8.056
Type of control :	mechanical
Number of speed settings :	3
Maximum output air extraction (m ³ /h) :	270
Maximum output recirculating air (m ³ /h) :	50
Number of lights :	2
Noise level (dB(A) re 1 pW) :	68
Diameter of air outlet (mm) :	120
Grease filter material :	Washable aluminium
EAN code :	4242002497723
Connection Rating (W) :	180
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation typology :	Built-under

Optional accessories

DHZ2400 : Active carbon filter



Serie | 2, built-under cooker hood, 60 cm, Stainless steel DHU625MGB

Design

- 60 cm wide
- Designed for wall mounted installation or suspended beneath a reduced height wall cupboard

Features

- Push button control for extractor speeds and light
- 3 power levels
- 2 x 20W low energy halogen lights
- 2 metal grease filter cassettes

Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591: max. 270 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting; extraction rate: 68 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)

Optional accessories

- Charcoal odour filter DHZ2400