


**Serie | 8, island cooker hood, 90 cm,  
Stainless steel  
DIB091U51B**

**A<sup>+</sup>**



**Optional accessories**

DHZ1231 : Adapter for roof inclination left/right  
 DHZ1241 : Adapter for roof inclination front/back  
 DHZ1246 : Chimney extension 1100 mm  
 DHZ1256 : Chimney extension 1600 mm  
 DHZ5385 : Standard recirculation kit  
 DSZ5201 : CleanAir active carbon filter spare part  
 DSZ6230 : CleanAir Recirculation Kit  
 DZZ0XX0P0 : Long Life odor filter (replacement)

**Stylish island chimney hoods perfectly complement island hob installations.**

- An impressive extraction rate of 1000 m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- **Especially quiet:** high performance at just 46 dB.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.

**Technical Data**

|   |                       |
|---|-----------------------|
| Color chimney :   | Stainless steel       |
| Typology :  | Chimney               |
| Approval certificates :                                   | CE, G-Mark, VDE       |
| Length electrical supply cord (cm) :                      | 130                   |
| Height of the chimney (mm) :                              | 698-878/698-998       |
| Height of product, without chimney (mm) :                 | 46                    |
| Minimum distance above an electric hob :                  | 550                   |
| Minimum distance above a gas hob :                        | 650                   |
| Net weight (kg) :   | 28.317                |
| Type of control :   | Electronic            |
| Number of speed settings :                                | 3-stage + 2 intensive |
| Maximum output air extraction (m <sup>3</sup> /h) :       | 620                   |
| Boost position output recirculating (m <sup>3</sup> /h) : | 480                   |
| Maximum output recirculating air (m <sup>3</sup> /h) :    | 400                   |
| Boost position air extraction (m <sup>3</sup> /h) :       | 1000                  |
| Number of lights :  | 4                     |
| Noise level (dB(A) re 1 pW) :                             | 60                    |
| Diameter of air outlet (mm) :                             | 150 / 120             |
| Grease filter material :                                  | Washable aluminium    |
| EAN code :  | 4242002779584         |
| Connection Rating (W) :                                   | 272                   |
| Current (A) :   | 10                    |
| Voltage (V) :   | 220-240               |
| Frequency (Hz) :  | 50; 60                |
| Plug type :   | GB plug               |
| Installation typology :                                   | Island                |



## **Serie | 8, island cooker hood, 90 cm, Stainless steel DIB091U51B**

**Stylish island chimney hoods perfectly  
complement island hob installations.**

---

### **Key Information**

- Electronic control
- Electronic power level display
- Grease and charcoal filter saturation indicators
- EcoSensor

### **Design**

- 90 cm wide
- Designed for ceiling mounted installation
- Height adjustable chimney sections

### **Features**

- Soft touch button control for extractor speeds and light
- 3 power levels and 2 intensive settings
- Automatic intensive revert
- LED lights
- Softlight dimmer function
- Dimmer function
- Additional noise reduction insulation
- 3 metal grease filter cassettes

### **Performance/technical information**

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591  $\varnothing$  15 cm:  
max. Normal use 620 m<sup>3</sup>/h  
Intensive 1000 m<sup>3</sup>/h
- Maximum extraction rate 1000 m<sup>3</sup>/h (intensive)
- Noise level according to EN 60704-3 and EN 60704-2-13 at  
maximum normal setting: extraction rate: 60 dB (A) re 1pW  
(46 dB (A) re 20  $\mu$ Pa sound pressure)
- Light Intensity: 888 lux
- Colour Temperature: 3500 K
- Energy Efficiency Class: A+ (at a range of energy efficiency  
classes from A+++ to D)
- Average Energy Consumption: 36.9 kWh/year\*
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Noise max. Normal Level: 60 dB\*

\* In accordance with the EU-Regulation No 65/2014

**Serie | 8, island cooker hood, 90 cm,  
Stainless steel  
DIB091U51B**

