

**Series 6, Island cooker hood, 90 cm,
Stainless steel
DIB98JQ50B**



A⁺



Optional accessories

DIZ2CX5C6 Clean Air Plus recirc. kit external, DIZ2FX5D1 Long Life recirculation kit external, DZZ0XX0P0 Long Life odor filter (replacement), DZZ1XX1B6 Clean Air Plus odor filter (replacement), DZZ2CB1B4 Clean Air Standard odor filter (repl.), DHZ1231 Adapter for roof inclination left/right, DHZ1241 Adapter for roof inclination front/back, DHZ1246 Chimney extension 1100 mm, DHZ1251 Extension for mounting kit 500 mm, DHZ1253 Extension for mounting kit 1000 mm, DHZ1256 Chimney extension 1600 mm, DHZ5346 Standard odor filter (replacement), DHZ5385 Standard recirculation kit, DIZ2CB114 Clean Air Standard recirculation kit

Stylish island chimney hoods perfectly complement island hob installations.

- **PerfectAir sensor:** automatic extractor control for high performance with low noise.
- **DirectSelect control:** direct selection of desired settings and light.
- **Extra silent:** the high-performance hood, with minimal noise.
- **EcoSilence Drive™:** the powerful, energy-saving drive for hoods.

Technical Data

Typology:	Island/Ceiling
Length electrical supply cord:	130.0 cm
Height of the chimney:	698-878/698-998 mm
Height of the appliance:	46 mm
Minimum distance above an electric hob:	550 mm
Minimum distance above a gas hob:	650 mm
Net weight:	28.7 kg
Type of control:	Electronic
Number of speed settings:	3-stage + 2 intensive
Max. air extraction:	445 m ³ /h
Boost position output recirculating:	457 m ³ /h
Max. air recirculation:	353 m ³ /h
Boost position air extraction:	867 m ³ /h
Maximum Air flow:	445 m ³ /h
Number of lights:	4
Noise level:	54 dB(A) re 1 pW
Diameter of air outlet:	120 / 150 mm
Grease filter material:	Washable stainless steel
EAN code:	4242005099276
Connection rating:	166 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	50; 60 Hz
Plug type:	GB plug
Installation typology:	Island
Delay Shut off modes:	10 min



Series 6, Island cooker hood, 90 cm, Stainless steel DIB98JQ50B

**Stylish island chimney hoods perfectly
complement island hob installations.**

Key performance features:

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 445 m³/h
 - Intensive 867 m³/h
- Noise max. Normal Level: 54 dB*

Special features

- PerfectAir sensor
- TouchControl with lightline
- 3 power levels and 2 intensive settings
- 4 x 1.5W LED light
- Colour Temperature: 3500 K
- Dimmer function
- Efficient BLDC-technology
- Automatic intensive revert (6mins)
- Automatic after running (10 min)
- 3 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- Additional noise reduction insulation
- easy to clean Inner frame

Design

- Island chimney hood
- Designed for ceiling mounted installation
- TouchControl
- Electronic control
- Efficient BLDC technology

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 max. 445 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 54 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 54 dB(A) re 1 pW
 - Intensive: 69 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 54 dB (A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
 - Extraction rate in recirculation mode: Max. normal use: 353 m³/h
 - Intensive: 457 m³/h
 - Noise level in recirculation mode: Max. normal use: 67 dB(A) re 1 pW
 - Intensive: 71 dB(A) re 1 pW
- Light Intensity: 423 lux
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 898 x 600 mm
- Blower Efficiency Class: A*



- Lighting Efficiency Class: A*

**Series 6, Island cooker hood, 90 cm,
Stainless steel
DIB98JQ50B**

