

**Serie | 8, wall-mounted cooker hood,  
60 cm  
DWB068J50B**



**A+**



**Optional accessories**

DHZ1225 : Chimney extension 1000 mm  
 DHZ1235 : Chimney extension 1500 mm  
 DHZ5326 : Standard odor filter (replacement)  
 DSZ5201 : CleanAir active carbon filter spare part  
 DSZ6200 : CleanAir Recirculation Kit  
 DZZ0XX0P0 : Long Life odor filter (replacement)

**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

- An impressive extraction rate of 760 m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.
- **Especially quiet:** high performance at just 46 dB.

**Technical Data**

Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-908/582-1018
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	15.429
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m <sup>3</sup> /h) :	430
Boost position output recirculating (m <sup>3</sup> /h) :	380.0
Boost position air extraction (m <sup>3</sup> /h) :	760
Number of lights :	2
Noise level (dB(A) re 1 pW) :	60
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable stainless steel
EAN code :	4242002811925
Connection Rating (W) :	166
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation typology :	Wall-mounted



## Serie | 8, wall-mounted cooker hood, 60 cm DWB068J50B

**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

### Key Information

- Electronic control via TouchControl

### Design

- Designed for wall mounted installation
- 60 cm wide
- Brushed steel
- Inner frame

### Features

- TouchControl with lightline
- 3 power levels and 2 intensive settings
- Automatic intensive revert (6mins)
- Automatic after running (10 min)
- 2 x LED lights
- Softlight dimmer function
- Dimmer function
- 2 metal grease filter cassettes
- Removable metal grease filters

### Performance/technical information

- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591  $\varnothing$  15 cm:  
max. Normal use 430 m<sup>3</sup>/h  
Intensive 760 m<sup>3</sup>/h
- Extraction rate exhaust air according to EN 61591:  
max. normal use 430 m<sup>3</sup>/h, intensive 760 m<sup>3</sup>/h
- 
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:  
Max. normal use: 60 dB(A) re 1 pW (46 dB(A) re 20  $\mu$ Pa sound pressure)  
Intensive: 72 dB(A) re 1 pW (58 dB(A) re 20  $\mu$ Pa sound pressure)
- Noise max. Normal Level: 60 dB\*
- Average Energy Consumption: 29.3 kWh/year\*
- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Dimensions exhaust air (HxWxD): 628-954 x 600 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 600 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
809-1139 x 600 x 500 mm
- Diameter pipe  $\varnothing$  150 mm ( $\varnothing$  120 mm enclosed)
- Light Intensity: 745 lux
- Colour Temperature: 3500 K
- Efficient BLDC-technology

### Accessories

- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed

\* In accordance with the EU-Regulation No 65/2014