

**wall-mounted cooker hood, 90 cm,
Stainless steel
DWB09E752B**



Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 740 m³/h ensures this hood will have your kitchen odour free in no time.
- **Especially quiet:** high performance at just 39 dB.
- Halogen lighting provides energy efficient and bright lighting of the hob area.
- Intensive speed setting with revert gives a quick intensive 10 min burst to clear strong odours and then reverts back to the normal setting.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-908/582-1018
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	19.558
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	410
Boost position output recirculating (m ³ /h) :	420
Maximum output recirculating air (m ³ /h) :	320
Boost position air extraction (m ³ /h) :	740
Number of lights :	3
Noise level (dB(A) re 1 pW) :	55
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable stainless steel
EAN code :	4242002625034
Connection Rating (W) :	280
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation typology :	Wall-mounted

Optional accessories

- DHZ1223 : Chimney extension 1000 mm
- DHZ1233 : Chimney extension 1500 mm
- DHZ5345 : Standard recirculation kit
- DHZ9550 : Brushed steel back panel
- DHZ9551 : Brushed steel back panel
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6240 : CleanAir Recirculation Kit



wall-mounted cooker hood, 90 cm, Stainless steel DWB09E752B

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Key Information

- Electronic control
- Electronic power level display

Design

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections
- Brushed steel canopy and chimney section

Features

- Soft touch button control for extractor speeds and light
- 3 power levels & intensive setting
- Automatic intensive revert
- 3 x 20W low energy halogen lights
-
- 3 metal grease filter cassettes

Performance/technical information

- Easy installation system
- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 420 m³/h
Intensive 740 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13
exhaust air:
Max. normal use: 53 dB(A) re 1 pW (39 dB(A) re 20 μ Pa sound pressure)
Intensive: 66 dB(A) re 1 pW (52 dB(A) re 20 μ Pa sound pressure)
- Extractor hose 120mm
- Recirculating kit DHZ5345
- Dimensions recirculating with CleanAir module (HxWxD):
654 x 900 x 500 mm - mounting with outer chimney
774-1104 x 900 x 500 mm - mounting with telescopic chimney