

**Serie | 4, wall-mounted cooker hood,
90 cm, clear glass
DWG96DM50B**



Optional accessories

DHZ1225 : Chimney extension 1000 mm
DHZ1235 : Chimney extension 1500 mm
DHZ9550 : Brushed steel back panel
DHZ9551 : Brushed steel back panel
DWZ0DX0A0 : Standard odor filter (replacement)
DWZ0DX0U0 : Standard recirculation kit
DWZ0XX0J0 : Long Life recirculation kit
DWZ1DX1I6 : Clean Air Plus recirculation kit
DWZ1FX5C6 : Clean Air Plus recirc. kit external
DZZ0XX0P0 : Long Life odor filter (replacement)
DZZ1XX1B6 : Clean Air Plus odor filter (replacement)

**Hood with glass design: performance
combined with straight glass design
matching your kitchen.**

- **Intensive speed setting:** removes strong kitchen odours quickly and effectively.

Technical Data

Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	576-906/576-998
Height of product, without chimney (mm) :	59
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	17.374
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	388
Boost position output recirculating (m ³ /h) :	364.0
Maximum output recirculating air (m ³ /h) :	303
Boost position air extraction (m ³ /h) :	636
Number of lights :	2
Noise level (dB(A) re 1 pW) :	61
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242005035144
Connection Rating (W) :	220
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation typology :	Wall-mounted



4 242005 035144

**Serie | 4, wall-mounted cooker hood, 90 cm, clear glass
DWG96DM50B**

Hood with glass design: performance combined with straight glass design matching your kitchen.

Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 Ø 15 cm: max. Normal use 388 m³/h Intensive 636 m³/h
- Noise max. Normal Level: 61 dB*

Features

- TouchControl with Electronic display
- Electronic display
- 3 power levels & intensive setting
- 2 x 1.5W LED light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- Designed for wall mounted installation

Design

- Chimney extractor hood
- TouchControl
- Electronic control

Performance/technical information


- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 636 m³/h
- Extraction rate in recirculation mode: Max. normal use: 303 m³/h Intensive: 364 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 61 dB(A) re 1 pW Intensive: 69 dB(A) re 1 pW
- Noise levels in recirculation mode: Max. normal use: 71 dB(A) re 1 pW Intensive: 75 dB(A) re 1 pW
- Power rating: 220 W
- Light Intensity: 214 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 525 mm
- Dimensions recirculating (HxWxD): 635-1075 x 900 x 525 mm
- Dimensions recirculating with CleanAir module (HxWxD): 703 x 900 x 525 mm - mounting with outer chimney 833-1163 x 900 x 525 mm - mounting with telescopic chimney
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 43 kWh/year*

Optional accessories

- Recirculating kit DHZ1225


** In accordance with the EU-Regulation No 65/2014*

**Serie | 4, wall-mounted cooker hood, 90 cm,
clear glass
DWG96DM50B**




- (1) Exhaust air
- (2) Circulated air
- (3) Air outlet – slots for exhaust air to be mounted facing down

measurements in mm




If a back panel is used, the design of the appliance must be considered.

measurements in mm



measurements in mm



measurements in mm