

**wall-mounted cooker hood, 90 cm,  
clear glass  
DWK09E850B**



**Optional accessories**

DHZ1225 : Chimney extension 1000 mm  
 DHZ1235 : Chimney extension 1500 mm  
 DHZ5326 : Standard odor filter (replacement)  
 DSZ5201 : CleanAir active carbon filter spare part  
 DSZ6200 : CleanAir Recirculation Kit



**Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.**

- An impressive extraction rate of 700 m<sup>3</sup>/h ensures this hood will have your kitchen odour free in no time.
- Halogen lighting provides energy efficient and bright lighting of the hob area.
- Intensive speed setting with revert gives a quick intensive 10 min burst to clear strong odours and then reverts back to the normal setting.

**Technical Data**

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-920/582-1030
Height of product, without chimney (mm) :	387
Minimum distance above an electric hob :	400
Minimum distance above a gas hob :	500
Net weight (kg) :	27.384
Type of control :	Electronic
Maximum output air extraction (m <sup>3</sup> /h) :	500
Boost position output recirculating (m <sup>3</sup> /h) :	380
Maximum output recirculating air (m <sup>3</sup> /h) :	330
Boost position air extraction (m <sup>3</sup> /h) :	700
Number of lights :	2
Noise level (dB(A) re 1 pW) :	61
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
EAN code :	4242002643816
Connection Rating (W) :	300
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation typology :	Wall-mounted



**wall-mounted cooker hood, 90 cm, clear  
glass  
DWK09E850B**

**Wall mounted chimney hoods add style and  
sophistication to the kitchen and give you  
complete freedom in your kitchen planning.**

---

**Key Information**

- Electronic control
- Electronic power level display

**Design**

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections
- Brushed steel

**Features**

- Soft touch button control for extractor speeds and light
- 3 power levels & intensive setting
- Automatic intensive revert
- 2 x 20W low energy halogen lights
- 2 metal grease filter cassettes

**Performance/technical information**

- Easy installation system
- Suitable for ducted or recirculating operation
- Extraction rate according to EN 61591  $\varnothing$  15 cm:  
max. Normal use 510 m<sup>3</sup>/h  
Intensive 700 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13  
exhaust air:  
Max. normal use: 62 dB(A) re 1 pW (48 dB(A) re 20  $\mu$ Pa sound  
pressure)  
Intensive: 68 dB(A) re 1 pW (54 dB(A) re 20  $\mu$ Pa sound  
pressure)
- Intensive: 68 dB (A) re 1 pW (54 dB (A) re 20  $\mu$ Pa sound  
pressure)
- Extractor hose 120mm
- Recirculating kit DHZ5325
- Dimensions recirculating with CleanAir module (HxWxD):  
853 x 900 x 441 mm - mounting with outer chimney  
973-1303 x 900 x 441 mm - mounting with telescopic chimney

**wall-mounted cooker hood, 90 cm, clear glass**  
**DWK09E850B**

